PROCTOR RAP PlastiGrip Washer

Plastic washer for Building Wraps & External Insulation

Product Description

The ProctorWrap PlastiGrip is a 45mm diameter polypropylene washer designed for the attachment of rigid insulation and building wraps.

Applications

Installation

Durabilty

The ProctorWrap Plasti-Grip Washer is not suitable in environments where it will be exposed to long term direct sunlight or UV after installation.

Screws should only be tightened sufficiently to apply clamping force around the perimeter of the washer - to avoid distortion of the product or substrate around the washer, do not over tighten. The use of corrosion resistant screws is recommended.

Although the ProctorWrap Plasti-Grip Washer can be exposed during construction while the wrap or insulation is exposed, the washers are not recommended for applications where they would remains permanently exposed to direct sunlight.

If the product is damaged in any way, such as cracked as a result of over tightening during use it should be replaced before completion of the project.

Benefits

- Flat base for flush mounting.
- Flexible perimeter reduces tearing of facer.
- Wide 45mm diameter and flexible perimeter reduces wrap tearing risk.
- Tested in conjunction with ProctorPassive RS-IT, ProctorWrap CW & ProctorWrap HTS to provide fixing span tables.
- Keyholes for basecoat bonding when used with rendered insulation.
- Use with multiple fasteners to attach rigid insulation, building wraps or fiberglass lath.



| Properties | Nominal value |
|---------------|-------------------------|
| Diameter | 45mm |
| Height | 5mm |
| Packaging | 1000 washers per carton |
| Carton Size | 255 x 205 x 205mm |
| Carton Weight | 2.4 kg |

ACOUSTIC INSULATION CONSTRUCTION MEMBRANES GEOSYNTHETIC ENGINEERING PASSIVE VENTILATION RAINSCREEN SYSTEMS THERMAL INSULATION

Proctor Group Australia a division of Dynamic Composite Technologies Pty. Ltd.

- т 02 8788 9555
- technical@proctorgroup.com.au Е W
 - www.proctorgroup.com.au

