



VAPOR SHIELD

Vapor Protection • Sound Isolation

VOC Free • Radiant Heat Compatible

Premium Floor Underlayment

Specifications

Foam Material	Irradiated Cross-Linked PolyEthelene
Vapor Barrier	PolyEthelene Film
Thickness	2mm (0.079 inches)
Roll Width	1000mm (3' 3 3/8")
Roll Length	19m (62' 4 1/8")
IIC Rating	69
STC Rating	61
Density	67kg/m ³
Square Ft / Roll	200
RoHS Compliant	Yes
Radiant Heat Compatible	Yes
Thermal Conductivity	0.032w/m ^o K
VOC Free	Yes

Installation

Prior to installation, make sure that your subfloor is completely free of debris and has been adequately levelled.

1. Unroll with the label-side facing down. Lay with the film extension on the side that you will attach the next strip of underlayment to.
2. Leave an up-stand of 2-3 inches up any walls. You will trim this off when the flooring installation is complete.
3. For subsequent rows, overlap the adhesive strip onto the film extension from the previously laid underlayment piece. When aligned, remove the adhesive cover and press firmly to adhere the two strips of underlayment together.
4. After all the underlayment and flooring has been laid, trim off the excess up-stand of underlayment from around the edges and proceed to install any baseboards or mouldings.



Easiklip Floors Inc.
8280 Manitoba St.
Vancouver BC, Canada
V5X 3A2

www.easiklip.com
855-539-5547

SKU: IXPE-2MM-2021
EASIKLIP Vapor Shield Premium Floor Underlayment

IXPE Foam Underlayment
19m² / 204.5 ft²
Made in China

Gross: 5.73 lbs (2.6kg)
Net: 5.73 lbs (2.6kg)

01/05/2021