

FACTOR™

LED LIGHTING



Model	FACTOR 1x1	FACTOR 1.5x1.5	FACTOR 1x2	FACTOR 2x2	FACTOR 1x4
SKU	LED-V2000ASVL-Fctr1x1	LED-V3000ASVL-Fctr1.5x1.5	LED-V4000ASVL-Fctr1x2	LED-V5000ASVL-Fctr2x2	LED-V6000ASVL-Fctr1x4
CRI	≥96	≥96	≥96	≥96	≥96
TLCI	≥93	≥93	≥93	≥93	≥93
Color Balance	3200k - 5600k (±300)	3200k - 5600k (±300)	3200k - 5600k (±300)	3200k - 5600k (±300)	3200k - 5600k (±300)
Lumens	3,200 lm	6,500 lm	6,300 lm	10,000 lm	8,600 lm
EV	9.9 Δ EV	11 Δ EV	10.8 Δ EV	11.5 Δ EV	11.2 Δ EV
Power Draw	100W / 24-30V	200W / 24-30V	200W / 24-30V	300W / 24-30V	300W / 24-30V
Battery Type	V-Lock Brick x2	V-Lock Brick x2	V-Lock Brick x2	V-Lock Brick x2	V-Lock Brick x2
Beam Angle	120°	120°	120°	120°	120°
Dimension	13.8 x 13.8 in (35 x 35 cm)	19.7 x 19.7 in (50 x 50 cm)	13.8 x 23.6 in (35 x 60 cm)	25.6 x 25.6 in (65 x 65 cm)	13.8 x 45.3 in (35 x 115 cm)
Weight	12.9 lbs (5.85 kg)	20.7 lbs (9.4 kg)	17.8 lbs (8.05 kg)	34.9 lbs (15.85 kg)	33.6 lbs (15.25 kg)
Add-Ons	50° Honeycomb Grid Padded Carrying Case	50° Honeycomb Grid Padded Carrying Case	50° Honeycomb Grid Padded Carrying Case	50° Honeycomb Grid Padded Carrying Case	50° Honeycomb Grid Padded Carrying Case



Model	FACTOR Jupiter12	FACTOR Jupiter18	FACTOR Jupiter24
SKU	LED-VR1200ASVL-Jptr12	LED-VR2500ASVL-Jptr18	LED-VR4500ASVL-Jptr24
CRI	≥96	≥96	≥96
TLCI	≥93	≥93	≥93
Color Balance	3200k - 5600k (±300)	3200k - 5600k (±300)	3200k - 5600k (±300)
Lumens	1,850 lm	3,350 lm	6,600 lm
EV	9.1 Δ EV	9.9 Δ EV	10.9 Δ EV
Power Draw	55W / 15V	100W / 15V	200W / 24-30V
Battery Type	V-Lock Brick x1	V-Lock Brick x1	V-Lock Brick x2
Beam Angle	120°	120°	120°
Dimension	12.6 in (32 cm)	18.1 in (46 cm)	24.8 in (63 cm)
Weight	8.6 lbs (3.9 kg)	13.9 lbs (6.3 kg)	21.8 lbs (9.9 kg)
Add-Ons	50° Honeycomb Grid Creative Shape Masks Padded Carrying Case	50° Honeycomb Grid Creative Shape Masks Padded Carrying Case	50° Honeycomb Grid Creative Shape Masks Padded Carrying Case

