

SIBARCO

THE ONE YOU CAN RELY ON



T43R

**Little giant
Care label printer
Total solution**



Specifications



CPU AND MEMORY

- CPU : 32-bit CPU
- MEMORY : 8MB SDRAM, 4MB Flash ROM

PRINT

- RESOLUTION : 300 dpi
- PRINT MODE : Thermal Transfer
- PRINT SPEED : 1" to 3" ips
- MAX. PRINT LENGTH : 50 inches
- PRINT WIDTH : 3.15" (80mm)
- BARCODE :
 - 1D : Code39, Code93, Code128 UCC, Code128 auto, Codabar, EAN8, EAN13, Interleaved 2 of 5, UCC/EAN 128, UPC A, UPC E, UPC Interleaved 2 of 5
 - 2D : Data Matrix, MaxiCode, PDF417, QR code
- FONT :
 - 5 internal expandable bitmap fonts (alpha-numeric)
 - 2 internal expandable bitmap fonts (numeric only)
 - Downloadable soft font
 - 4 directions : 0, 90, 180, 270 degrees
- IMAGE : PCX, Direct binary graphic

SENSOR TYPE : Moveable reflective sensor, Cover open sensor, ribbon sensor

CONTROL PANEL : 4 function keys, 4 status LED light, 1 error LED light

CARE LABEL

- WIDTH : 0.59"~3.15"(15mm~80mm)
- MEDIA ROLL DIAMETER : ID-3" (76.2mm)/OD-Max. 10"(254mm)
- MEDIA THICKNESS : 0.0059" (0.15mm)
- MEDIA TYPE : Care label, Satin label

RIBBON

- WIDTH : 1.0" (25.4mm) to 4.3" (110mm)
- RIBBON ROLL DIAMETER : ID- 0.5"/OD-1.535"
- RIBBON LENGTH : Max. length-110M
- RIBBON TYPE : Wax, wax/resin, resin

INTERFACE : USB A, USB B, RS-232, Ethernet 10/100Mbps (option)

POWER : Switching power adapter- Input : 100 to 240V/Output : 24V

OPTION : Ethernet module

OPERATING TEMPERATURE : 5°C to 45°C(40°F to 112.9°F)

PRINTER DIMENSION : Width : 200(W) x 263(L) x 188(H) mm, Weight : 3.7KG

CERTIFICATION : CE, FCC class B, CCC, CB



Specifications subject to change without notice. Copyright 2010. Sbarco Technology Co., Ltd.
All right reserved. SBARCO is a registered trade mark of Sbarco Technology Co., Ltd.

- Total solution for care label printer
- 300 dpi printing resolution
- Exclusive cutter, stacker and label holder
- No shifting, no sticking during printing label
- Free professional label design software

- 1cm min. cutting length
- Cutter for Nylon and Satin
- LCD monitor for standalone
- SD support up to 4G
- Free symbols

SBARCO Technology Co., Ltd.

Add : 4F., No.115, Lide St., JhongHe Dist., 23556, New Taipei City, Taiwan

Tel : 886-2-3234-3098 Fax : 886-2-3234-1700 Website : www.sbarcotech.com