

WINGCO®

Quality Generators Since 1927

WL18000VE



Engine:

- Briggs and Stratton Vanguard
- CARB and EPA certified engine (specify CARB when ordering)
- V-Twin OHV
- Cast iron cylinder sleeves
- Vanguard is the proven industry standard for BIG BLOCK™ engine power, performance, and reliability. For the most challenging applications-where downtime is not an option-this BIG BLOCK™ has been engineered to deliver the dependability people need to get a lot more done in less time throughout the workday

Generator End:

- 100% copper windings - longer life and improved motor starting
- Dampers, skewed rotors for <5% harmonic distortion
- 425 Volt heavy duty capacitors
- 25 Amp 1200 volt diodes
- Varistors provide an extra layer of protection for the rotor diodes by intervening at 360 VAC and 470 VDC

Components:

- 15 gallon steel fuel tank
- Heavy duty 1 1/4 inch 13 gauge tubular steel cradle
- Powder coat paint on all steel for an incredibly durable finish
- Optional 4 wheel industrial dolly kit with a fold down handle
- Solid full width steel axles
- Standard lifting eye
- Electric start
- Generous receptacle package
- All 120 volt receptacles GFCI protected, the 120/240 volt 14-60 receptacle is compatible with building distribution panels
- NEMA 5-20 GFCI receptacles fitted with UL listed metal covers for protection against the elements
- Square D Circuit Breakers-Industry's leading trip reaction time at 1/60th of a second
- Industry's only trip indicator system (Red-Visi Trip)
- USFS spark arrestors
- Battery not included, battery required: 12V BCI group 26 rated 500 CCA or larger



Big Dog Series

SURGE WATTS	18000
CONTINUOUS WATTS	15000
AMPS	125/62.5
VOLTS	120/240
VOLTAGE REGULATION	+/-5%
FREQUENCY REGULATION	+/-3%
ENGINE BRAND	B & S VANGUARD
ENGINE MODEL	MODEL 54
ENGINE STARTER	ELECTRIC
ENGINE SPEED	3600 RPM
DISPLACEMENT	895 CC
ENGINE CYLINDERS	V-TWIN
LOW OIL PROTECTION	STANDARD
dBA AT 7 METERS	TBD
FUEL TANK	15 GAL
FULL LOAD RUN TIME	7 HOURS
FUEL USE (GAL/HR)	1.6
FULL PRESSURE OIL LUBE WITH SPIN-ON FILTER	STANDARD
MOTOR STARTING (CODE G)	6 HP
4 WHEEL DOLLY KIT	OPTIONAL
MAIN CIRCUIT BREAKER	60 AMP, 240 VOLT
OUR METER	STANDARD
120 VOLT RECEPTACLES	(6) NEMA 5-20R GFCI
	(1) NEMA L5-20 GFCI
120/240 VOLT RECEPTACLE	(1) NEMA 14-60R 60 AMP
240 VOLT RECEPTACLE	(1) NEMA L6-30R 30 AMP
DIMENSIONS (LxWxH)	40" x 27" x 26.7"
NET WEIGHT	416
SHIP WEIGHT	489
WARRANTY (ENG/GEN)	3 YRS / 2 YRS

Toll Free: 1-800-733-2112
sales@wincogen.com

www.wincogen.com

225 South Cordova Avenue
Le Center MN, 56057