

# T9 REV

For excavators 2.5-12.0 ton



## HYDRAULIC MULCHERS

T9 70 REV

T9 90 G2 REV

T9 MZ90 REV

T9 MZ105 REV



**HF3**

Ø max 8 cm

*standard equipment*



**KF3**

Ø max 6 cm

T9 FR90 REV

T9 FR105 REV



**HF7 - HF8**

Ø max 12 cm



T9 DF90 REV

T9 DF105 REV



**HF14**

Ø max 25 cm

*standard equipment*



**HF15**

Ø max 20 cm

**MZ**











**FR**



**DF**



Model	 (ton)	 (cm)	 (LxAxH cm)	 Kg	Motor displacement	 (L/min)	 bar (min-max)		Rotor	
T9 70 REV	2.5-4.0	70	85x80x60	180	11-16	20-30	170-220	2	helical	10
T9 90 G2 REV	4.0-5.0	90	105x80x60	245	16	30	170-220	2	helical	14
T9 MZ90 REV	5.0-8.0	90	105x80x60	260	22-27-34	40-50-60	170-220	3	helical	14
T9 MZ105 REV	6.0-12.0	105	125x80x60	310	22-27-34-44-51	40-50-60 80-90	200-220	3	helical	16
T9 FR90 REV	6.0-8.0	90	105x80x60	300	27-34-44-51	50-60 80-90	200-220	3	4 lines	18
T9 FR105 REV	6.0-12.0	105	125x80x60	360	27-34-44-51	50-60 80-90	200-220	3	4 lines	22
T9 DF90 REV	6.0-12.0	90	105x80x60	400	27-34-44-51	50-60 80-90	200-220	3	helical	24
T9 DF105 REV	6.0-12.0	105	125x80x60	490	27-34-44-51	50-60 80-90	200-220	3	helical	27

### TECHNICAL FEATURES AND STANDARD EQUIPMENT

- MZ Helicoidal Rotor with hammers austempered and cutting blade interchangeable.
- FR Forestal rotor wood flanged with 360° rotating hammer.
- DF Forestal rotor fixed teeth.
- Toothed high-performance V-belts transmission.
- Internally reinforced with inside double-case body with interspace.
- Protective belts-cover.
- Shearing symmetric head, for a faster working by the excavator rotation.
- Input and output mouths completely identical, adjustable
- Adjustable hood, fully openable for higher cutting capacity.
- Side skids adjustable on 3 positions to change the height of the cut.
- Inside Rotor Supports with "labyrinth" for the protection of the bearings by the impurities.
- Double Row spherical adjustable bearings of 1st quality.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation.
- Cast iron gear motor.
- Accident prevention chains protections according to EC directives.

### ACCESSORIES

- 1 - Mounting hitch & pins 1.2-4.0 ton.
- 1 - Mounting hitch & pins 4.1-8.0 ton.
- 1 - Mounting hitch & pins 8.1-12.0 ton.
- 2 - Kit hoses Lg. 2 meters 70/90G2.
- 2 - Kit hoses Lg. 2 meters MZ/FR/DF.
- 3 - Feeler roller.
- 4 - Self-levelling support (+40kg).
- 5 - Hydraulic rotation device (not self-levelling support).
- 6 - Valves block deduction, only anticavitation.



1



3



4



5