

S5

For skid steer loader 50-90 hp

HYDRAULIC MULCHERS

S5 MZ160

S5 MZ180

S5 MZ200











HF16
Ø max 8 cm

standard equipment



KF3
Ø max 6 cm



Model	 (hp)	 (cm)	 (LxAxH cm)	 Kg	Motor displacement	 (L/min)	 bar (min-max)		Rotor	
S5 MZ160	50-90	160	182x120x110	890	27-34-44-51	60-80 100-120	200-220	4	4 lines	18
S5 MZ180	50-90	180	202x120x110	930	27-34-44-51	60-80 100-120	200-220	4	4 lines	20
S5 MZ200	50-90	200	222x120x110	970	27-34-44-51	60-80 100-120	200-220	4	4 lines	22

TECHNICAL FEATURES AND STANDARD EQUIPMENT

- Floating self levelling universal hitch.
- MZ Helicoidal Rotor with hammers austempered and cutting blade interchangeable.
- Mechanical side shift S5 MZ180, MZ200.
- Toothed high-performance V-belts transmission.
- Internally reinforced with inside double-case body with interspace.
- Protective belts-cover.
- Inside Rotor Supports with "labyrinth" for the protection of the bearings by the impurities.
- Bearings of 1st quality.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation.
- Cast iron gear motor.
- Accident prevention protections according to EC directives.

ACCESSORIES

- 1 - Price reduction for fixed type mount plate.
- 2 - Hydraulic side shift.
- 3 - Diverter valve, to operate the hydraulic side shift S5 MZ180, MZ 200.
- 4 - Kit hoses Lg.3 meters.
- 5 - Piston motor.
- 6 - Hitch coupler for articulated backhoe-loader, backhoe loader, telescopic.