

T echnical Data (at 230V/50Hz)



Model	Power (KW)	Current (A)	Speed (r/min)	Eff. (%)	Power Factor (CosΦ)	T _{st} /T _n (Times)	T _{max} /T _n (Times)	Starting Current (A)	Run Capacitor (μF/V)	Noise dB(A)	W.T (Kg)
TPC 5612	0.09	0.80	2740	54	0.91	0.69	1.8	2.5	4μF/450V	67	2.8
TPC 5622	0.12	0.90	2760	60	0.93	0.69	1.8	3.5	6μF/450V	67	3.05
TPC 5632	0.18	1.40	2760	62	0.93	0.55	1.8	4.5	8μF/450V	70	3.5
TPC 6312	0.18	1.40	2760	62	0.93	0.55	1.8	4.5	8μF/450V	70	4.1
TPC 6322	0.25	1.70	2780	66	0.93	0.55	1.8	6	10μF/450V	70	4.5
TPC 6332	0.37	2.50	2780	67	0.93	0.45	1.65	8	12μF/450V	75	5.25
TPC 711-2	0.37	2.60	2640	66	0.94	0.72	1.65	8	14μF/450V	75	6.1
TPC 712-2	0.55	3.60	2760	71	0.95	0.7	1.8	14	20μF/450V	75	7.7
TPC 801-2	0.75	4.50	2735	73	0.98	0.68	1.75	16	25μF/450V	75	10.3
TPC 802-2	1.10	6.60	2720	74	0.98	0.65	1.8	23	35μF/450V	78	11.6
TPC 803-2	1.50	9.20	2730	74	0.98	0.65	1.8	31	50μF/450V	78	13.6
TPC 90S-2	1.50	8.50	2755	76	0.98	0.65	1.8	31	50μF/450V	80	14.6
TPC 90L-2	2.20	12.30	2765	77	0.98	0.65	1.8	51	70μF/450V	80	17.8
TPC 100L-2	3.00	16.90	2765	77	0.99	0.55	1.75	64	90μF/450V	83	23.7
TPC 5614	0.06	0.60	1360	50	0.94	0.75	1.75	2	4μF/450V	63	3.3
TPC 5624	0.09	0.80	1360	52	0.94	0.6	1.75	3	6μF/451V	63	3.6
TPC 5634	0.12	1.30	1370	52	0.92	0.6	1.75	3	8μF/452V	65	4.1
TPC 6314	0.12	1.30	1370	52	0.92	0.6	1.75	3	8μF/453V	65	4.45
TPC 6324	0.18	1.50	1370	54	0.94	0.6	1.6	4	10μF/450V	65	5.05
TPC 6334	0.25	2.00	1370	58	0.95	0.6	1.6	5	12μF/450V	65	5.4
TPC 711-4	0.25	2.00	1320	56	0.94	0.75	1.6	5	14μF/450V	65	6.2
TPC 712-4	0.37	2.90	1325	58	0.94	0.7	1.55	7	20μF/450V	68	7.3
TPC 801-4	0.55	3.90	1340	64	0.94	0.7	1.7	11	25μF/450V	73	10.1
TPC 802-4	0.75	5.30	1340	64	0.94	0.7	1.75	15	35μF/450V	73	11.4
TPC 90S-4	1.10	7.00	1355	72	0.95	0.68	1.8	22	50μF/450V	75	14.4
TPC 90L-4	1.50	9.30	1360	74	0.95	0.68	1.8	32	50μF/450V	78	17.5
TPC 100L1-4	2.20	12.60	1390	78	0.97	0.48	1.75	49	70μF/450V	80	24.5
TPC 100L2-4	3.00	16.50	1380	79	0.99	0.45	1.6	61	90μF/450V	80	32
TPC 6316	0.09	0.92	900	46	0.92	0.8	1.45	2	8μF/464V	63	5.1
TPC 6326	0.12	1.05	900	54	0.92	0.75	1.45	3	11μF/465V	63	6
TPC 7116	0.18	1.55	900	55	0.92	0.7	1.5	4	16μF/466V	68	6.3
TPC 7126	0.25	2.07	900	57	0.92	0.68	1.5	5	20μF/467V	68	7.6
TPC 8016	0.37	2.82	900	62	0.92	0.68	1.6	8	25μF/468V	68	9
TPC 8026	0.55	4.08	900	63	0.93	0.68	1.6	14	30μF/469V	70	11.6
TPC 90S6	0.75	5.20	900	66	0.95	0.65	1.6	16	40μF/470V	70	13.5
TPC 90L6	1.10	7.51	900	67	0.95	0.62	1.6	25	50μF/471V	70	16.2