

Safety Data Sheet

EOT-16

Complies with OSHA's Hazard Communication Standard 29 CFR 1910.1200.

Preparation: June 17, 2008
Review / Revision: May 2014

1. IDENTIFICATION

Part No. and Description: EOT-16, Break-In Zinc Lube

Product Code: 1604

Manufacturer: Pro-Blend Motorsports
1110 Fairchild Road
Winston-Salem, NC 27105
336-767-1027 or 800-535-5053

Distributor: Goodson Tools & Supplies
156 Galewski Drive
Winona, MN 55987
507-452-1830 or 800-533-8010

Emergency Phone: 800-924-6804 (24 hours)

2. HAZARDOUS INGREDIENTS

SECTION 1910 * 1000 Subpart Z - Toxic Air Contaminants

29 CFR OSHA CODE

DOT 49 CFR 172.101 - Table of Hazardous Materials

EPA 40 CFR 302.4 - CERCLA Hazardous Substance List

Carcinogenic Listing: NONE

HMIS Ratings: HEALTH 1 FIRE 1 REACTIVITY 1

3. PHYSICAL DATA

Boiling Point: 325° F

Specific Gravity: 1.05 (9.2 lbs./gal.)

Vapor Pressure: NA

Melting Point: Not Determined

Vapor Density: Heavier than Air

Volatile: 100%

Solubility in Water: 0%

Appearance & Odor: Thin Amber liquid with Petroleum Odor

4. FIRE AND EXPLOSION HAZARD

Flash Point: 480° F

Flammable Limits: Non Flammable

Extinguishing Media: Fires involving this product are extremely unlikely, however, should one occur, extinguish using Water Fog, Foam, Dry Chemical, Water Spray, CO2.

Special Fire Fighting Procedures and Precautions: Stored containers should be cooled to prevent pressure build up. At extreme temperatures, this product may produce harmful byproducts of combustion. SCBA is necessary for firefighters.

Unusual Fire and Explosion Hazards: Combustible

5. REACTIVITY DATA

Stability: Stable

Hazardous Polymerization: Will not occur.

Hazardous Decomposition Products: Combustible byproducts

Conditions to Avoid: Open flame, extreme heat.

Materials to Avoid: Strong alkalis

6. HEALTH HAZARD DATA

Signs and Symptoms of Exposure:

Eyes: May produce mild irritation.

Dermal: May produce mild irritation.

Inhalation: NA

Ingestion: Not expected to produce toxic effects when ingested.

Emergency and First Aid Procedures:

Eyes: Flush eyes with large amounts of water.

Dermal: Wash with soap and water.

Inhalation: Remove to fresh air.

Ingestion: Not expected to produce toxic results if accidentally ingested in small amounts.

7. PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled: Shut off leak source and contain spill. Prevent material from entering sewers or waterways. Absorbent Material and pads can be used.

Waste Disposal Method: In accordance with Federal, State, and Local laws.

STORAGE: To prevent discoloring of this product, do not store in temperatures above 130° F, or in freezing temperatures.

8. CONTROL MEASURES

Respiratory Protection: Not required under normal use. NIOSH approved Air respirator in areas of high misting or spraying.

Ventilation: Adequate.

Protective Gloves: Impermeable gloves.

Eye Protection: Goggles or face shield.

Hygienic Practices: Use good personal hygiene practices. Wash hands with soap before eating, drinking, smoking or use of toilet facilities. Oil soaked clothing should be promptly removed and laundered before reuse. Discard oil soaked leather goods.

9. DISCLAIMER

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third person proximately caused by the material if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in the use of this material.

REFERENCES:

Code of Regulations - DOT

Code of Regulations - EPA

Code of Regulations - OSHA

NIOSH/OSHA Guidelines for Chemical Hazards