

USD-MD50 Ultra Sonic Detergent Instructions

GOODSON

Tools and Supplies for Engine Builders

156 Galewski Drive • P.O. Box 847 • Winona, MN 55987-0847

Toll-Free 1-800-533-8010 • Local 507-452-1830 • www.goodson.com

USD-MD50

Please read instructions before using.

HMIS HAZARD RATING

Health	1
Flammability	0
Reactivity	0
PPE	8

Directions

Product must be diluted with water before use. For light soil, mix Ultra Sonic Detergent at 1:20 with water. For heavy-duty cleaning, use Ultra Sonic Detergent at 1:10. Determine the proper ratio based on the volume of the tank. The minimum recommended concentration for cleaning aluminum is 5.0% (v/v) to insure that adequate corrosion protection is provided.

Pour water into tank, add product and agitate. Heat solution from 140° to 170°F. Immerse parts in tank and soak until soil is removed. After cleaning, remove parts, rinse and allow to air dry.

CAUTION:

KEEP OUT OF REACH OF CHILDREN

May cause eye irritation. Prolonged contact may cause skin irritation. Rubber gloves recommended for prolonged handling.

First Aid:

Eyes: Flush with large amounts of water for 15 minutes, lifting upper and lower lids occasionally. Get medical attention.

Skin: Wash with mild soap and water. Remove contaminated clothing and laundry before reuse.

Ingestion: If conscious, dilute by giving two glasses of water. Call physician or poison control center immediately.

Right to know ingredients: Water (CAS#7732-18-5), NJ TSR #80100366-5001P, Sodium Tripolyphosphate (CAS#7758-29-4), NJ TSR #80100366-5000P, NJ TSR #80100366-5002P