

If you have questions concerning the operation of this Whistler product please call customer technical service:

1-800-531-0004

Hours:

Monday - Friday

9:00 am - 5:00 pm EST

INTRODUCTION

Dear Whistler Owner,

For many of us, a vehicle is more than just transportation. It can be a mobile office, communications or entertainment center, or simply an expression of our personality. Whistler Corporation recognizes this and has created a selection of products we call "Enhanced Driving Tools". These products are designed to make the time you spend in your vehicle more productive, more fulfilling, safer, or just simply more fun. Our mission is to provide products that improve your driving experience though keeping you...

IN TOUCH • IN COMFORT • IN CONTROL

Your new Whistler 1570/1575 laser/radar detector detects all radar, laser and safety radar systems, plus offers Whistler's exclusive Safe Driving System™. This comprehensive safety system detects the Safety Warning System™ keeping you informed of road hazards and adverse weather. Plus, Whistler's unique Stay Alert™ feature tests driver's alertness on long solo trips. Whistler's 1570/1575 also offers a digital display with safety message icons to keep you informed while you drive.

To fully acquaint yourself with the operation of the Whistler 1570/1575 and to better understand the differences between detecting radar, laser and safety radar signals, we recommend reading this entire manual.

Enjoy the Whistler 1570/1575 and please drive safely.

Sincerely,


WHISTLER CORPORATION

TABLE OF CONTENTS

Topic	Page
Model Features Summary	3 - 5
Installation	6 - 8
<ul style="list-style-type: none">• Mounting Guidelines• Dash/Visor/Windshield Mounting• Power Connection And Fuse Replacement	
Operation	9 - 15
<ul style="list-style-type: none">• Power On And Self-Test• Memory/Beep Confirmation• Audio Level Adjustment• Auto Quiet/Mute Modes• City Modes• Dim/Dark Mode• Stay Alert• Option Select Mode• Teach/Tutorial Mode• Auxiliary Jack	
Radar, Laser And VG-2 Alerts	16 - 19
<ul style="list-style-type: none">• Speed Radar Audio/Visual Alerts• Pulse Protection®• Safety Radar Audio/Visual Alerts• Laser Audio/Visual Alerts• VG-2 Audio/Visual Alerts• Alert Priority• Reset Features/Care Maintenance	
Troubleshooting Guide	20
Are Detectors Legal?	21
Speed Monitoring Technologies	22 - 23
<ul style="list-style-type: none">• Radar Facts• Laser Facts• Other Speed Detection Systems• Radar Detector Detectors	
Warranty Information	24 - 26
Specifications	27
Accessories	28

WHISTLER FEATURES

Whistler 1570/1575



Whistler's ergonomic and user-friendly design provides a new level of operating convenience. Special features include:

1. Bracket Release Button - Provides quick and easy release of the mounting bracket.

2. Power Jack - Provides connection for the power cord.

3. Speaker - Provides distinct audio warnings for X, K, Ka band radar, safety radar, laser, VG-2 and Stay Alert.

4. Power/Dim/Dark Button  Turns unit on/off and engages Dim/Dark modes (press and hold for 2 seconds).

5. Volume Up/Down Buttons   - Adjust volume up or down.

6. High Visibility LCD Display - Provides distinct visual confirmation of signals detected, signal strength, and indicates engaged modes of operation.

7. Mute/Menu Button  - Pressing MUTE before a signal is detected engages Auto Quiet Mode which automatically reduces


WHISTLER FEATURES

the audio level after the initial warning to a low audio level setting. Pressing MUTE during a radar/laser encounter silences audio alerts, while allowing visual alerts to keep you informed.

8. CITY/CITY 1 Button  - Reduces the annoyance of false alerts typically encountered in urban driving areas.

9. External Speaker/Voice Box Jack - Provides easy connection of the **WHISTLER EXTERNAL SPEAKER, Part Number 202180** or **WHISTLER MOTORCYCLE HELMET SPEAKER, Part Number 202698** or **WHISTLER VOICE BOX Part Number 202797** (see page 28). **Any other device may damage the unit and void your warranty.**

10. Laser Antenna (Rear) - An integrated optical waveguide provides superior detection of laser signals transmitted from behind.



11. Laser Antenna (Front) - High gain optical lens array provides increased sensitivity and field of view for leading-edge laser detection.

12. Radar Antenna - Compact, high-efficiency antenna receives radar signals.

13. Mounting Bracket Location - Slot holds mounting bracket firmly.

WHISTLER FEATURES

Accessories

Accessories included are highly functional and easy to use.

Coiled Power Cord (1570) Coiled and Straight Power Cords with Modular Plug (1575) - Connects to the unit's power jack and your vehicle's lighter socket.

Windshield Bracket - Allows installation of unit on your vehicle's windshield.

Visor Bracket (1575 only)

Velcro® Fasteners - Designed to secure the unit on a level dashboard.


Mounting Guidelines

- To maximize visibility of the display, particularly during periods of bright sunlight, we recommend mounting your detector on the visor or high on the windshield, if possible, above the rear view mirror. This "eye level" mounting position is preferred as it will ensure visibility at any time day or night.
- Do not mount your unit behind wipers, ornaments, mirrored sunscreens, etc. These obstructions have metal surfaces which can affect radar and laser signals and reduce critical warning time. (Regular tinted glass does not affect reception.)
- Some newer windshields have an Instaclear™ or Electriclear™ type coating, which affect radar signals. Consult your dealer or the owner's manual supplied with your vehicle to determine if your windshield has this coating.
- Avoid placing unit in direct contact with windshield.
- To reduce the possibility of theft, conceal your unit when not in use.

Windshield Mounting

- Install the two suction cups and rubber bumper onto the bracket by fitting them into their holes.
- Press the suction cups onto the windshield at the location you have chosen.
- Slide the detector onto the bracket until it locks into place.
- If necessary, the unit may be leveled by bending the windshield bracket. Press the bracket release button and remove the detector before bending.


INSTALLATION



IMPORTANT: Some newer cars have a plastic safety coating on the inside of the windshield. The windshield bracket may leave permanent marks on this type of surface. To find out if your vehicle has this type of windshield, check the owner's manual or ask your dealer. We recommend that you do not leave the suction cup bracket on the window in direct sunlight. If the detector is removed, this may cause blistering of the dash in some vehicles.

Dash Mounting

- Make sure the mounting location you have chosen is relatively level and is clean and dry. Clean with isopropyl alcohol if necessary to remove any waxes or polishes.
- Separate the Velcro® fastener strips. Peel the paper backing off each strip and adhere one piece to the dash and the other piece to the bottom of the unit, taking care **not to cover the serial number**.





Be careful not to place the Velcro® over the unit's serial number. If the Velcro® is removed, the serial number may be pulled off the unit. Units without serial numbers are not covered under warranty.

INSTALLATION

Visor Mounting (optional accessory)

- Slide the visor bracket into the bracket mounting slot.
- Clip the visor bracket onto the visor making sure it is relatively level and has a clear view of the road.




Power Connection

- Plug the small end of the power cord into the unit's power jack.
- Plug the large end into the vehicle's cigarette lighter.

Fuse Replacement

The lighter socket plug is equipped with a replaceable 2 amp 3AG fuse located behind the silver tip. To replace the fuse, carefully unscrew the tip of the plug. (**IMPORTANT:** Unscrew slowly. The tip contains a spring which may fly out when disassembling.) Insert the new fuse with the spring and screw on the tip. **With use, screw cap on plug may loosen. Retighten occasionally.**




Unscrew the tip of the lighter socket plug carefully when replacing the 2 amp fuse.

OPERATION

Power On And Self-Test

Each time your Whistler detector is turned on, an automatic self-test sequence confirms that the speaker and visual displays are functional and displays the engaged features.

- Press  (Power) or apply Power. Display reads:



- Press  or remove power to turn unit off.

Memory/Beep Confirmation


All features selected (except Stay Alert) are retained in memory. Each time a button is pressed one beep confirms feature "on", two beeps confirm feature "off".

Audio Level Adjustment

The audio levels can be adjusted high to low, or low to high, in four steps: (1) is the lowest audio level, (4) the highest.

- Press Volume  to increase audio level.
- Press Volume  to decrease audio level.


As audio level is adjusted, beeps are provided and the display indicates volume level. Example:



Auto Quiet Mode

Auto Quiet reduces the selected audio level to a level (1) approximately 5 seconds after a radar or safety radar signal is detected. The audio alert for any new signal within 20 seconds will resume at level (1). Auto Quiet does not affect VG-2 or laser alerts.

- Press  (Mute/Menu) (before a signal is detected) to engage Auto Quiet. Display reads:



- Once the Auto Quiet mode is engaged, you may cancel the audio alarm by pressing .
- Press  (when the unit is not alarming) to cancel Auto Quiet mode.

OPERATION

Mute Mode

Mute cancels audio during an alert and any new alert within 20 seconds. After 20 seconds, approximately 2 beeps are provided on any new alert and then unit remains quiet.

- Press  to cancel the audio.
- Press  a second time during an alert to restore the standard audio alert pattern or by turning the unit off then on.

City/City 1 Mode

Whistler's two-stage City Modes are designed to reduce the annoyance of automatic door openers, intrusion alarms and other devices which share frequencies with police radar.

- Press  (City) to engage City. Display reads:



CITY

- Pressing  a second time engages City 1. Display reads:



CITY 1

- Pressing  (City) a third time cancels City and City 1. Display reads:



HIGHWAY

In City Mode, weak speed/safety radar signals give an initial alarm of two beeps, and then remains quiet unless the signal becomes very strong. When the signal strength increases, two additional beeps are provided. In City 1 Mode, only the X band sensitivity is lowered. If Auto Quiet is engaged and the unit receives a strong X

OPERATION

band signal, the unit performs the Auto Quiet feature. City Modes do not change the audio alert for Laser or VG-2.


Dim/Dark Mode

Dim/Dark Mode reduces the illumination of the display.

- Press and hold  (Power) for 2 seconds to reduce illumination to a Dim setting. Display reads:

 DIM

- Pressing and holding  for 2 seconds a second time reduces illumination to a dimmer setting. Display reads:

 DARK


Dim or dark can be engaged during an alert. In Dark Mode, the display goes dark for as long as a signal is being detected and for 20 seconds after, then the display returns to the dimmer setting.

- Pressing and holding  for 2 seconds a third time restores full illumination to the display.

Stay Alert Feature

The Stay Alert Feature is designed to test a driver's alertness. To engage (when unit is not alarming):

- Press and hold  (City) for 2 seconds. Display reads:

 RU ALERT

Within 30-60 seconds two beeps are sounded; to show alertness, the driver must press the   (Volume),  (City) or  (Mute) button within 3-5 seconds. If the button is pressed

OPERATION

within 3-5 seconds, the cycle is repeated.

If a button was not pressed within 3-5 seconds alarm sounds and the display reads:



GET REST

- Press  (Power) to exit.

WARNING!!! Stay Alert is NOT intended as a substitute for adequate rest. You should NOT operate a vehicle if you are drowsy. During extended periods of vehicle operation, you should take frequent breaks. Improper reliance on the Stay Alert feature may result in vehicle damage, personal injury or death. **NEVER OPERATE A VEHICLE IF YOU ARE DROWSY.**

OPERATION

Option Select Mode

Entering Option Select Mode Tone Select, Voice Box, Abbreviated Power Up Sequence, VG-2 Mode, and External Speaker Mode may be engaged or disengaged. When selecting options, the ,  or  must be pressed within 20 seconds or options mode will automatically be exited. To enter:


Press  :	Display Reads:	To Change, Press	Option:
For 2 Seconds	TONE 3	 or 	Tone 1, 2, or 3 (3 different X, K, Ka patterns)
2nd time	TEST YES	 = YES  = NO	X, K, Ka Audio tones 1 beep during Power Up
3rd time	VG2 OFF	 = ON  = OFF	Turns VG-2 On Turns VG-2 Off (Factory default)
4th time	VOICE OFF	 = ON  = OFF	Aux Jack set for Whistler Voice Box Part #202797 Aux Jack set for Whistler External Speaker Part #202180 or 202698

Press  anytime to exit.

Teach/Tutorial Mode

Provides simulated alerts for each type of signal.

- Press  (City) and  (Mute) simultaneously and release. Display reads:



City and Mute modes can also be accessed while Teach/Tutorial mode is engaged.

- Press  to exit.


External Speaker/Voice Box Jack

Allows you to use a **WHISTLER EXTERNAL SPEAKER**, Part Number 202180, **WHISTLER MOTORCYCLE HELMET SPEAKER**, Part Number 202698 or **WHISTLER VOICE BOX**, Part Number 202797 (see page 28). **Any other device may damage the unit and void your warranty.** If you engage mute or auto quiet modes, this will disengage audio through the Auxiliary Jack.

RADAR ALERTS

Speed Radar Audio/Visual Alerts

When X, K or Ka is detected the band ID and signal strength is displayed. The audio alert is continuous and has a geiger counter-like pattern. The faster the beep the closer the radar source. Example:



Pulse Protection®

When a pulse type signal (instant on strong signal) is detected an urgent 3 second audio warning is sounded and the display reads:

The word 'PULSE' is displayed in a pixelated font within a rounded rectangular border.


After 3 seconds standard alert pattern continues.

SAFETY RADAR ALERTS

Safety Warning System displays over 60 text messages. When Safety Radar is detected the audio alert is geiger counter-like.

Safety Warning System Text

Example: Poor Road Surface:



Note: Safety Warning System consists of 60 text messages. See insert for full description and abbreviations.

LASER/VG-2 ALERTS

Laser Audio/Visual Alerts


When a laser signal is detected the word "Laser" and signal strength is displayed, the audio alert is continuous for a minimum of 3 seconds. Example:



The more "■" the closer the laser source.

VG-2 Audio/Visual Alerts

When a VG-2 signal is detected, the detector "hides" its own radiated signal and becomes undetectable by the VG-2.



Text message confirms detection of VG-2.

Every 30 seconds, the detector checks for a VG-2 signal. If a VG-2 signal is detected, the unit continues to hide and repeats the VG-2 alert. If no signal is detected, two beeps are provided, indicating an "all clear" condition. During VG-2 Alert X, K, and Ka band signals cannot be received.

Alert Priority

When two or more signals are received at the same time, the alert priority is:

1. Laser
2. VG-2
3. Speed Radar
4. Safety Radar

Example:

If X band is alerting, then suddenly VG-2 is detected, the VG-2 warning will override the X band alert.

Reset Features

All user features can be reset to factory set positions.

- Remove Power from unit.
 - Press and hold  (Power) and  (Mute).
 - Apply power to the unit.
 - Wait for 2 beeps.
 - Release  and . Unit is now reset.
1. Audio to level (4).
 2. Display reads Highway.
 3. Dim/Dark Mode to full illumination of display.
 4. Auto Quiet Mode OFF.
 5. VG-2 Detection Mode OFF.
 6. External Speaker ON (voice off).
 7. Full Power Up sequence.
 8. Default TONE 3.
 9. Unit ON or OFF.

Care And Maintenance

During the summer months, avoid prolonged exposure to direct sunlight by removing your unit from the dash when your vehicle is parked for an extended period of time.

Do not spray water, cleaners or polishes directly onto the unit. The spray may penetrate through the openings and damage the unit. Also, do not use any abrasive cleaners on the unit's exterior.

TROUBLESHOOTING GUIDE

Your Whistler detector is expertly engineered and designed to exacting quality standards to provide you with reliable, trouble-free operation. If your unit has been correctly installed following the guidelines in this manual, but is not operating optimally, please refer to the troubleshooting guide below.

PROBLEM: No display or audio.

- Check fuse in Whistler plug; replace if necessary with a 2 amp 3AG type.
- Check fuse for lighter socket; replace if necessary.
- Make sure lighter socket is clean.

PROBLEM: Unit alarms when vehicle hits bumps.

- Check for loose lighter socket; tighten and clean.
- Check connections at both ends of power cord. Substitute another cord to determine if cord is defective. Return defective cord to the factory.

PROBLEM: Unit alarms when using vehicle equipment or electrical accessories (brakes, power mirrors/windows, directionals, horn, etc.).

- Vehicle's electrical system, including battery and alternator, may have electrical noise. Install a filter capacitor (470mfd. 25 volt or larger capacitance value) on the back of the lighter socket.

PROBLEM: Audio alerts are not loud enough.

- Cancel Auto Quiet Mode or City Mode.
- Check audio level setting (see page 11).

If difficulties occur which cannot be solved by information in this Troubleshooting Guide, please call Whistler Customer Technical Service at 1-800-531-0004 before returning your unit for service.

ARE DETECTORS LEGAL?

In Most States YES!

Laser detectors are completely legal in every state when used in automobiles or light trucks (under 10,000 lbs.). Similarly, when used in automobiles or light trucks, radar detectors are legal in almost every state. Exceptions are Virginia and Washington, D.C., which have local regulations restricting the use of radar receivers in any vehicle.

Concerning trucks over 10,000 lbs., the Federal Highway Administration (FHWA) issued a regulation, effective January, 1994 which prohibits radar and laser detector use in these types of vehicles nationally.

Because of legal and legislative efforts underway to repeal the regulation, and because enforcement varies from state to state, we recommend contacting the Radio Association Defending Airwave Rights (R.A.D.A.R.) for the most current information concerning the status and enforcement of the FHWA regulation in areas where you travel. RADAR can be reached at:

Telephone: (513)667-5472

FAX: (513)667-3178

Prior to the FHWA regulation, laws existed in the state of New York restricting the use of radar detectors in trucks over 18,000 lbs. and in Illinois in trucks over 26,000 lbs.

Radar Facts

A radar gun operates by transmitting radio waves at certain frequencies which reflect off objects and are then picked up by the radar gun's receiving section. When a radar beam reflects off a moving target, a measurable frequency shift occurs. The radar unit converts this shift into miles per hour to determine your vehicle's speed.

Currently, the FCC (Federal Communications Commission) permits operation of traffic radar guns at X Band (10.500 - 10.550 GHz), K Band (24.050 - 24.250 GHz), and Ka Band (33.400 - 36.000 GHz).

Laser Facts

It's well documented that many radar guns cannot reliably provide the speed of a targeted vehicle that is traveling in a group of vehicles. In contrast, a laser gun can target a specific vehicle out of a line of traffic and determine its speed. The advantage of laser over radar in terms of target identification is the result of the laser gun's narrow beam. A radar transmission can cover more than a four-lane highway at a distance of 1,000 feet, compared with a laser transmission which covers about 6 feet at the same distance.

For best protection, keep these points in mind:

- Because your vehicle's license plate or headlights are the laser gun's primary targets, mounting your Whistler detector on the dashboard can improve laser detection at short range.
- Do not follow closely behind any vehicle you cannot see through. If you can't see past a vehicle ahead of you, chances are your detector won't either.
- The receiving range of your laser detector will not be the same as a radar detector. Laser guns are most often used at short range.

Other Speed Detection Systems

Several techniques other than radar or laser are used to measure vehicle speeds. When these methods are being used, no detector can provide a warning. These techniques include:

- Pacing - A patrol car drives behind you and matches your driving speed.
- Vascar/Aircraft - The time it takes a vehicle to travel a known distance is measured.

Radar Detector Detectors

The Interceptor VG-2, or simply VG-2, is a microwave receiver used by police to detect signals radiated by the local oscillator of a radar detector. Because its purpose is to identify persons driving with radar detectors, the VG-2 is known as a "radar detector detector".

The VG-2 is the primary tool used by the police to identify radar detector equipped vehicles. If caught, drivers risk losing their radar detector and receiving a fine. In addition, instant-on radar is almost always used in combination with a VG-2, leaving unsuspecting motorists vulnerable to receiving two tickets — one potentially for speeding, the other for possession of a detector.

Having a radar detector capable of detecting the VG-2 alerts you to the presence of a speed trap and preserves your radar detector investment.

WARRANTY INFORMATION

Consumer Warranty

Your Whistler detector is warranted to the original purchaser for a period of one year for the 1570 (two years for the 1575) from the date of original purchase against all defects in materials and workmanship. This limited warranty is void if the unit is abused, modified, installed improperly, if the housing has been removed, or if the serial number is missing. There are no express warranties covering this product other than those set forth in this warranty. All express or implied warranties for this product are limited to one year for the 1570, two years for the 1575. Whistler is not liable for damages of any type arising from the use, misuse, or operation of this product.

Service Under Warranty

During the warranty period, defective units will be repaired or replaced (with the same or a comparable model), at Whistler's option, without charge to the purchaser when returned pre-paid, with dated proof of purchase to the address below. Units returned without dated proof of purchase will be handled as described in section "Service Out Of Warranty." Due to the specialized equipment necessary for testing a radar/laser receiver, there are no authorized service stations for Whistler brand detectors other than the factory.

When returning a unit for service under warranty, please follow these instructions:

1. Ship the unit in the original carton or in a suitable sturdy equivalent, fully insured, with return receipt requested, and shipping charges prepaid to:

Whistler CTS
16 Elizabeth Drive
Chelmsford, MA 01824

WARRANTY INFORMATION

IMPORTANT: Whistler will not assume responsibility for loss or damage incurred in shipping. Therefore, please ship your unit insured with return receipt requested.

2. Include with your unit the following information, clearly printed:

- Your name and street address (for shipping via UPS), and a daytime telephone number. (No P.O. Box please.)
- A detailed description of the problem (e.g., "Unit performs self-test but does not respond to radar").
- A copy of your dated proof of purchase or bill of sale.

3. Be certain your unit is returned with its serial number. For reference, please write your unit's serial number in the following space: s/n _____.

Units without serial numbers are not covered under warranty.

IMPORTANT: To validate that your unit is within the warranty period, make sure you keep a copy of your dated proof of purchase.

WARRANTY INFORMATION

Service Out Of Warranty

Units will be repaired at "out of warranty" service rates when:

- The unit's original warranty has expired.
- Dated proof of purchase is not supplied.
- The unit has been returned without its serial number.
- The unit has been abused, modified, installed improperly, or had its housing removed.

The minimum out of warranty service fee for your Whistler detector is \$55.00 (U.S.). If you require out of warranty service, please return your unit as outlined in the section "Service Under Warranty" along with a certified check or money order for \$55.00. Payment may also be made by MasterCard or VISA; personal checks are not accepted. In the event repairs cannot be covered by the minimum \$55.00 service fee, you will be contacted by a Whistler technical service specialist who will outline options available to you. If you elect not to have your unit repaired/replaced, it will be returned to you along with your certified check or money order.

IMPORTANT: When returning your unit for service, be certain to include a daytime telephone number.

Customer Service

If you have questions concerning the operation of your Whistler detector, or require service during or after the warranty period, please call Customer Technical Service at 1-800-531-0004. Representatives are available to answer your questions Monday - Friday from 9:00 a.m. to 5:00 p.m. (EST).

SPECIFICATIONS

- **Dimensions:** 1.1"H x 2.7"W x 4.6"L
- **Weight:** 6.5 oz.
- **Laser Wavelength Detection Range:**
905 ± 50 nanometers (nm)
- **Radar Frequencies:**
10.500 - 10.550 GHz (X Band)
24.050 - 24.250 GHz (K Band)
33.400 - 36.000 GHz (Ka Superwideband)
- **Operating Temperature Range:**
-20° C to +80° C (-4° F to +176° F)
- **Power Requirements:**
Operational 12 to 15 volts DC, 200mA nominal

One or more U.S. patents apply: #4,315,261; #5,146,227; #5,379,456. Other patents pending.

Specifications are subject to change without notice.

ACCESSORIES

The following accessories are available through Whistler retailers or can be ordered directly from Whistler by calling 1-800-531-0004.

Order Code	Description	Price
202138	Visor Bracket	\$6.95
202139	Windshield Bracket	\$9.95
206294	*Modular Lighter Plug (Requires 206550 or 206551)	\$7.95
206553	Coiled Power Cord (7")	\$15.95
206552	Straight Power Cord (5')	\$14.95
206550	*Modular Straight Power Cord (5') (Requires 206294)	\$6.95
206551	*Modular Coiled Power Cord (7') (Requires 206294)	\$7.95
206879	Velcro®	\$1.95
206880	Hardwire Kit (10') for wiring to fuse box)	\$9.95
201998	Travel Case	\$9.95
202180	External Speaker	\$19.95
202698	Motorcycle Helmet Speaker	\$19.95
202797	Voice Box	\$49.95

*Modular: interconnecting pieces cord and plug.

Shipping and handling (per order) \$3.00

Massachusetts residents please add applicable sales tax. Prices are subject to change without notice.

ACCESSORY ORDER FORM

PLEASE SHIP TO:

Name _____

Street _____

City _____ State _____ Zip _____

Telephone Number (_____) _____

Order Code/Description	Quantity	Total Price
		\$
Subtotal		
Sales Tax (if Applicable)		
Shipping and Handling		\$ 3.00
Total Enclosed		\$

SEND ORDER FORM WITH CERTIFIED CHECK OR MONEY ORDER TO:

Whistler CTS
16 Elizabeth Drive
Chelmsford, MA 01824

IF PAYING BY MASTERCARD OR VISA PLEASE PROVIDE:

Type Of Card _____ MasterCard _____ VISA

Name On Card _____

Card Number _____

Expiration Date _____

Cardholder's Signature _____