The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

AeroShell Oil Diesel Ultra

Version 1.7		Revision Date 04.08.2020	Print Date 22.10.2020
SECTION 1. PRODUCT AND COM	MP	ANY IDENTIFICATION	
Product name	:	AeroShell Oil Diesel Ultra	
Product code	:	001D7346	
Manufacturer or supplier's of Supplier Telephone Telefax Emergency telephone	:	ails Petroleum Logistics Unit 2, 4 Glover Street, Ngauranga, Wellington, 6035, New Zealand 04 233 6180 0800 428 383	
number		nical and restrictions on use	
Recommended use	:	Synthetic lubricating oil for aircraft diese details consult the AeroShell Book on v	-
Restrictions on use	:	This product must be used, handled an accordance with the requirements of th manufacturer's manuals, bulletins and o	e equipment

SECTION 2. HAZARDS IDENTIFICATION

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. Not classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2017., Not classified as Dangerous Goods for transport, according to NZS 5433:2012 Transport of Dangerous Goods on Land.

Hazard classification

GHS Classification

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements	
Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

AeroShell Oil Diesel Ultra

Version 1.7	Revision Date 04.08.2020	Print Date 22.10.2020
Precautionary statements	:	
	Prevention:	
	No precautionary phrases.	
	Response:	
	No precautionary phrases.	
	No precadionary prirases.	
	Storage:	
	No precautionary phrases.	
	Disposal:	
	No precautionary phrases.	

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	: Mixture
Chemical nature	 Synthetic base oil and additives. Highly refined mineral oil. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. The highly refined mineral oil is only present as additive diluent.
	 * contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9, 68649-12-7, 151006-60-9, 163149-28-8.

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	Asp. Tox.1; H304	0 - 90

For explanation of abbreviations see section 16.

SECTION 4. FIRST-AID MEASURES

If inhaled

: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

AeroShell Oil Diesel Ultra

Version 1.7	Revision Date 04.08.2020	Print Date 22.10.2020
In case of skin contact	: Remove contaminated clothing. F water and follow by washing with If persistent irritation occurs, obta	soap if available.
In case of eye contact	 Flush eye with copious quantities Remove contact lenses, if preser rinsing. If persistent irritation occurs, obta 	nt and easy to do. Continue
If swallowed	: In general no treatment is necess are swallowed, however, get med	, ,
Most important symptoms and effects, both acute and delayed	: Oil acne/folliculitis signs and sym of black pustules and spots on th Ingestion may result in nausea, v	e skin of exposed areas.
Protection of first-aiders	: When administering first aid, ens appropriate personal protective e incident, injury and surroundings.	quipment according to the
Notes to physician	: Treat symptomatically.	

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during firefighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

AeroShell Oil Diesel Ultra

Version 1.7	Revision Date 04.08.2020	Print Date 22.10.2020
Personal precautions, protective equipment and emergency procedures	: Avoid contact with skin and eyes.	
Environmental precautions	: Use appropriate containment to avo contamination. Prevent from spread ditches or rivers by using sand, earl barriers.	ling or entering drains,
	Local authorities should be advised cannot be contained.	if significant spillages
Methods and materials for containment and cleaning up	: Slippery when spilt. Avoid accident Prevent from spreading by making a or other containment material. Reclaim liquid directly or in an abso Soak up residue with an absorbent suitable material and dispose of pro	a barrier with sand, earth orbent. such as clay, sand or other
Additional advice	: For guidance on selection of persor see Section 8 of this Safety Data SI For guidance on disposal of spilled this Safety Data Sheet.	neet.

SECTION 7. HANDLING AND STORAGE

General Precautions :	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling :	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Avoidance of contact :	Strong oxidising agents.
Product Transfer :	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Storage	
Other data :	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
	Store at ambient temperature.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

AeroShell Oil Diesel Ultra

Version 1.7	Revision Date 04.08.2020	Print Date 22.10.2020
Packaging material	: Suitable material: For containers or steel or high density polyethylene. Unsuitable material: PVC.	container linings, use mild
Container Advice	: Polyethylene containers should not temperatures because of possible ri	

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	WES-TWA (Mist)	5 mg/m3	NZ OEL
	Further informa vapour.	ation: Sampled b	by a method that does	s not collect
Oil mist, mineral	Not Assigned	WES-STEL (Mist)	10 mg/m3	NZ OEL
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures :	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:
------------------------	---

AeroShell Oil Diesel Ultra

Version 1.7	Revision Date 04.08.2020	Print Date 22.10.2020
	Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.	
	General Information: Define procedures for safe handling an controls.	id maintenance of
	Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle.	
	Always observe good personal hygiene washing hands after handling the mate drinking, and/or smoking. Routinely wa protective equipment to remove contan contaminated clothing and footwear that	rial and before eating, ash work clothing and ninants. Discard
	Practice good housekeeping.	

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection	 No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].
Hand protection	
	Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice

AeroShell Oil Diesel Ultra

sion 1.7	Revision Date 04.08.2020	Print Date 22.10.2020
	from glove suppliers. Contaminate replaced. Personal hygiene is a ke care. Gloves must only be worn or gloves, hands should be washed a Application of a non-perfumed mo	ey element of effective hand n clean hands. After using and dried thoroughly.
	For continuous contact we recommended to the set of the	40 minutes with preference gloves can be identified. For commend the same but ering this level of protection ase a lower breakthrough appropriate maintenance wed. Glove thickness is not ce to a chemical as it is on of the glove material. y greater than 0.35 mm
Eye protection	: If material is handled such that it of protective eyewear is recommend	
Skin and body protection	: Skin protection is not ordinarily red work clothes. It is good practice to wear chemica	
Thermal hazards	: Not applicable	
Environmental exposure c	ontrols	
General advice	: Take appropriate measures to fulf relevant environmental protection contamination of the environment Section 6. If necessary, prevent u being discharged to waste water. V treated in a municipal or industrial before discharge to surface water. Local guidelines on emission limits must be observed for the discharg vapour.	legislation. Avoid by following advice given in indissolved material from Waste water should be waste water treatment plan s for volatile substances
CTION 9. PHYSICAL AND CI	HEMICAL PROPERTIES	
Appearance	· Liquid at room temperature	

Appearance	: Liquid at room temperature.
Colour	: amber
Odour Threshold	: Data not available
рН	: Not applicable
pour point	: -39 °C / -38 °FMethod: ASTM D97
Melting / freezing point	Data not available

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

AeroShell Oil Diesel Ultra

Version 1.7	Revision Date 04.08.2020 Print Date 22.10.2020
Initial boiling point and boiling range	: > 280 °C / 536 °Festimated value(s)
Flash point	: 215 °C / 419 °F Method: ASTM D92 (COC)
Evaporation rate	: Data not available
Flammability (solid, gas)	: Data not available
Upper explosion limit	: Typical 10 %(V)
Lower explosion limit	: Typical 1 %(V)
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)
Relative vapour density	: > 1estimated value(s)
Relative density	: 0.850 (15 °C / 59 °F)
Density	: 850 kg/m3 (15.0 °C / 59.0 °F) Method: ASTM D4052
Solubility(ies)	
Water solubility	: negligible
Solubility in other solvents	: Data not available
Partition coefficient: n- octanol/water	: log Pow: > 6(based on information on similar products)
Auto-ignition temperature	: > 320 °C / 608 °F
Decomposition temperature	: Data not available
Viscosity	
Viscosity, dynamic	: Data not available
Viscosity, kinematic	: 68.2 mm2/s (40.0 °C / 104.0 °F) Method: ASTM D445
	12.0 mm2/s (100 °C / 212 °F) Method: ASTM D445
Explosive properties	: Not classified
Oxidizing properties	: Data not available
Conductivity	: This material is not expected to be a static accumulator.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

AeroShell Oil Diesel Ultra

Version 1.7	Revision Date 04.08.2020	Print Date 22.10.2020
SECTION 10. STABILITY AND F	REACTIVITY	
Reactivity	: The product does not pose any fu addition to those listed in the follo	
Chemical stability	: Stable.	
Possibility of hazardous reactions	: Reacts with strong oxidising agen	its.
Conditions to avoid	: Extremes of temperature and dire	ect sunlight.

Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Information on likely routes of exposure	:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute toxicity		
Product:		
Acute oral toxicity	:	LD50 rat: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

AeroShell Oil Diesel Ultra

Version 1.7 Revision Date 04.08.2020 Print Date 22.10.2020

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

AeroShell Oil Diesel Ultra

Version 1.7

Revision Date 04.08.2020

Print Date 22.10.2020

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

SECTION 12. ECOLOGICAL INFORMATION		
Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract). 	
Ecotoxicity		
Product:		
Toxicity to fish (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.	
Toxicity to crustacean (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.	
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.	
Toxicity to fish (Chronic toxicity)	: Remarks: Data not available	
Toxicity to crustacean (Chronic toxicity)	: Remarks: Data not available	
Toxicity to microorganisms (Acute toxicity)	: Remarks: Data not available	

Persistence and degradability

AeroShell Oil Diesel Ultra

Version 1.7	Revision Date 04.08.2020	Print Date 22.10.2020	
Product:			
Biodegradability		 Remarks: Not readily biodegradable., Major constituents are inherently biodegradable, but contains components that may persist in the environment. 	
Bioaccumulative potential			
Product:			
Bioaccumulation	: Remarks: Contains components window bioaccumulate.	th the potential to	
Partition coefficient: n- octanol/water	: log Pow: > 6Remarks: (based on ir products)	nformation on similar	
Mobility in soil			
Product:			
Mobility	 Remarks: Liquid under most enviro enters soil, it will adsorb to soil part mobile. Remarks: Floats on water. 		
Other adverse effects			
no data available <u>Product:</u>			
Additional ecological information	 Does not have ozone depletion pot ozone creation potential or global v is a mixture of non-volatile compon released to air in any significant qu conditions of use. Poorly soluble mixture., Causes ph organisms. 	varming potential., Product ents, which will not be antities under normal	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
	Disposal methods, including disposal of packaging, should be in accordance with the Hazardous Substances (Disposal) Notice 2017 and the Act.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

AeroShell Oil Diesel Ultra

Version 1.7	Revision Date 04.08.2020	Print Date 22.10.2020
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.	
Local legislation Remarks	: Disposal should be in accordance v national, and local laws and regulat	

SECTION 14. TRANSPORT INFORMATION

National Regulations

Land Transport Rule: Dangerous Goods 2012 -NZS 5433 Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

R-phrase(s)	:	Not classified.
S-phrase(s)	:	Not classified.

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

AeroShell Oil Diesel Ultra

Version 1.7	Revision Date 04.08.2020	Print Date 22.10.2020		
Workplace Exposure Standards and Biological Exposure Indices November 2017.				
New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.				
Other international regulations				
The components of this product are reported in the following inventories:				
EINECS	: All components listed or polymer e	exempt.		
TSCA	: All components listed.			

SECTION 16. OTHER INFORMATION

Full text of H-Statements

H304 May be fatal if swallowed and enters airways. **Full text of other abbreviations**

Asp. Tox. Aspiration hazard

Abbreviations and Acronyms

AICS - Australian Inventory of Chemical Substances; AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide: GHS - Globally Harmonized System: GLP - Good Laboratory Practice: IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 -Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch -Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Further information

Training advice

: Provide adequate information, instruction and training for operators.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

AeroShell Oil Diesel Ultra

Version 1.7	Revision Date 04.08.2020	Print Date 22.10.2020
Other information	: A vertical bar () in the left margin indicates an amendment from the previous version.	
Sources of key data used to compile the Safety Data Sheet	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN