

INDUSTRIAL LUBRICATION FITTINGS

FITTING ACCESSORIES

Couplers - Flush Type Nozzle

| Product # | Thread | Type | Pressure |
|-----------|--------------|----------|----------------------|
| 314150 | 1/8" NPTF(f) | Midget | 10,000 psi (690 bar) |
| Z737 | 1/8" NPTF(f) | Standard | 10,000 psi (690 bar) |

Couplers - Kits

| Product # | Description |
|-----------|----------------------------------|
| 398727 | Standard Button Head Coupler Kit |
| 398726 | Giant Button Head Coupler Kit |

Fitting Tools

Zerk-Mate fitting cleaning tools are a quick, effective way to unplug clogged grease fittings. Light viscosity oil is injected into the plugged joint, loosening grease and allowing new grease to enter, saving the time of replacing fittings and joints. Available in standard and pocket sized models. Easy out fitting tools are used to extract broken fittings, rethread holes, and install new fittings.

| Product # | Description | Thread | Weight |
|-----------|--|----------------------|----------------|
| 339841 | Heavy-Duty Zerk-Mate to unplug fittings | – | 1.5 lb (680 g) |
| 340004 | Pocket-Sized Joint/Fitting Cleaner | – | 8 oz (226 g) |
| B315790 | Easy-out fitting tool to remove and install fittings | 1/4"-28 Taper Thread | 0.2 lb (90 g) |
| B315791 | Easy-out fitting tool to remove and install fittings | 1/8" NPTF | 0.2 lb (90 g) |



Elbow Bodies

Alemite Elbow Bodies change the angle of a fitting to be attached to a bearing.

| Product # | Thread | Angle | Overall Length | Shank Length | Thread Length |
|-----------|--|----------|----------------|--------------------------------------|--------------------------------------|
| 43706 | 1/8" NPTF(f) x 1/8" PTF SAE Short(m) | 90° | 1-1/8" | 17/32" | 17/64" |
| 43716 | 1/8" NPTF(f) x 1/8" PTF SAE Short(m) | 45° | 1" | 7/16" | 7/32" |
| 44701 | 1/8" NPTF(f) x 1/8" PTF SAE Short(m) | 90° | 1" | 7/16" | 7/32" |
| 43718 | 1/8" NPTF(f) x 1/4" PTF(m) | 90° | 1-3/16" | 5/8" | 13/32" |
| 43748 | 1/4" NPTF(f) x 1/4" PTF(m) | 90° | 1-11/32" | 19/32" | 13/32" |
| 369586 | 1/4"-28 Taper Thread SAE-LT(f) x 1/4"-28 UNF-2B(m) | 65° | 45/64" | 1/5" | 19/64" |
| 369594 | 1/4"-28 Taper Thread SAE-LT(f) x 1/4"-28(m) | 45° | 45/64" | 1/5" | 19/64" |
| 306722 | 1/8" NPTF(m) x 1/4" NPTF(m) adapter | Straight | 1-3/16" | 1/4" end -37/64" 1/8" end -25/64" | 1/4" end -13/32" 1/8" end -17/64" |
| 51943 | 1/4"-28(m) Taper x 1/8" NPTF(f) | 90° | 1.03" | 0.22" | 0.110" (minimum) |