SECTION TWELVE

COMPRESSED AIR COMPONENTS

FILTERS, REGULATORS AND LUBRICATORS

Alemite Compressed Air Components allow you to accurately and reliably regulate, clean, dry and lubricate the air going into your system. These high quality components improve productivity by reducing the risk of down time due to poor quality air supply. Alemite offers a variety of packages and individual filters, gauges, regulators and lubricators, allowing you to choose the best option to meet your need.

Filter and Regulator Packages

Alemite Filter and Regulator Packages include the filter, moisture separator with auto drain, air regulator and air gauge, along with required connecting hardware.

3	3	8	8	6	0

Product #	Max Inlet Pressure	Inlet/Outlet			Regulator and Gauge	Connector (2 each)	Auto-Drain	Weight
338860	250 psi <i>(17 bar)</i>	1/4" NPTF(f)	125 psi <i>(9 bar)</i>	5644-2	7604-B	327033	343303	2.8 lb (1.3 kg)
338862	250 psi <i>(17 bar)</i>	1/2" NPTF(f)	125 psi <i>(9 bar)</i>	386295-1	7608-B	51888	343303	4.0 lb (1.8 kg)



Regulators

Constant regulated pressure prevents damage to air operated equipment. Alemite regulators include a pressure relief feature which bleeds off excess pressure when adjustment to lower pressure occurs. Strainer is included with each regulator.

Product #	Max Inlet Pressure	Inlet/Outlet	Max Regulated Pressure	Pressure Gauge	Air Gauge Inlet	Weight
7604-B*	300 psi <i>(21 bar)</i>	1/4" NPTF(f)	125 psi <i>(9 bar)</i>	323449-4	1/4" NPT(m)	2.3 lb (1.0 kg)
7604-1*	300 psi <i>(21 bar)</i>	1/4" NPTF(f)	125 psi <i>(9 bar)</i>	-	-	2.1 lb (0.95 kg)
7606-B*	300 psi <i>(21 bar)</i>	3/8" NPTF(f)	125 psi <i>(9 bar)</i>	323449-4	1/4" NPT(m)	2.3 lb (1.0 kg)
7606-1*	300 psi <i>(21 bar)</i>	3/8" NPTF(f)	125 psi <i>(9 bar)</i>	-	_	2 lb (0.91 kg)
7608-B*	300 psi <i>(21 bar)</i>	1/2" NPTF(f)	125 psi <i>(9 bar)</i>	323449-4	1/4" NPT(m)	3.5 lb (1.6 kg)
7608-1*	300 psi <i>(21 bar)</i>	1/2" NPTF(f)	125 psi <i>(9 bar)</i>	_	_	3.2 lb (0.91 kg)
7612-B*	250 psi <i>(17 bar)</i>	3/4" NPTF(f)	125 psi <i>(9 bar)</i>	323449-4	1/4" NPT(m)	6.3 lb (2.9 kg)
7616-B*	250 psi <i>(17 bar)</i>	1" NPT	125 psi <i>(9 bar)</i>	323449-4	1/4" NPT(m)	6.3 lb (2.9 kg)
7624-A	300 psi <i>(21 bar)</i>	1/4" NPTF(f)	125 psi <i>(9 bar)</i>	391421	1/8" NPT(m)	2 lb (0.91 kg)

* **A WARNING** California Proposition 65: Cancer and reproductive harm. www.P65Warnings.ca.gov