General Accessories

Proximity Switch Cables

Ordering Information

| Part | Proximity Switch Connection | 2nd Connection | Length | Note |
|---|-----------------------------|-------------------------|----------------|---|
| Number | , | Zilu Guillection | Lengui | NOIG |
| Cables for Legacy Proximity Switches | | | | |
| 558021 | 3-pin BH Mini, straight | Flying leads | 6 ft (1.83 m) | - |
| 558022 | 3-pin BH Mini, straight | Flying leads | 12 ft (3.66 m) | - |
| 558025 | 4-pin CH Mini, straight | Flying leads | 12 ft (3.66 m) | PNP LED |
| 558026 | 4-pin CH Mini, 90° | Flying leads | 12 ft (3.66 m) | PNP LED |
| 558023 | 5-pin BH Mini, straight | Flying leads | 6 ft (1.83 m) | _ |
| 558024 | 5-pin BH Mini, straight | Flying leads | 12 ft (3.66 m) | _ |
| Cables for Solid State Proximity Switches | | | | |
| For use with a G3 Max or G3 SP when connecting directly to the pump, when LED is required. | | | | |
| 25M602 | M12 female, straight | Flying leads | 16.5 ft (5 m) | PNP switch with NPN LED – requires 124594 |
| 25M603 | M12 female, straight | M12 male, straight | 16.5 ft (5 m) | PNP switch with NPN LED |
| For use with an external lubrication controller, G-Mini, PLC or other controller, when LED is required. | | | | |
| 25M604 | M12 female, straight | Flying leads | 16.5 ft (5 m) | - |
| 24Z720 | M12 female, 90° | Flying leads | 16.5 ft (5 m) | - |
| For use when replacing a legacy proximity switch with a new solid state proximity switch. | | | | |
| 24Z714 | M12 female, 90° | 5-pin BH Mini, straight | 1 ft (0.3 m) | NPN-BH adapter cable |
| 24Z715 | M12 female, 90° | 3-pin BH Mini, straight | 1 ft (0.3 m) | NPN-BH adapter cable |
| 24Z716 | M12 female, 90° | 4-pin CH Mini, straight | 1 ft (0.3 m) | NPN-BH adapter cable |
| 24Z719 | M12 female, 90° | 4-pin CH Mini, straight | 1 ft (0.3 m) | PNP-CH adapter cable |
| Other M12 cables, without LED indication | | | | |
| 126331 | M12 female, straight | Flying leads | 16.5 ft (5 m) | Requires 124594 when used with G3 Max, SP, etc. |
| 124300 | Flying leads | M12 male, straight | 16.5 ft (5 m) | Requires 124301 when used with solid state proximity switch |
| 124333 | M12 female, straight | M12 male, straight | 16.5 ft (5 m) | - |
| 131214 | M12 female, 90° | M12 male, straight | 3.3 ft (1 m) | - |
| 131215 | M12 female, 90° | M12 male, straight | 6.6 ft (2 m) | - |
| 131216 | M12 female, 90° | M12 male, straight | 9.8 ft (3 m) | - |
| 130282 | M12 female, straight | M12 male, straight | 3.3 ft (1 m) | - |
| 130280 | M12 female, straight | M12 male, straight | 6.6 ft (2 m) | - |
| 130283 | M12 female, straight | M12 male, straight | 9.8 ft (3 m) | - |