



**THE
GOOD
STUFF**

GT-1® Endurance Motor Oil with Liquid Titanium®

Kendall® GT-1® Endurance Motor Oil with Liquid Titanium® protection additive is a premium quality, part-synthetic automotive engine oil specially designed for use in gasoline-fueled vehicles with more than 75,000 miles. It also is recommended for use in lower-mileage vehicles, including new cars under warranty.

GT-1 Endurance Motor Oil with Liquid Titanium is formulated with a blend of synthetic and conventional base stocks, a proprietary seal conditioner, and a performance additive package fortified with our exclusive Liquid Titanium protection additive for extra wear protection and improved fuel savings. The part-synthetic formulation provides enhanced protection against viscosity breakdown and the formation of sludge and varnish compared with conventional engine oils. Our proprietary SealMax® seal conditioner helps recondition and revitalize engine seals, thereby helping to reduce oil consumption, minimize driveway leaks and reduce exhaust smoke. Our Liquid Titanium protection additive provides increased engine protection by forming a strongly bonded titanium shield on the surface of critical engine parts, which reduces friction and wear and can help extend engine life. Reduced friction also helps improve fuel economy performance beyond ILSAC GF-5 requirements. These performance benefits help to maximize engine performance and extend engine life in high-mileage vehicles, while also providing excellent engine protection in newer vehicles.

GT-1 Endurance Motor Oil with Liquid Titanium (except SAE 10W-40) meets new car warranty requirements as defined by ILSAC GF-5. It meets "Resource Conserving" requirements for fuel economy improvement, emission system and turbocharger protection, and protection of vehicles operating on ethanol-containing fuels up to E85. It is backward serviceable for use where API SM or earlier "S" category engine oils are recommended.

**Synthetic Blend
Passenger Car
Engine Oil for
High Mileage
Vehicles;
Formulated with
SealMax® and
Liquid Titanium®
Protection
Additive**



Applications

- Gasoline-fueled and flex-fuel passenger cars, light trucks and sport utility vehicles, especially those with more than 75,000 miles

GT-1® Endurance Motor Oil with Liquid Titanium® is licensed for:

- ILSAC GF-5 (SAE 5W-20, 5W-30, 10W-30)
- API Service SN with Resource Conserving (SAE 5W-20, 5W-30, 10W-30)
- API Service SN (SAE 10W-40)

GT-1® Endurance Motor Oil with Liquid Titanium® meets or exceeds the requirements of:

- Chrysler MS-6395 (Rev. T) (except SAE 10W-40)
- Ford WSS-M2C945-A (SAE 5W-20), WSS-M2C946-A (SAE 5W-30)
- GM6094M (obsolete specification)

Features/Benefits

- Meets ILSAC GF-5 requirements for new cars under warranty (except SAE 10W-40)
- Part-synthetic formulation provides enhanced protection against deposit formation and oil thickening, compared with conventional engine oils
- Exclusive Liquid Titanium® protection additive provides extra wear protection and improved fuel economy
- Proprietary SealMax® seal conditioner helps recondition and revitalize engine seals to reduce oil consumption and leaks
- Protects against rust and bearing corrosion
- Low volatility for reduced oil consumption
- Excellent low-temperature pumpability for protection during cold starts
- Highly resistant to foaming
- Helps maximize engine performance and minimize exhaust smoke
- Formulated to protect turbochargers and emissions control system catalysts
- Formulated for use in vehicles operating on ethanol-containing fuels up to E85



GT-1® Endurance Motor Oil with Liquid Titanium®

Typical Properties				
SAE Grade	5W-20	5W-30	10W-30	10W-40
Specific Gravity @ 60°F	0.863	0.861	0.867	0.870
Density, lbs/gal @ 60°F	7.18	7.17	7.22	7.24
Color, ASTM D1500	3.0	3.0	3.0	3.0
Flash Point (COC), °C (°F)	218 (424)	216 (421)	229 (444)	227 (441)
Pour Point, °C (°F)	-39 (-38)	-39 (-38)	-39 (-38)	-36 (-33)
Viscosity, Kinematic				
cSt @ 40°C	49.9	67.0	65.7	111
cSt @ 100°C	8.6	10.8	10.5	15.8
Viscosity Index	150	152	148	151
Cold Cranking Viscosity, cP				
@ (°C)	6,150	6,150	4,550	6,900
@ (°C)	(-30)	(-30)	(-25)	(-25)
High-Temp/High-Shear Viscosity, cP @ 150°C	2.6	3.1	3.0	3.9
Sulfated Ash, ASTM D874, wt %	0.96	0.96	0.96	0.96
Total Base Number (TBN), ASTM D2896	8.0	8.0	8.0	8.0
Phosphorus, wt %	0.077	0.077	0.077	0.077
Titanium, wt %	0.010	0.010	0.010	0.010
Zinc, wt %	0.085	0.085	0.085	0.085

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <http://www.phillips66.com/EN/products/Pages/MSDS.aspx>.

07-08-16

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

©Phillips 66 Company. Kendall® and its respective logos and products are registered trademarks of Phillips 66 Company in the U.S.A. and other countries.