



Reducing bushings

Model	Thread size	Construction
–	in.	–

10200*	1/8 NPT (f) x 1/2-27 (m)	Brass
10204*	1/4 NPT (f) x 1/2-27 (m)	Brass

***WARNING** California Proposition 65:
Cancer and reproductive harm. www.P65Warnings.ca.gov

Reducing couplings

Model	Thread size NPT (f)	Construction
–	in.	–

11852	1/8 x 1/2-27	Steel
10522*	1/4 x 1/2-27	Brass

***WARNING** California Proposition 65:
Cancer and reproductive harm. www.P65Warnings.ca.gov

Adapter unions

Model	Thread size	Construction
–	in.	–

66883	1/2 NPSM (f) x 1/2 NPT (m)	Steel
69375	1 NPT (f) swivel x 1 NPT (m)	Steel

Nipples

Model	Thread size NPT (m)	Construction
–	in.	–

10130	1/8 x 1/8	Steel
10199*	1/8 x 1/2-27	Brass
10462	1/4 x 1/4	Steel

10198*	1/4 x 1/2-27	Brass
10540	3/8 x 3/8	Steel
11107	3/8 x 1/2	Steel

11197	1/2 x 1/2	Steel
12957	1/2 x 1/2-27	Steel
10202*	1/2-27 x 1/2-27	Brass

12296	3/4 x 3/4	Steel
--------------	-----------	-------

***WARNING** California Proposition 65:
Cancer and reproductive harm. www.P65Warnings.ca.gov

Shut-off valves – needle-type for chassis grease

Model	Thread size NPT (f)	Construction
–	in.	–

778	1/4	High pressure
884	3/8	High pressure
885	1/2	High pressure

Maximum working pressure 10 000 psi (680 bar)

Quarter-turn valves

High pressure

Control lever with “on” or “off” positions provides visual check as to whether lubrication line is open or closed. Buna-N seals with PTFE seat.

Quarter-turn valves – high pressure

Model	Inlet size NPT (f)	Maximum pressure	
		psi	bar
–	in.		
69503	1/2	2 000	138
69425	3/4	2 500	172
69423	1	2 500	172

Quarter-turn valves – medium pressure

Model	Inlet size NPT (f)	Maximum pressure	
		psi	bar
–	in.		
256200	1/4	600	52
66084	1/2	600	52

Low-pressure hose – air and water

Model	Size		ID		Thread size	Maximum pressure Working	
	ft.	m	in.	in.		psi	bar
72024	2	0,6	1/4	5/8	1/4 NPT (m)	300	20,68
72036	3	0,9	1/4	5/8	1/4 NPT (m)	300	20,68
72060	5	1,5	1/4	5/8	1/4 NPT (m)	300	20,68
72120	10	3,0	1/4	5/8	1/4 NPT (m)	300	20,68
72240	20	6,1	1/4	5/8	1/4 NPT (m)	300	20,68
72360	30	9,1	1/4	5/8	1/4 NPT (m)	300	20,68
72600	50	15,2	1/4	5/8	1/4 NPT (m)	300	20,68
72024A	2	0,6	3/8	23/32	3/8 NPT (m)	300	20,68
72360A	30	9,1	3/8	23/32	3/8 NPT (m)	300	20,68
72480A	40	12,2	3/8	23/32	3/8 NPT (m)	300	20,68
72600A	50	15,2	3/8	23/32	3/8 NPT (m)	300	20,68
72720A	75	22,9	3/8	23/32	3/8 NPT (m)	300	20,68
72900A	75	22,9	3/8	23/32	3/8 NPT (m)	300	20,68
74024	2	0,6	1/2	27/32	1/2 NPT (m)	300	20,68
74060	5	1,5	1/2	27/32	1/2 NPT (m)	300	20,68
74480	40	12,2	1/2	27/32	1/2 NPT (m)	300	20,68
74600	50	15,2	1/2	27/32	1/2 NPT (m)	300	20,68
74900	75	22,9	1/2	7/8	1/2 NPT (m)	300	20,68
278749*	50	15,2	3/8	23/32	1/4 NPT (m)	300	20,68
278752*	50	15,2	1/2	27/32	1/2 NPT (m)	300	20,68

* ⚠️ **WARNING** California Proposition 65: Cancer and reproductive harm. www.P65Warnings.ca.gov

Nipples, couplers and bushings for Lincoln 75 grease hose

Bushings

Model	Thread size
	in.
10200*	1/8 NPT (f) x 1/2 – 27 (m)
10204*	1/4 NPT (f) x 1/2 – 27 (m)
12287	1/2 – 27 (f) x 1/2 NPT (m)

* ⚠️ **WARNING** California Proposition 65: Cancer and reproductive harm. www.P65Warnings.ca.gov

Reducing couplings

Model	Thread size
	in.
11852	1/8 NPT (f) x 1/2 – 27 (f)
10522*	1/4 NPT (f) x 1/2 – 27 (f)
67171	3/4 NPT (m) x 1/2 NPT (f)

* ⚠️ **WARNING** California Proposition 65: Cancer and reproductive harm. www.P65Warnings.ca.gov

Nipples

Model	Thread size
	in.
10198*	1/4 NPT (m) x 1/2 – 27 (m)
10199*	1/8 NPT (m) x 1/2 – 27 (m)
10202*	1/2 – 27 (m) x 1/2 – 27 (m)
12957	1/2 NPT (m) x 1/2 – 27 (m)
11197	1/2 NPT (m) x 1/2 NPT (m)

* ⚠️ **WARNING** California Proposition 65: Cancer and reproductive harm. www.P65Warnings.ca.gov

Lincoln high-pressure replacement hose – cross reference

Model	Size
	in.
Alemite	1/2 – 27 (f) x 1/2 – 27 (f)
Aro	1/8 NPT (m) x 1/8 NPT (f)
Balcrank	1/8 NPT (m) x 1/8 NPT (f)
Graco	1/4 NPT (m) x 1/4 NPT (m)

