



**Reducing bushings**

Model	Thread size	Construction
–	in.	–

<b>10200*</b>	1/8 NPT (f) x 1/2-27 (m)	Brass
<b>10204*</b>	1/4 NPT (f) x 1/2-27 (m)	Brass

\***WARNING** California Proposition 65:  
Cancer and reproductive harm. [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**Reducing couplings**

Model	Thread size NPT (f)	Construction
–	in.	–

<b>11852</b>	1/8 x 1/2-27	Steel
<b>10522*</b>	1/4 x 1/2-27	Brass

\***WARNING** California Proposition 65:  
Cancer and reproductive harm. [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**Adapter unions**

Model	Thread size	Construction
–	in.	–

<b>66883</b>	1/2 NPSM (f) x 1/2 NPT (m)	Steel
<b>69375</b>	1 NPT (f) swivel x 1 NPT (m)	Steel

**Nipples**

Model	Thread size NPT (m)	Construction
–	in.	–

<b>10130</b>	1/8 x 1/8	Steel
<b>10199*</b>	1/8 x 1/2-27	Brass
<b>10462</b>	1/4 x 1/4	Steel

<b>10198*</b>	1/4 x 1/2-27	Brass
<b>10540</b>	3/8 x 3/8	Steel
<b>11107</b>	3/8 x 1/2	Steel

<b>11197</b>	1/2 x 1/2	Steel
<b>12957</b>	1/2 x 1/2-27	Steel
<b>10202*</b>	1/2-27 x 1/2-27	Brass

<b>12296</b>	3/4 x 3/4	Steel
--------------	-----------	-------

\***WARNING** California Proposition 65:  
Cancer and reproductive harm. [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**Shut-off valves – needle-type for chassis grease**

Model	Thread size NPT (f)	Construction
–	in.	–

<b>778</b>	1/4	High pressure
<b>884</b>	3/8	High pressure
<b>885</b>	1/2	High pressure

Maximum working pressure 10 000 psi (680 bar)

**Quarter-turn valves**

**High pressure**

Control lever with “on” or “off” positions provides visual check as to whether lubrication line is open or closed. Buna-N seals with PTFE seat.

**Quarter-turn valves – high pressure**

Model	Inlet size NPT (f)	Maximum pressure	
		psi	bar
–	in.		
<b>69503</b>	1/2	2 000	138
<b>69425</b>	3/4	2 500	172
<b>69423</b>	1	2 500	172

**Quarter-turn valves – medium pressure**

Model	Inlet size NPT (f)	Maximum pressure	
		psi	bar
–	in.		
<b>256200</b>	1/4	600	52
<b>66084</b>	1/2	600	52