Lincoln Centro-Matic automatic lubrication systems





Centro-Matic® Automatic Lubrication Systems















Injector Connector Tube

Permits application of combined discharge of two or more Series SL-V, SL-1, SL-41 or SL-44 injectors through one feed line. Used where bearing size is such that multiple injector output is required. Fittings 1/8" NPT male each end. Carbon steel construction.

Model	For Injector Series	Connections		
81646	SL-V, SL-V XL OR SL1, SL41, SL44	1/4" NPTF Male		
274824	SL-1 to SL-V connection	1/4" NPTF Male		

Injector Outlet Adapter

Converts individual injector lubricant outlet when standard 1/8" O.D. tube is not desired. All adapters are carbon steel unless otherwise noted.

Model	For Injector Series	Outlet Connections
14988		1/8" NPTF Female
84200		1/4" O.D. Tube
14991	SL32, SL33, SL42, SL43	⅓" NPTF Male
249281		4 mm Tube
249282		6 mm Tube

Manual Grease Fitting Adapter

Allows manual lubrication of the machine between normal system cycles. Carbon steel with Nitrile seals.

Model	For Injector Series	Outlet Connections		
84195	CL 00 CL 00 CL 40 CL 40	1⁄₃" O.D. Tube		
84203	SL32, SL33, SL42, SL43	1/4" O.D. Tube		

Injector Locking Cap

Carbon steel locking caps set injectors to fixed output.

Model	For Injector Series	Fixed Volume Output		
102781	SL32, SL43	.002 in ³ / .033 cc		
	SL33, SL42	.003 in ³ / .049 cc		

Injector Cover Caps

Injector cover caps are designed to protect the injector from dirt, harmful liquids and fumes.

Model	Fits Injector Series	Covers	Material	Length		Diameter		
				in.	mm	in.	mm	
273088	SL-V	Indicator Stem Measuring Chamber	Polycarbonate	1.5	38.1	.715 (ID)	18.2	
273089	SL-V XL		Polycarbonate	2.2	55.9	.715 (ID)	18.2	
83272	SL1, SL44		Stem		1.5	38.1	.69 (ID)	17.5
83730	SL11		Vinyl	2.0	50.8	1.125 (ID)	28.6	
68483	SL32, SL33, SL42, SL43		,	1.25	31.2	.5 (ID)	12.7	
90537	SL1, SL41, SL44	Injector Body	Aluminum	3.25	82.6	1.19 (ID)	30.2	