Lubrication tools and equipment








Grease Hose Extensions





Premium Extensions for Manually Operated Grease Guns

Maximum working pressure 4500 psi. Strategically placed coil spring provides non-slip, push-pull grip and prevents accidental "kinking" which could cause hose ruptures.





Extensions for Manually Operated Grease Guns

Maximum working pressure 3000 psi.



Manually Operated—Packaged

Model	Length	Thread Size
71512	12"	1/8" NPT(m)
71518	18"	1/8" NPT(m)

Manually Operated—Bulk (Unpackaged)

Manadily Operaced	Bain (Onpac	n (Onpuchagea)		
Model	Length	Thread Size		
75912CL	12"	1/8" NPT(m)		
75918CL	18"	1/8" NPT(m)		
75924CL	24"	1/8" NPT(m)		
75936CL	36"	1/8" NPT(m)		



PowerLuber® Whip Hoses

Attaches with 7/16" UNEF fitting; 1/8" NPT(m) outlet. Working press. 7500 psi (517 bar). For use with 120-, 18-, 14.4- and 12-volt PowerLubers and pneumatic model 1162.

Model	Length	
1218	18"	
1224	24"	
1230	30"	
1236	36"	

Assemblies for Standard Hydraulic Fittings

Maximum working pressure 4500 psi.

Model	Whip Hose	Coupler	Thread Size
81725	5818/18"	5845	1/8" NPT(m)
81726	5812/12"	5845	1/8" NPT(m)
81795 *	5812/12"	5845	1/8" NPT(m)

^{*} Includes 81980 locking sleeve.

Assemblies for Button-Head Couplers with Swivel

Maximum working pressure 4000 psi. Includes 81606 swivel.

Model	Whip Hose	Coupler	Thread Size
3029	5812/12"	80933/large	1/8" NPT(m)
3034	5812/12"	81458/standard	1/8" NPT(m)
3055	5861/36"	81458/standard	1/8" NPT(m)
3056	5861/36"	80933/large	1/8" NPT(m)

Whip Hoses Models 3029, 3034, 5812, 5818, 5861, 81725, 81726, 81795 Install as shown Incorrect

WARNING

Flexible & Rigid Extension Adapter Model 5858

Maximum working pressure 5000 psi. Allows operator to switch from flexible to rigid extension with one hand. Overall length 13". 1/8" NPT(m). For use on hand guns or air operated grease control valves.

5KF 11