

# Lincoln high-, medium- and low-pressure hoses – every size for every application

## High-pressure hose – grease

Model	Size		Hose type	ID	OD	Thread size	Maximum pressure Working	
	ft.	m					psi	bar
75024	2	0,6	75/100R2A	1/4	11/16	1/2– 27 (f)	5 000	345
75060	5	1,5	75/100R2A	1/4	11/16	1/2– 27 (f)	5 000	345
75084	7	2,1	75/100R2A	1/4	11/16	1/2– 27 (f)	5 000	345
75120	10	3,0	75/100R2A	1/4	11/16	1/2– 27 (f)	5 000	345
75168	14	4,3	75/100R2A	1/4	11/16	1/2– 27 (f)	5 000	345
75240	20	6,1	75/100R2A	1/4	11/16	1/2– 27 (f)	5 000	345
75360	30	9,1	75/100R2A	1/4	11/16	1/2– 27 (f)	5 000	345
75480	40	12,2	75/100R2A	1/4	11/16	1/2– 27 (f)	5 000	345
75600	50	15,2	75/100R2A	1/4	11/16	1/2– 27 (f)	5 000	345
76024B	2	0,6	76B/100R2	3/8	27/32	1/2 NPT (f)	4 000	276
76120B	10	3,0	76B/100R2	3/8	27/32	1/2 NPT (f)	4 000	276
76360B	30	9,1	76B/100R2	3/8	27/32	1/2 NPT (f)	4 000	276
76600B	50	15,2	76B/100R2	3/8	27/32	1/2 NPT (f)	4 000	276
76900B	75	22,9	76B/100R2	3/8	27/32	1/2 NPT (f)	4 000	276
76024A	2	0,6	76B/100R2	1/2	27/32	1/2 NPT (f)	4 000	276
76600A	50	15,2	76B/100R2	1/2	27/32	1/2 NPT (f)	4 000	276

## Medium-pressure hose – oil, gear lube and antifreeze

Model	Size		Hose type	ID	OD	Thread size	Maximum pressure Working	
	ft.	m					psi	bar
73024	2	0,6	73/100R3	1/2	13/16	1/2 NPT (m)	1 500	103
73036	3	0,9	73/100R3	1/2	13/16	1/2 NPT (m)	1 500	103
73060	5	1,5	73/100R3	1/2	13/16	1/2 NPT (m)	1 500	103
73120	10	3,0	73/100R3	1/2	13/16	1/2 NPT (m)	1 500	103
73240	20	6,1	73/100R3	1/2	13/16	1/2 NPT (m)	1 500	103
73360	30	9,1	73/100R3	1/2	13/16	1/2 NPT (m)	1 500	103
73480	40	12,2	73/100R3	1/2	13/16	1/2 NPT (m)	1 500	103
73600	50	15,2	73/100R3	1/2	13/16	1/2 NPT (m)	1 500	103
73720	60	18,3	73/100R3	1/2	13/16	1/2 NPT (m)	1 500	103
73900	75	22,9	73/100R3	1/2	13/16	1/2 NPT (m)	1 500	103
1230120	10	3,0	1230/100R2	3/4	1 1/4	3/4 NPT (m)	2 250	155

## Hose accessories – ball stops

Lincoln ball stops are used to cushion and stop hose retraction.

### Ball stops

Model	Description	Hose type	OD
			in.
85515	Adjustable	RMA Class A	5/8
85516	Adjustable ball stop	RMA Class A and 74	11/16 to 23/32
85517	Adjustable	73, 74, 76A and 76B	27/32 to 31/32
84347	Adjustable	78 and 78B	11/32
84122	Adjustable	–	1 3/4 to 1 7/8
84257	Adjustable	–	1 1/2 to 1 5/8

