





Model 602136

Suction kit

Model 84945 suction kit

For transfer of product from drums, bulk tanks or reservoirs. Includes bung bushing suction tube, hose and coupling assembly.

Note: 2 x 1 in. (*50*,8 x 25,4 mm) bell reducer required for use with model 1914, supplied by others – general plumbing part.

Model 85806

16 gallon (60 liter) suction tube.

Model 85807

55 gallon (208 liter) suction tube.

Modular air line equipment accessories – lockout valve

Install in-line or modular with other AirCare products to help conform to OSHA lockout regulations. In the closed position, valves block inlet air flow and exhaust downstream air.

¥	Lockout v	alve
1	Model	١
		L

Modular In-line Maximum Temperature range pressure use use °F °C in. in. psi bar 247771 ³/₈ modular 3/8 250 17,24 0 to 150 –18 to +65

Integrated, modular filter and regulator with gauge

Model	Maximum pressure		Temperature range		Pressure range		Drain type	Size	Size	Weight								
								PTF	А		В		С		Diameter			
_	psi	bar	°F	°C	psi	bar	_	in.	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kg
602136	250	17,24	0 to 150	–18 to +65	5 to 150	0,3 to 10,34	Manual	³ /8	5.27	134	2.89	73	1.98	50	3.29	83	1.2	0,5

Element particle size 40µ