

LMC 101 controller

For low-voltage lubrication applications



The versatile SKF LMC 101 controller operates as a timer or controller on single-line or progressive lubrication systems. Developed for use on off-road and mobile equipment, the LMC 101 also is suitable for many low-voltage, industrial lubrication applications, such as those found in food and beverage, pulp and paper and steel markets.

When operating as a controller, the LMC 101 ends the lubrication cycle when a pressure switch, pressure transducer or piston detector is actuated. In the timer mode, the lubrication cycle ends when time has expired.

Designed to meet OEM vibration standards for major construction equipment, the LMC 101 controller can cycle a pneumatically, hydraulically or electrically driven pump in one- to 10-second intervals.

LMC 101 controller features:

- Operates single-line or progressive lubrication systems
- Functions as a timer or controller
- Records history of system operation and fault codes
- Configured using PC software and USB connection

- Controls FlowMaster or high-current pump without external relay
- Uses pressure switch or pressure transducers (1 to 6 V or 4 to 20 mA) in controller mode
- LED indicators show power, pump function, low-level fault and system faults
- Manual lubrication cycle activation button
- Data logging includes date and time of alarms, power ups, configuration changes, lubrication cycles and totals lubrication count, manual lubrication count, pressure alarm, low levels and pump on-time information
- Four inputs:
 - Two pressure switches, pressure transducers or piston detectors
 - Remote manual lubrication switch
 - Low-level switch
- Four outputs:
 - Pump
 - Low-level alarm relay
 - System fault relay
 - Vent solenoid



LMC 101 controller



Technical data

Model	86535
Power input Enclosure rating	12 or 24 V DC, -20% + 30% NEMA 12
Operating temperature Inputs	-40 to +150 °F (-40 to +66 °C) 4
Outputs Approvals	4 none
Pump relay contact Vent and alarm relay contacts	20 amps at 30 V DC 2 amps at 30 V DC
Enclosure size Mounting dimensions	8.25 x 5.0 x 3.5 in. (210 x 127 x 89 mm) 8.75 x 3.75 in. (222 x 95 mm)

PC requirements

Model	86535
Operating system Processor minimum	Windows XP, Vista, 7 and 8 1 GHz
Memory minimum Additional software	512 MB Microsoft .Net 4.0
Hard drive space USB port	50 MB 1 needed

Timing characteristics

Model	86535
Pause time	min. 15 seconds max. 99 hours
Pumping time	min. 15 seconds max. 99 minutes

Please contact:
SKF USA, Inc.
One Lincoln Way
St. Louis, MO 63120 USA
Tel. +1 (314) 679-4200

© SKF is a registered trademark of the SKF Group.

© FlowMaster is a registered trademark of Lincoln Industrial Corp.

Microsoft and Windows XP, Windows Vista, Windows 7 and Windows 8 are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

© SKF Group 2015

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB LS/P8 15556 EN · March 2015

