

e-mail info@akemi.de

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 3 (replaces version 2) Revision: 03.08.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Akepox 5000 Component A · Trade name:

· Article number: 10681A, 10682A, 11635, 11636, 12689

KRS1-N0QQ-300H-46P0 · UFI:

· 1.2 Relevant identified uses of the substance or mixture and

No further relevant information available. uses advised against

· Application of the substance / the

mixture Epoxy resin adhesive

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH Tel. +49(0)911-642960 Fax. +49(0)911-644456

Lechstrasse 28 D 90451 Nürnberg

· Further information obtainable

Laboratory 1.4 Emergency telephone

number: Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-64296-59

Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m.

#### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation

(EC) No 1272/2008

The product is classified and labelled according to the CLP regulation. · Hazard pictograms





GHS07

· Signal word Warning

· Hazard-determining components of

labelling: bis[4-(2,3-epoxypropoxy)phenyl]propane

Cyclohexanedimethanol diglycidyl ether

H315 Causes skin irritation. Hazard statements

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements If medical advice is needed, have product container or label at P101

hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing vapours.

Avoid release to the environment. P273

Wear protective gloves/protective clothing/eye protection/face P280

protection/hearing protection.

(Contd. on page 2)



Page 2/12

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 3 (replaces version 2) Revision: 03.08.2023

Trade name: Akepox 5000 Component A

(Contd. of page 1)

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P501 Dispose of contents/container in accordance with local/

regional/national/international regulations.

· Additional information: Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

· Determination of endocrine-

For information on endocrine disrupting properties see section 11. disrupting properties

#### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 1675-54-3	bis[4-(2,3-epoxypropoxy)phenyl]propane	50-100%
EINECS: 216-823-5	Aquatic Chronic 2, H411	
Index number: 603-073-00-2	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
Reg.nr.: 01-2119456619-26-xxxx		
	Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 %	
	Skin Irrit. 2; H315: C ≥ 5 %	
CAS: 14228-73-0	Cyclohexanedimethanol diglycidyl ether	12.5-25%
EINECS: 238-098-4 Reg.nr.: 01-2120068066-56-xxxx	Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317	
Neg.III 01-2120000000-30-XXXX	EUH205	
CAS: 2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	1-5%
EINECS: 219-784-2	Eye Dam. 1, H318	
Reg.nr.: 01-2119513212-58		
· Additional information:	For the wording of the listed hazard phrases refer to section 16.	

#### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

· General information: Take affected persons out into the fresh air.

Position and transport stably in side position.

Immediately remove any clothing soiled by the product.

· After inhalation: Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for

transportation.

· After skin contact: If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

Rinse opened eye for several minutes under running water. If symptoms persist, · After eye contact:

consult a doctor.

Rinse out mouth and then drink plenty of water. After swallowing:

· 4.2 Most important symptoms and effects, both acute and

delayed Breathing difficulty

Coughing

Allergic reactions

(Contd. on page 3)



(Contd. of page 2)

Page 3/12

· Hazards

# Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 3 (replaces version 2) Revision: 03.08.2023

**Trade name:** Akepox 5000 Component A

Danger of impaired breathing.

4.3 Indication of any immediate medical attention and special

<u>treatment needed</u> If swallowed, gastric irrigation with added, activated carbon.

**SECTION 5: Firefighting measures** 

5.1 Extinguishing media

· <u>Suitable extinguishing agents:</u> CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam.

5.2 Special hazards arising from

the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO) Hydrogen chloride (HCl)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

· <u>Protective equipment:</u> Wear fully protective suit.

Wear self-contained respiratory protective device. Do not inhale explosion gases or combustion gases.

· Additional information Collect contaminated fire fighting water separately. It must not enter the sewage

system.

Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

**SECTION 6: Accidental release measures** 

 6.1 Personal precautions, protective equipment and

**emergency procedures** Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

• 6.2 Environmental precautions: Do not allow to penetrate the ground/soil.

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

**containment and cleaning up:** Dispose of the material collected according to regulations.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust).

Ensure adequate ventilation.

• 6.4 Reference to other sections See Section 13 for disposal information.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

**SECTION 7: Handling and storage** 

· 7.1 Precautions for safe

handling Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles. Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and

explosion protection: No special measures required.

(Contd. on page 4)



Page 4/12

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 3 (replaces version 2) Revision: 03.08.2023

Trade name: Akepox 5000 Component A

(Contd. of page 3)

#### · 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by

storerooms and receptacles: Store only in the original receptacle. Prevent any seepage into the ground.

· Information about storage in one

common storage facility:

Store away from reducing agents.

Store away from foodstuffs.

· Further information about storage

conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

· Storage class: 12

7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters

· Ingredients with limit values that

require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical

values that have to be monitored at the workplace.

		des that have to be monitored at the workplace.
· <u>DNELs</u>		
	bis[4-(2,3-epoxypropoxy)pl	
Oral	DNEL (Kurzzeit-akut)	0.5 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.5 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	8.33 mg/kg bw/day (ARB)
		3.571 mg/kg bw/day (BEV)
	DNEL ( Langzeit-wiederholt)	0.75 mg/kg bw/day (ARB)
		0.0893 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	12.25 mg/m³ Air (ARB)
	DNEL (Langzeit-wiederholt)	4.93 mg/m³ Air (ARB)
		0.87 mg/m³ Air (BEV)
14228-73-0 Cyclohexanedimethanol diglycidyl ether		
Oral	DNEL (Langzeit-wiederholt)	0.5 mg/kg bw/day (BEV)
Dermal	DNEL ( Langzeit-wiederholt)	1 mg/kg bw/day (ARB)
		0.5 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	3.52 mg/m³ Air (ARB)
		0.86 mg/m³ Air (BEV)
2530-83-8	[3-(2,3-epoxypropoxy)prop	yl]trimethoxysilane
Oral	DNEL (Langzeit-wiederholt)	12.5 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	21 mg/kg bw/day (ARB)
		12.5 mg/kg bw/day (BEV)
	DNEL ( Langzeit-wiederholt)	21 mg/kg bw/day (ARB)
		5 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	147 mg/m³ Air (ARB)
		43.5 mg/m³ Air (BEV)
	DNEL (Langzeit-wiederholt)	147 mg/m³ Air (ARB)
		43.5 mg/m³ Air (BEV)

(Contd. on page 5)



Page 5/12

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 3 (replaces version 2) Revision: 03.08.2023

<u>Trade name:</u> Akepox 5000 Component A	١.

	(1	Contd. of page 4)	
	· <u>PNECs</u>		
_	-(2,3-epoxypropoxy)phenyl]propane		
PNEC (wässrig)			
	0.0006 mg/l (MW)		
	0.006 mg/l (SW)		
	0.018 mg/l (WAS)		
PNEC (fest)	0.065 mg/kg Trockengew (BO)		
	0.034 mg/kg Trockengew (MWS)		
	0.341 mg/kg Trockengew (SWS)		
	14228-73-0 Cyclohexanedimethanol diglycidyl ether		
PNEC (wässrig)	0.6 mg/l (KA)		
	0.012 mg/l (MW)		
	0.117 mg/l (SW)		
PNEC (fest)	0.24 mg/kg Trockengew (BO)		
	0.047 mg/kg Trockengew (MWS)		
	0.47 mg/kg Trockengew (SWS)		
	3-epoxypropoxy)propyl]trimethoxysilane		
PNEC (wässrig)	8.2 mg/l (KA)		
	0.1 mg/l (MW)		
	1 mg/l (SW)		
	1 mg/l (WAS)		
PNEC (fest)	0.14 mg/kg Trockengew (BO)		
	0.36 mg/kg Trockengew (MWS)		
	3.6 mg/kg Trockengew (SWS)		

Additional information:

The lists valid during the making were used as basis.

#### 8.2 Exposure controls

· Appropriate engineering controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic

measures: Do not eat, drink, smoke or sniff while working.

Apply solvent resistant skin cream before starting work. Clean skin thoroughly immediately after handling the product.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

· Respiratory protection: Short term filter device:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Preventive skin protection by use of skin-protecting agents is recommended.

Hand protection Preventive skin protection by use of skin-protecting agents is recorn After use of gloves apply skin-cleaning agents and skin cosmetics.

Skin protection agent recommendation for preventive skin shelter in application

and combination of protective gloves: STOKO EMULSION (http://www.stoko.com)

Skin protection recommendation for skin cleaning after product handling:

Kresto Classic (http://debstoko.com)

Skin protection agent recommendation for skin aftercare:

(Contd. on page 6)

Page 6/12

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 3 (replaces version 2)

Trade name: Akepox 5000 Component A

(Contd. of page 5)

Revision: 03.08.2023

STOKO VITAN (http://www.stoko.com)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: http://www.kcl.de).



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level ≤ 6, 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Butoject (KCL, Art No. 897, 898) Fluorocarbon rubber (Viton) Vitoject (KCL, Art No. 890)

 As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Camatril (KCL, 730, 731, 732, 733)

Chloroprene rubber, CR

Camapren (KCL, Art\_No. 720, 722, 726)

· Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

Eye/face protection



Tightly sealed goggles

· Body protection:

Protective work clothing

(Contd. on page 7)



Page 7/12

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 3 (replaces version 2) Revision: 03.08.2023

**Trade name:** Akepox 5000 Component A

(Contd. of page 6)

#### **SECTION 9: Physical and chemical properties**

· General Information

Colour:
 Odour:
 Melting point/freezing point:
 Boiling point or initial boiling point and boiling range

Elash point:

 Colourless
 Characteristic
 Undetermined
 Undetermined

• Flash point:
• pH

Not applicable.

Not applicable

Not applicable

· Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 3,900 mPas

Solubility

· water: Not miscible or difficult to mix.

· Vapour pressure at 20 °C: 2 hPa

Density and/or relative density

Density at 20 °C: 1.15 g/cm<sup>3</sup>

### 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and

environment, and on safety.

· <u>Ignition temperature:</u> Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

· Information with regard to physical hazard classes

Void Explosives · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in Void contact with water

Contact with water

Oxidising liquids

Oxidising solids

Organic peroxides

Corrosive to metals

Desensitised explosives

#### **SECTION 10: Stability and reactivity**

• **10.1 Reactivity** No further relevant information available.

· 10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous

<u>reactions</u> May produce violent reactions with bases and numerous organic substances

including alcohols and amines.

(Contd. on page 8)



(Contd. of page 7)

Page 8/12

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 3 (replaces version 2) Revision: 03.08.2023

Trade name: Akepox 5000 Component A

Reacts with acids.

Exothermic polymerisation.

10.4 Conditions to avoid

· 10.5 Incompatible materials: · 10.6 Hazardous decomposition

products:

Irritant gases/vapours

Carbon monoxide and carbon dioxide

No further relevant information available.

No further relevant information available.

Hydrogen chloride (HCI)

#### **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Based on available data, the classification criteria are not met. · Acute toxicity

· <u>LD/LC50</u> values relevant for classification:			
1675-54-3	1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane		
Oral	LD50	>2,000 mg/kg (rat) (OECD 420)	
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)	
14228-73-	14228-73-0 Cyclohexanedimethanol diglycidyl ether		
Oral	LD50	1,098 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane			
Oral	LD50	8,025 mg/kg (rat) (OECD 401)	
	NOAEL-Werte	≥5 mg/kg (mouse)	
		200 mg/kg (rabbit) (OECD 414)	
		500 mg/kg (rat) (OECD 415)	
Dermal	LD50	4,250 mg/kg (rabbit) (OECD 402)	
Inhalative	LC50/4 h	>5.3 mg/l (rat) (OECD 403)	
	NOAEC	0.225 mg/l (rat) (OECD 412)	

· Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation. Respiratory or skin sensitisation May cause an allergic skin reaction.

· Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. · STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard

· 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

#### **SECTION 12: Ecological information**

### · 12.1 Toxicity

· Aquatic toxicity:	
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane	
IC50	>100 mg/l (BES)
EC10/16h	100 mg/l (pseudomonas putida)
EC50/48h	1.8 mg/l (daphnia magna)
	(Contd. on page 9)



Page 9/12

# Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 3 (replaces version 2) Revision: 03.08.2023

Trade name: Akepox 5000 Component A

NOEC/21d | 0.3 mg/l (daphnia magna) (Contd. of page 8)

EC50/72h 11 mg/l (selenastrum capricornutum)
LC50/96h 2 mg/l (Oncorhynchus mykiss)

14228-73-0 Cyclohexanedimethanol diglycidyl ether

EC50/48h 16.3 mg/l (daphnia magna)

LC0/96h 10 mg/l (piscis)

EC50/72h 36.6 mg/l (Pseudokirchneriella subcapitata)

LC50/96h 13 mg/l (piscis)

EC50

10.1 mg/l (Oncorhynchus mykiss)

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

EC50/96h | 350 mg/l (Pseudokirchneriella subcapitata) (OECD 201)

>100 mg/l (salmon) 119 mg/l (algae)

IC50 255 mg/l (Scenedesmus subspicatus)

EC50/48h 324 mg/l (daphnia magna)

EC10/5h 1,500 mg/l (pseudomonas putida)
ErC50/72h 350 mg/l (Selenastrum capricornutum)

ECO/96h 44 mg/l (Cyprinus carpio)

NOEC >100 mg/kg (Klärschlamm: Atmungs-/Vermehrungshemmung) (OECD 209)

NOEC/21d ≥100 mg/l (daphnia magna) (OECD 211) EC50/48h 324-710 mg/l (daphnia magna) (OECD 202) EC50/72h 255 mg/l (Scenedesmus subspicatus) LC50/96h 55 mg/l (Cyprinus carpio) (OECD 203)

276 mg/l (lem)

237 mg/l (Oncorhynchus mykiss)

· 12.2 Persistence and

degradability
 12.3 Bioaccumulative potential
 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.

 $\begin{array}{ll} \cdot \ \underline{\text{12.5 Results of PBT and vPvB assessment}} \\ \cdot \ \underline{\text{PBT:}} & \text{Not applicable.} \end{array}$ 

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting

**properties**The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

· Remark: Toxic for fish

· Additional ecological information:

General notes: Toxic for aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for

water

#### **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods

· Recommendation Must not be disposed together with household garbage. Do not allow product to

reach sewage system.

(Contd. on page 10)



Page 10/12

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 3 (replaces version 2) Revision: 03.08.2023

**Trade name:** Akepox 5000 Component A

(Contd. of page 9)

	(conta. of page o)	
· European waste catalogue		
	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS	
20 01 00	separately collected fractions (except 15 01)	
20 01 27*	paint, inks, adhesives and resins containing hazardous substances	

Uncleaned packaging:

Recommendation: Empty contaminated packagings thoroughly. They may be recycled after

thorough and proper cleaning.

· Recommended cleansing agents: Alcohol

#### **SECTION 14: Transport information**

· <b>14.1 UN number or ID number</b> · ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name	
· <u>ADR</u>	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane)
· <u>IMDG</u>	ENVIRONMENTALLY HAZARDOUS SÜBSTÄNCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane), MARINE POLLUTANT
· <u>IATA</u>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane)

#### · 14.3 Transport hazard class(es)

· ADR



· <u>Class</u> 9 (M6) Miscellaneous dangerous substances and articles.

· Label

· <u>IMDG</u>, IATA



· <u>Class</u> 9 Miscellaneous dangerous substances and articles.

· Label

· 14.4 Packing group · ADR, IMDG, IATA

· 14.5 Environmental hazards:
· Marine pollutant:

Symbol (fish and tree)
Special marking (ADR):
Special marking (IATA):
Symbol (fish and tree)
Symbol (fish and tree)

• **14.6 Special precautions for user** Warning: Miscellaneous dangerous substances and articles.

Hazard identification number (Kemler code):
 EMS Number:
 F-A,S-F

(Contd. on page 11)



Page 11/12

# Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 3 (replaces version 2) Revision: 03.08.2023

Trade name: Akepox 5000 Component A

(Contd. of page 10)

 Stowage Category Α

14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

 Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

 Transport category 3 · Tunnel restriction code (-)

· IMDG

· Limited quantities (LQ) Excepted quantities (EQ) 5L Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE. LIQUID, N.O.S. (BIS[4-(2,3-EPOXYPROPOXY)PHENYL]

PROPANE), 9, III

#### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- Named dangerous substances -

ANNEX I None of the ingredients is listed.

· Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the

application of lower-tier

requirements 200 t

· Qualifying quantity (tonnes) for the

application of upper-tier

500 t requirements

· REGULATION (EC) No 1907/2006

**ANNEX XVII** Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 12)





# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.08.2023 Version number 3 (replaces version 2) Revision: 03.08.2023

**Trade name: Akepox 5000 Component A** 

(Contd. of page 11)

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be

observed.

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· <u>VOC EU</u> 0.0 g/l

· 15.2 Chemical safety

<u>assessment:</u> A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS:
 Date of previous version:
 Laboratory
 14.12.2022

· Version number of previous

version:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European

Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

ΕU