

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

1. Identification

1.1. Product identifier

Code: **DOMO10_CAR_A**
 Product name: **DOMO 10 CARTUCCIA PARTE A**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **EPOXY GLUE FOR STONES PART A.**

Identified Uses	Industrial	Professional	Consumer
ADHESIVE SYSTEM/TREATMENT FOR STONE SECTOR	✓	✓	-

1.3. Details of the supplier of the safety data sheet

Name	TENAX SPA		
Full address	Via I Maggio, 226		
District and Country	37020 Volargne		(VR)
	Italy		
	Tel. +39 045 6887593		
	Fax +39 045 6862456		
e-mail address of the competent person responsible for the Safety Data Sheet	msds@tenax.it		
Supplier:	Tenax Usa		
	7606 Whitehall Executive Center Drive Suite 400, 28273 Charlotte NC, US		
	Tel. 001 7045831173 - Fax 001 7045833166		
	info@tenaxusa.com		

1.4. Emergency telephone number

For urgent inquiries refer to **Infotrac**
US and Canada: 1-800-535-5053
Int'l: 1-352-323-3500
info@infotrac.net

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Flammable liquid, category 4	Combustible liquid.
Germ cell mutagenicity, category 2	Suspected of causing genetic defects.
Eye irritation, category 2	Causes serious eye irritation.
Skin irritation, category 2	Causes skin irritation.
Skin sensitization, category 1	May cause an allergic skin reaction.

Hazard pictograms:



Signal words: **Warning**

Hazard statements:
H227 Combustible liquid.

2. Hazards identification ... / >>

H341	Suspected of causing genetic defects.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

Precautionary statements:

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust / fume / gas / mist / vapours / spray.
P202	Do not handle until all safety precautions have been read and understood.
P201	Obtain special instructions before use.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P264	Wash the hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.

Response:

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice / attention.
P333+P313	If skin irritation or rash occurs: Get medical advice / attention.
P337+P313	If eye irritation persists: Get medical advice / attention.
P302+P352	IF ON SKIN: wash with plenty of water / . . .
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: use CO2, sand, powder to extinguish.
P363	Wash contaminated clothing before reuse.

Storage:

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Disposal:

P501	Dispose of contents / container according to applicable law.
-------------	--

2.2. Other hazards

Environmental classification as for Reg. (EC) 1272/2008 (CLP):

The product is classified as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

Classification and Hazard Statement

Hazardous to the aquatic environment, chronic toxicity, category 2 Toxic to aquatic life with long lasting effects.

Hazard pictograms:



Hazard statements:

H411	Toxic to aquatic life with long lasting effects.
-------------	--

Precautionary statements:

Prevention:

P273	Avoid release to the environment.
-------------	-----------------------------------

Response:

P391	Collect spillage.
-------------	-------------------

Storage:

--

Disposal:

P501	Dispose of contents / container according to applicable law.
-------------	--

Additional hazards

Information not available

3. Composition/information on ingredients

3. Composition/information on ingredients ... / >>

3.2. Mixtures

Contains:

Identification x = Conc. % Classification:

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE
 INDEX 603-073-00-2 $40 \leq x < 42$

Eye irritation, category 2 H319, Skin irritation, category 2 H315, Skin sensitization, category 1B H317, Hazardous to the aquatic environment, chronic toxicity, category 2 H411

EC 216-823-5
 CAS 1675-54-3
 REACH Reg. 01-2119456619-26

REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE (1:2)
 $20 \leq x < 22$

Flammable liquid, category 4 H227, Eye irritation, category 2 H319, Skin irritation, category 2 H315, Skin sensitization, category 1 H317, Hazardous to the aquatic environment, chronic toxicity, category 3 H412

EC 618-939-5
 CAS 933999-84-9
 REACH Reg. 01-2119463471-41

2,3-EPOXYPROPYL NEODECANOATE
 $6 \leq x < 7$

Germ cell mutagenicity, category 2 H341, Skin sensitization, category 1 H317, Hazardous to the aquatic environment, chronic toxicity, category 2 H411

EC 247-979-2
 CAS 26761-45-5
 REACH Reg. 01-2119431597-33-0000

* There is a batch to batch variation.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.
SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.
INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.
INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT
 The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.
UNSUITABLE EXTINGUISHING EQUIPMENT
 Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE
 Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

Combustion products: COx and calcium fumes.

5. Fire-fighting measures ... / >>

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
	TLV-ACGIH	ACGIH 2022

8. Exposure controls/personal protection ... / >>

TALC

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	2				RESP
OSHA	USA		20			
OSHA	USA	30				INHAL
OSHA	USA	10				RESP
CAL/OSHA	USA	2				RESP
NIOSH	USA	2				RESP

CASTOR OIL, HYDROGENATED

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	10				INHAL
TLV-ACGIH	-	3				RESP

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (OSHA 29 CFR 1910.138): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

HAND PROTECTION: Protect hands with work gloves for protection from chemical agents in nitrile or fluoroelastomer (EN 374-1: 2016) at least type B or higher based on the risk assessment carried out by the company. Breakthrough time > 480 minutes.

Material thickness:

NITRILE

short contact > 0.38 mm

prolonged contact > 0.55 mm

FLUOROELASTOMER

short contact > 0.50 mm

prolonged contact > 1.50 mm

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	paste	
Colour	various	

9. Physical and chemical properties ... / >>

Odour	typical		
Odour threshold	not available		
pH	not available		Reason for missing data:substance/mixture is non-polar/aprotic (eg: an organic solvent mixture)
Melting point / freezing point	not available		
Initial boiling point	not available		
Boiling range	not available		
Flash point	60 < T ≤ 93	°C	(140 < T ≤ 199,4 °F)
Evaporation rate	not available		
Flammability	not available		
Lower inflammability limit	not available		
Upper inflammability limit	not available		
Lower explosive limit	not available		
Upper explosive limit	not available		
Vapour pressure	not available		
Vapour density	not available		
Relative density	1.26	g/cm ³	
Solubility	insoluble in water		
Partition coefficient: n-octanol/water	not available		
Auto-ignition temperature	not available		
Decomposition temperature	not available		
Viscosity	not available		Remark:Trixtropic paste
Explosive properties	not available		
Oxidising properties	not available		

9.2. Other information

VOC : 7,16 % - 90,26 g/litre

10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE
 Avoid contact with: acids,bases,oxidising substances.
 Avoid unintentional contact with amines.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE
 The decomposition products depend on the temperature, the available air and the presence of other substances.
 An uncontrolled exothermic reaction of epoxy resins liberates phenolic derivatives, carbon monoxide and water.

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
 It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

11. Toxicological information ... / >>

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE (1:2)

Oral NOAEL

Rat

Dose: 300 mg/kg/d Repeated Dose 408 Repeated Dose 90-Day Oral Toxicity Study in Rodents

Exposure: 90 days repeated dose, 7 days per week

Interactive effects

2,3-EPOXYPROPYL NEODECANOATE

NOAEL Oral

Rat

Dose: 100 mg/kg/d Repeated Dose 408 Repeated Dose 90-Day Oral Toxicity Study in Rodents

Exposure: 90 days, 7 per week

ACUTE TOXICITY

2,3-EPOXYPROPYL NEODECANOATE

LD50 (Oral): > 9700 mg/kg Ratto

LD50 (Dermal): 3800 mg/kg Ratto

LC50 (Inhalation vapours): > 240 mg/m3 Ratto (4 ore)

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE

LD50 (Oral): 11400 mg/kg Ratto

LD50 (Dermal): 2000 mg/kg Ratto

REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE (1:2)

LD50 (Oral): 2900 mg/kg Ratto

LD50 (Dermal): > 2000 mg/kg Ratto

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

Skin sensitization

2,3-EPOXYPROPYL NEODECANOATE

Sensitiser: OECD 406

REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE (1:2)

Sensitiser: OECD 429

GERM CELL MUTAGENICITY

Suspected of causing genetic defects

2,3-EPOXYPROPYL NEODECANOATE

OECD 488

Subject: Mammal - Animal

Cell: Germs

Experiment: In vivo

11. Toxicological information ... / >>

CARCINOGENICITY

Does not meet the classification criteria for this hazard class
Carcinogenicity Assessment:
1675-54-3 BIS-[4-(2,3-EPOXIPROPONI)FENIL]PROPANO
IARC:3
7631-86-9 AMORFOSA SILICATA IDRATA
IARC:3

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

2,3-EPOXIPROPIL NEODECANOATE

LC50 - for Fish	9.6 mg/l/96h
EC50 - for Crustacea	4.8 mg/l/48h Daphnia (2 gg)
EC50 - for Algae / Aquatic Plants	3.5 mg/l/72h

BIS-[4-(2,3-EPOXIPROPONI)FENIL]PROPANO

LC50 - for Fish	1.3 mg/l/96h
EC50 - for Crustacea	2.1 mg/l/48h Daphnia
EC50 - for Algae / Aquatic Plants	> 11 mg/l/72h
Chronic NOEC for Crustacea	0.3 mg/l Daphnia

REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CLOROMETIL)OSSIRANO (1:2)

LC50 - for Fish	30 mg/l/96h Trota arcobaleno
EC50 - for Crustacea	47 mg/l/48h Daphnia
EC50 - for Algae / Aquatic Plants	23.1 mg/l/72h

12.2. Persistence and degradability

2,3-EPOXIPROPIL NEODECANOATE

Based on the results of two readily biodegradable studies according to the OCSE standard (Test Guideline), 2,3-epoxypropyl neodecanoate has undergone approximately 7-11% biodegradation. Therefore 2,3-epoxypropyl neodecanoate is not to be considered readily biodegradable. However, when 2,3-epoxypropyl neodecanoate was evaluated in a test compliant with OECD 302A "Inherent Biodegradability: Modified SCAS Test", the biodegradation level reached 68% +/- 5% on study days 22-36. Therefore, 2,3-epoxypropyl neodecanoate is both inherently biodegradable and ultimately biodegradable under the conditions and criteria of OECD 302A (Testing Guideline 302A).

12. Ecological information ... / >>

REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE (1:2)
 71% - Easily biodegradable - 28d

BIS-[4-(2,3-EPOXYPROPOXI)PHENYL]PROPANE
 NOT rapidly degradable

REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE (1:2)
 Rapidly degradable

12.3. Bioaccumulative potential

2,3-EPOXYPROPYL NEODECANOATE

Partition coefficient: n-octanol/water 2.6

REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE (1:2)

Partition coefficient: n-octanol/water 0.822

BCF 3.57

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.
 Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
 CONTAMINATED PACKAGING
 Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 3082

ADR / RID: In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to ADR provisions.

IMDG: In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to IMDG Code provisions.

IATA: In accordance with SP A197, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to IATA dangerous goods regulations.

14.2. UN proper shipping name

ADR / RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (BIS-[4-(2,3-EPOXYPROPOXI)PHENYL]PROPANE; 2,3-EPOXYPROPYL NEODECANOATE)
 IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (BIS-[4-(2,3-EPOXYPROPOXI)PHENYL]PROPANE; 2,3-EPOXYPROPYL NEODECANOATE)
 IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (BIS-[4-(2,3-EPOXYPROPOXI)PHENYL]PROPANE; 2,3-EPOXYPROPYL NEODECANOATE)

14. Transport information ... / >>

14.3. Transport hazard class(es)

ADR / RID: Class: 9 Label: 9



IMDG: Class: 9 Label: 9



IATA: Class: 9 Label: 9



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: Environmentally Hazardous



IMDG: Marine Pollutant



IATA: Environmentally Hazardous



14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 90	Limited Quantities: 5 L	Tunnel restriction code: (-)
	Special provision: -		
IMDG:	EMS: F-A, S-F	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 450 L	Packaging instructions: 964
	Passengers:	Maximum quantity: 450 L	Packaging instructions: 964
	Special provision:	A97, A158, A197, A215	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

TSCA:

All components of this product are listed on US Toxic Substances Control Act (TSCA) Inventory or are exempt from the listing / notification requirements.

Clean Air Act Section 112(b):

No component(s) listed.

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

15. Regulatory information ... / >>

No component(s) listed.

Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

No component(s) listed.

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

No component(s) listed.

EPCRA 313 TRI:

No component(s) listed.

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations

Massachussetts:

14807-96-6	TALC
7631-86-9	AMORPHOUS SILICATE HYDRATE

Minnesota:

14807-96-6	TALC
7631-86-9	AMORPHOUS SILICATE HYDRATE

New Jersey:

14807-96-6	TALC
------------	------

New York:

No component(s) listed.

Pennsylvania:

7631-86-9	AMORPHOUS SILICATE HYDRATE
-----------	----------------------------

California:

14807-96-6	TALC
7631-86-9	AMORPHOUS SILICATE HYDRATE

Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H227	Combustible liquid.
H341	Suspected of causing genetic defects.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAA 112 © RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112©)
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: Regulation (EC) 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REACH: Regulation (EC) 1907/2006
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112© of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"

16. Other information ... / >>

- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

01 / 03 / 05 / 08 / 09 / 10 / 11 / 12 / 14 / 16.