



PRODUCT SHEET MATT LINEN OIL COLOR INDOOR

The paint has high coverage and is painted undiluted 1-2 times a primed or non-absorbent surface. The color can be applied to almost all substrates such as PH-neutral plaster, wood, board material, previously painted surface, metal etc.

ATTENTION! Untreated highly absorbent substrates are first primed with Ottosson Linseed oil paint White Basic Indoors.

In addition to linseed oil and pigment, our matt linseed oil paint contains a unique and gentle solvent with an extremely low benzene content (0.01%), which means that the paint is neither classified as harmful to health nor environmentally hazardous.

See separate safety data sheet.

Color consumption: 6-14 sq.meters per liter depending on application method and substrate.

Tools: Brush, roller or sprayer.

Lyngby Konsult & Måleri has carried out a test on spray painting with the colour. See separate Test Report.

Gloss number: Matt approx. 10

Dust dry after approx. 10 hours.

Can be painted over after approx. 24 hours.

The painted surface is easy to clean with detergent and water after 3 weeks. The paint does not contain water and is therefore not sensitive to frost and can be stored for a long time.

Other: The paint has several advantages compared to water-soluble emulsion paints. The surface becomes more durable and easier to wipe off. The paint works in unheated spaces and has a long shelf life.