PEEL-TEK LIQUID MASKING



Version

1.0

Revision Date:

10/27/2020

MSDS Number:

F000004666

Date of last issue: -

Date of first issue: 10/27/2020

SECTION 1. IDENTIFICATION

Product name

PEEL-TEK LIQUID MASKING

00000000000028871

Product code

: F000004666

Manufacturer or supplier's details

Company Name of Supplier

Peel-Tek, LLC

Address

150 Watterson Rd Bastrop, TX 78602

Telephone

512-993-4976

Email

info@peel-tek.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS Label element

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical Name	CAS-No.	Concentration (%)	
Rubber, natural	9006-04-6	>= 30 - < 50	

SECTION 4. FIRST AID MEASURES

If inhaled

: Move to fresh air in case of accidental inhalation of vapours.

Oxygen or artificial respiration if needed.

Call a physician or poison control centre immediately.

If symptoms persist, call a physician.

In case of skin contact

: Wash off immediately with soap and plenty of water while

removing all contaminated clothes and shoes.

PEEL-TEK LIQUID MASKING



Version 1.0

Revision Date: 10/27/2020

MSDS Number: F000004666

Date of last issue: -

Date of first issue: 10/27/2020

If symptoms persist, call a physician.

In case of eye contact

: In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least

15 minutes.

Keep eye wide open while rinsing.

Remove contact lenses. Seek medical advice.

If swallowed

: Do NOT induce vomiting.

If symptoms persist, call a physician. If conscious, drink plenty of water.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

: None known.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media

: Foam

Carbon dioxide (CO2)

ABC powder Water mist

Specific hazards during fire-

fighting

: Burning produces irritant fumes.

Exposure to decomposition products may be a hazard to

Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water

courses.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Use water spray to cool unopened containers.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Exposure to decomposition products may be a hazard to

health.

SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Ensure adequate ventilation.

Material can create slippery conditions.

Use non-slip safety shoes in areas where spills or leaks can

occur.

PEEL-TEK LIQUID MASKING



Version

1.0

Revision Date:

10/27/2020

MSDS Number:

F000004666

Date of last issue: -

Date of first issue: 10/27/2020

Environmental precautions

: Prevent further leakage or spillage if safe to do so.

Do not let product enter drains.

Do not allow contact with soil, surface or ground water. Do not allow uncontrolled discharge of product into the envi-

ronment.

Methods and materials for containment and cleaning up

: Dam up.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up and shovel.

Pick up and transfer to properly labelled containers.

Clean contaminated floors and objects thoroughly while ob-

serving environmental regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

: Keep away from open flames, hot surfaces and sources of

ignition. No special protective measures against fire required.

Advice on safe handling

: Wear personal protective equipment.

Handle with care.

Take care to avoid waste and spillage when weighing, loading

and mixing the product.

Conditions for safe storage

: No smoking.

Keep in properly labelled containers.

Observe label precautions.

Keep containers tightly closed in a dry, cool and well-

ventilated place.

Materials to avoid

: Do not freeze.

Keep away from food and drink. Keep away from tobacco products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Rubber, natural	9006-04-6	TWA (Inhal- able fraction)	0.0001 mg/m3 (as inhalable allergenic proteins)	ACGIH

Engineering measures

: Handle only in a place equipped with local exhaust (or other

appropriate exhaust).

Maintain air concentrations below occupational exposure

standards.

Personal protective equipment

PEEL-TEK LIQUID MASKING



Version 1.0 Revision Date: 10/27/2020

MSDS Number: F000004666

Date of last issue: -

Date of first issue: 10/27/2020

Respiratory protection

: No personal respiratory protective equipment normally re-

quired.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Use NIOSH approved respiratory protection.

Hand protection

Material

: Impervious gloves

Eye protection

: Safety glasses with side-shields Tightly fitting safety goggles

Franchiold

Face-shield

Skin and body protection

: Chemical resistant apron

Footwear protecting against chemicals Skin should be washed after contact.

Change working clothes after each workshift.

Protective measures

Avoid contact with skin.

When using do not eat, drink or smoke.

Personal protective equipment comprising: suitable protective

gloves, safety goggles and protective clothing

The type of protective equipment must be selected according to the concentration and amount of the dangerous substance

at the specific workplace.

Hygiene measures

Do not smoke.

Keep away from food and drink.

Avoid contact with skin, eyes and clothing. Change working clothes after each workshift.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

: liquid

Colour

: green

Odour

: characteristic

рН

: 8.0 - 9.5

Melting point/range

: No data available

Boiling point/boiling range

: 212 °F

Flash point

: No data available

Vapour pressure

: No data available

Relative density

: No data available

PEEL-TEK LIQUID MASKING



Version

1.0

Revision Date: 10/27/2020

MSDS Number: F000004666

Date of last issue: -

Date of first issue: 10/27/2020

Density

: 899 - 1,078 kg/m3

Solubility(ies)

Water solubility

: completely miscible

Solubility in other solvents

: not determined

Partition coefficient: n-

octanol/water

: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

: Stable

Possibility of hazardous reac-

tions

: Stable under recommended storage conditions.

Conditions to avoid

: Protect from frost.

Incompatible materials

: Oxidizing agents

Strong acids and strong bases

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of ni-

trogen (NOx), dense black smoke.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity

: Remarks: This information is not available.

Acute inhalation toxicity

: Remarks: This information is not available.

Acute dermal toxicity

: Remarks: This information is not available.

Skin corrosion/irritation

Product:

Remarks: This information is not available.

Serious eye damage/eye irritation

Product:

Remarks: This information is not available.

PEEL-TEK LIQUID MASKING



Version

1.0

Revision Date:

10/27/2020

MSDS Number:

F000004666

Date of last issue: -

Date of first issue: 10/27/2020

Respiratory or skin sensitisation

Product:

Remarks: This information is not available.

Carcinogenicity

IARC

No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by OSHA.

NTP

No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: No data available

Toxicity to daphnia and other

aquatic invertebrates

Remarks: No data available

Toxicity to algae

Remarks: No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

PEEL-TEK LIQUID MASKING



Version

1.0

Revision Date:

10/27/2020

MSDS Number:

F000004666

Date of last issue: -

Date of first issue: 10/27/2020

Can be landfilled or incinerated, when in compliance with local

regulations.

Contaminated packaging

Clean container with water.

Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulation

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 302

: No chemicals in this material are subject to the reporting re-

quirements of SARA Title III, Section 302.

SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis)

reporting levels established by SARA Title III, Section 313.

California Prop 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

PEEL-TEK LIQUID MASKING



Version 1.0

Revision Date: 10/27/2020

MSDS Number:

F000004666


Date of last issue: -

Date of first issue: 10/27/2020

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

Revision Date

: 10/27/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN