

PC 608



CONTRACTOR GRADE, CO-EXTRUDED POLY-HANGING DUCT TAPE



TYPICAL APPLICATIONS

- For use when building containments and a variety of other applications in remediation, restoration and abatement jobs
- Can be used for mold and asbestos removal

PRODUCT FEATURES

- High tack
- Excellent holding power with good conformability
- Cold temperature adhesion
- Easy to unwind and tear
- Made using Polybonded CO-EX Technology®

CONSTRUCTION

Overall Grade/Function: Contractor

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Blended rubber

STANDARD WIDTH(S)

1.88 in 2.83 in

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

Tested in accordance with UL 723

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	26 lbs/in width	45.5 N/10 mm
Adhesion to Stainless Steel	80 oz/in width	8.76 N/10 mm
Thickness	9 mils	0.23 mm
Elongation	20%	20%
Service Temperature Range	35 F to 200 F	2 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

