

PC 745



SUPER-TOUGH, PREMIUM CLOTH TAPE

TYPICAL APPLICATIONS

- For use on rough or dirty surfaces
- For heavy duty repairs that demand a ferociously strong hold
- Can also be used as a bottom board tape in the manufactured housing industry

PRODUCT FEATURES

- All-weather performance
- Quick stick, even to rough or dirty surfaces
- Reinforced backing; extra thick adhesive
- Superior holding power
- Made using Polybonded CO-EX Technology

CONSTRUCTION

Overall Grade/Function: Super-Tough

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber

STANDARD WIDTH(S)

1.88in 2.83in

STANDARD LENGTH(S)

30 yd

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	47 lbs/in width	82.3 N/10 mm
Adhesion to Stainless Steel	105 oz/in width	11.5 N/10 mm
Thickness (nominal)	17 mils	0.43 mm
Service Temperature Range	32 F to 200 F	0 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



Shurtape
TECHNOLOGIES