

TECHNICAL DATA SHEET (TDS)

LIQUID WAX RR/1

ID Product Code 006

Pag | 1

Repolishable liquid wax for maintenance of marble, granite, terrazzo, agglomerated marble.





Product description:

Emulsified liquid wax studied for maintenance of floors made of natural stones as marble, granite, limestone, sandstone, terrazzo, agglomerated and engineered stones. Its formula is based on natural and synthetic waxes. It gives a brilliant and warm shining. RR/1 is the ideal product for to maintain natural shine of floors. It is a special liquid wax that, once applied, has good resistance to washing when regular detergents are used.

Chemical characteristics:

Appearance Color Odor Specific gravity at 20° C (68° F) Hydro-solubility Shelf life at 20°C (68° F)

Liquid Milky white Perfume of lavender $1,00 \pm 0,02$ Soluble in every ratio $8,00 \pm 0,02$ 24 months in original container

Instruction for use

Surface must be clean and dry; stains, mildew, crusting must be scraped off. On floors that have deposits of previous waxes, clean with Wax Remover DECER-DOS. Spread the wax, diluted 1 to 20 in lukewarm water (1 dosing cap in 1 liter of water), using a damp cloth, a wax spreader fleece or a mop. Allow the wax to dry without walk over it, then vigorously rub with a woolen cloth or buff with household polishing machine or with a floor machine equipped with white polishing disc. Periodic cleaning must be done with our neutral Detergent LEM-3. After these washings the wax can to be polished as described above. Repeat applications periodically.

Suggestion for use and recommendations:


- Let dry well the wax on the floor before buffing to achieve a better result.
- We suggest always diluting the wax in order to avoid build-up on the floor.
- In the case of floor application, pay attention to the following slipperiness of the surface; slipperiness will be reduced after a few days and as a result of periodic washing will continue to maintain a great shiny.
- Product for indoor use.
- Read carefully recommendations printed on label and perform a preliminary test on a small area before actual use.

Application surfaces

Marble, granite, terrazzo, marble resin, marble-cement, all agglomerated materials.













TECHNICAL DATA SHEET (TDS)

Application tools











Pag | 2

Fleece

Scrubbing brush

Household polisher

Single disc machine

Coverage

For the polishing of polished marble and granite after grit 800, one liter of product can treat from 150 to 250 sqm (1600 to 2700 sq ft)

Safety procedures

As far as the proper working procedures is concerned, we recommend to consult Material Safety Data Sheets issued according to E.U. rules and to follow your national laws concerning safety in the working place. MSDS is available on our web site www.bellinzoni.com.

Packing

Item N°	Content	Pcs
006BRR01	1,00 lt (1,05 qt)	12
006BRR05	5,00 lt (1,32 gal)	4
006BRR25	25,00 lt 6,60 gal)	1

The composition of the tins is Steel (ACC), drums are in High Density Polyethylene (HDPE). After use, comply with the local and national regulations currently in force regarding recycling. Our packing is conformed as per U.N. rules for inland transport (A.D.R.) and by sea (I.M.O.) for transportation via air refer to updated rules (I.A.T.A.). For further information regarding transport please check MSDS.

Trademark and Origin of the good

BELLINZONI® is a registered trademark of Bellinzoni company. The law considers a trademark to be a form of property and any misuse can be persecuted by law. Bellinzoni s.r.l. declares that our product RR/1 is MADE IN ITALY.





