

SAFETY DATA SHEET

Date Issued: 3/24/15

Page 1 of 5

SECTION 1 – COMPANY and PRODUCT IDENTIFICATION

MANUFACTURER

GARDNER-GIBSON CORPORATION
4161 East 7th Avenue
Tampa, FL 33605

EMERGENCY TELEPHONE NUMBER
1-800-424-9300 CHEMTREC

Product Information
813-248-2101
gardner-gibson.com

Product Class

Acrylic Latex Sealant used in building construction.

Product Code Number

5227-1-61

Trade Name

Black Jack Roof & Construction Sealant - White

SECTION 2 – HAZARDS IDENTIFICATION

Product Classification: No need for classification according to GHS criteria.

Effects of acute toxicity:

EYES: Direct contact may cause irritation.

SKIN: May cause irritation to sensitive skin or open wounds.

INHALATION: May cause irritation to respiratory passages.

INGESTION: May cause nausea.

Precautions:

Wear suitable protective clothing, gloves and eye protection.

If the product adheres to exposed skin, irritation may occur when the product dries.

Use with local exhaust ventilation.

Do not take internally. Wash hands before eating or drinking.

SECTION 3 – COMPOSITION / INFORMATION on INGREDIENTS

INGREDIENT	Content (By Weight)	TLV PPM	PEL - TWA PPM
Diisononyl Phthalate (DINP) CAS # 28553-12-0	4.0 - 7.0%	N.E.	N.E.
Mineral Spirits (Stoddard solvent) CAS # 8052-41-3	0.5 - 1.5%	100	100
All other ingredients in this waterborne product are trade secret.	91.5 - 95.5%	N.A.	N.A.

There are no ingredients in this product of unknown acute toxicity.

N.E. = Not Established

N.A. = Not Applicable

SAFETY DATA SHEET

Black Jack Roof & Construction Sealant - White

Page 2 of 5

SECTION 4 – FIRST-AID MEASURES

Inhalation: If inhaled, remove victim to fresh air and keep at rest in a position comfortable for breathing. If signs/symptoms of difficulty in breathing continue, get immediate medical attention.

Skin: Rinse skin immediately with plenty of clean water for 5 to 10 minutes. Remove contaminated clothing. If skin irritation occurs get medical advice/attention.

Eye(s): Rinse cautiously with water for several minutes. Remove contact lenses if present and if it is easy to do so. Continue rinsing. If eye irritation persists get medical advice/attention.

Ingestion: If swallowed, do not induce vomiting. If conscious, give 2 to 3 glasses of water and seek medical advice/attention immediately.

SECTION 5 – FIRE-FIGHTING MEASURES

Extinguishing Media: Carbon dioxide, dry chemical, foam, or water spray

Unusual Fire and Explosion Hazards: None known

Special Fire Fighting Procedures: Water can be used to cool fire-exposed containers. Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled: Observe all personal protective equipment recommendations described in Section 8. Wipe up or scrape up spilled material and contain for disposal. Final cleaning may require use of hot water and/or detergents. Dispose of saturated absorbent or cleaning materials appropriately.

SECTION 7 – HANDLING and STORAGE

Precautions for safe handling: Keep away from extreme heat. Do not get in eyes, on skin, on clothing. Do not swallow product. Wash thoroughly after handling. Use with adequate ventilation.

Conditions for safe storage: Store in a cool, dry place in the original container. Keep container closed when not in use. Store the product away from strong oxidizing chemicals. Avoid extreme heat. Store above 7 °C (45 °F). Product will freeze below 0 °C (32 °F).

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory Protection: Use with adequate ventilation.

Skin Protection: Chemical resistant gloves are recommended for prolonged exposure.

Eye Protection: Wear safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT: None required.

SAFETY DATA SHEET

Black Jack Roof & Construction Sealant - White

Page 3 of 5

SECTION 9 – PHYSICAL and CHEMICAL PROPERTIES

Appearance (Physical state, color):	Thick fluid paste, bright white
Odor:	Mild, acrylic-like
Odor Threshold:	No information is available.
pH:	7.5 – 8.5
Melting point:	No data is available.
Initial Boiling Point & Boiling Range:	100 °C to 244 °C (212 °F to 471 °F)
Flash Point:	>94 °C (>201 °F)
Evaporation Rate:	Slower than Ether
Flammability:	Nonflammable
Upper/Lower Flammability Limits:	No data is available.
Vapor Pressure:	17.5 mm Hg @ 20 °C (68 °F)
Vapor Density:	Heavier than air
Density:	1.46 g/cm ³ (12.1 Lbs/gal) 21 °C (70 °F)
Solubility (in water):	Dispersible in water
Partition coefficient (n-octanol/water):	No data is available.
Auto-ignition temperature:	No data is available.
Decomposition temperature:	>250 °C (482 °F)
Viscosity (Brookfield RV, 5 rpm):	430,000 cP ±100,000 @ 21 °C (70 °F)

SECTION 10 – STABILITY and REACTIVITY

Reactivity: No hazardous reactions if stored and handled as prescribed.

Chemical Stability: The product is stable if stored and handled as prescribed.

Hazardous decomposition products: Carbon dioxide, carbon monoxide, and hydrocarbons.

Hazardous polymerization: Will not occur. The product is chemically stable.

SECTION 11 – TOXICOLOGICAL INFORMATION

Primary routes of exposure: Routes of entry for the product into the human body are accidental ingestion, accidental eye contact, and prolonged skin contact. Inhalation of the vapor released from the product as it dries is dependent upon the absence of proper ventilation during use of the product.

Acute Toxicity/Effects:

EYES: Direct contact may cause irritation.

SKIN: May cause irritation to sensitive skin or open wounds.

INHALATION: May cause irritation to respiratory passages.

INGESTION: May cause nausea/gastrointestinal distress.

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

SAFETY DATA SHEET

Black Jack Roof & Construction Sealant - White

Page 4 of 5

SECTION 11 – TOXICOLOGICAL INFORMATION (continued from page 3)

No human toxicological studies (Oral, Inhalation or Dermal) have been conducted on this compounded product.

No animal toxicological studies (Oral, Inhalation or Dermal) have been conducted on this compounded product.

Chronic Toxicity/Effects:

EYES: No data available.

SKIN: No data available.

INHALATION: No data available.

INGESTION: No data available.

SECTION 12 – ECOLOGICAL INFORMATION

Ecological Fate: * No data available.

Persistence/Degradability: * No data available.

Bioaccumulation Potential: * No data available.

Mobility in Soil: * No data available.

SECTION 13 – DISPOSAL CONSIDERATIONS

Dispose of unused product and/or empty containers in accordance with local, regional, national, and/or international regulations.

Do not discharge into drains/surface waters/groundwater or open ground/soil.

SECTION 14 – TRANSPORT INFORMATION

DOT Proper Shipping Name: Not Regulated by D.O.T.

DOT Hazard Class: None

DOT UN/NA Number: None

Packing Group: None

IMO/IMDG – International Maritime Transport Shipping Name: Not Regulated.

IATA – International Air Transportation Association: Not Regulated.

Do not transport this product on passenger seats or inside the passenger compartment of any vehicle. Transport product in the cargo area of the vehicle and secure it on and under protective cloths or plastic wrap to prevent damage due to accidental spills.

SECTION 15 – REGULATORY INFORMATION

SARA Title III – No substances are contained in this product subject to the reporting requirements of EPCRA Section 313 of the Super Fund Amendments and Reauthorization Act, 40 CFR Part 372.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

California Proposition 65 Chemical Warning (California Health and Safety Code #25249.5 et seq): This product contains chemicals known to the state of California to cause cancer, birth defects or reproductive harm.

SAFETY DATA SHEET

Black Jack Roof & Construction Sealant - White

Page 5 of 5

SECTION 16 – OTHER INFORMATION

Hazardous Materials Identification System (HMIS)

Health	Flammability	Physical Hazard	Personal Protection Equipment (PPE)
1	0	0	B – Safety glasses and gloves

Legend: 0 = Insignificant 1 = Slight 2 = Moderate 3 = High

Other Precautions: Keep out of the reach of children.
Protect from freezing.

Disclaimer/Statement of Liability:

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to verify the suitability and completeness of such information for a particular use. Gardner-Gibson does not accept liability for any loss or damage that may occur from the use of this information.

Prepared by: Morton Jones
3-24-15
Product # 5227-1-61