



# 6150

## ROLL ROOFING ADHESIVE Data Sheet

### Bonding adhesive for new construction or repairs

- Use with roll roofing
- Great adhesive & bonding strength
- Adds extra waterproof protection
- Fiber reinforced
- Heavy brush grade

**WHAT IS THIS?** Black Jack 6150 Roll Roofing Adhesive is a liquid applied, brushable, asphalt based adhesive, designed to bond sheets roll roofing and also adds additional waterproofing protection to the roof surface. No Heating Needed.

**TOOLS/SUPPLIES:** Roof brush, gloves and roll roofing material.

**PREPARATION:** Surfaces must be clean, free of surface rust and loose material. Apply in exterior applications only. Wear protective clothing. Don't apply to wet or damp surfaces. Don't apply to plastic, EPDM, Hypalon or similar type of synthetic rubber roof system. If there is a question on compatibility, test a small section first before application to entire surface area.

**APPLICATION:** Use brush to spread across surface of roof and roll the rolls of roofing material into wet adhesive. Apply on a clear warm day with no rain forecasted for 24-36 hours. MIXING MAY BE REQUIRED TO ENSURE PRODUCT UNIFORMITY. DO NOT APPLY DIRECT HEAT/FLAMES OR THIN. Apply when surface temperatures are between 50° and 120° F. In colder weather (50°F and below), product should be stored in heated room (70° to 80° F.) at least 24 hours prior to application to promote ease of application. Product formulated to be used year round.

**COVERAGE RATE:** Covers approx. 40 - 45 sq. ft. per gallon.

**PRECAUTIONS:** Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100°F. Do not reuse empty containers. Do not use in drinking water or food systems.

**CLEAN-UP:** Clean tools or spills with mineral spirits or paint thinner.

### TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Flash Point (ASTM 93-52)	105°F (41°C)
Weight Per Gallon, lbs.	8.5 lbs.
Consistency	Brush
Residue by Evaporation, %	74% Min.
Cure Time	24-48 Hours

**Approx. Shipping Weights:** (Note: All approx. weights include container.)

5 gallons (18.9L)	46
55 gallons (208.2L)	501

### CAUTION!: COMBUSTIBLE MIXTURE. HARMFUL OR FATAL IF SWALLOWED. KEEP OUT OF THE REACH OF CHILDREN.

For exterior use only. Contains petroleum based products. Keep away from heat, sparks and open flame. Eye, skin and respiratory irritant. In case of contact with eyes, flush with plenty of clean, room temperature water. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid prolonged breathing of vapor or spray mist. Use only with adequate ventilation. In case of irregular or stopped breathing, administer oxygen and/or give artificial respiration. Get medical attention, immediately. Contact with skin should be followed by washing with soap and water. If swallowed, do not induce vomiting. Call physician immediately. Seal container when not in use.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

VOC/VOS - 250 g/L max. (2.07lbs./gal.)

**COMPLIANCE:** SCAQMD RULE # 1168

ASPHALT C.A.S.# 8052-42-4

MINERAL SPIRITS C.A.S.# 8052-41-3

CELLULOSE FIBER C.A.S.# 9004-34-6

Product is asbestos free

PATENT PENDING

© 2007 Gardner-Gibson, Inc.  
Manufactured by: Gardner-Gibson, Inc.  
P.O. Box 5449, Tampa, FL 33675  
www.gardner-gibson.com

See SDS for more info

**Limited Warranty:** Gardner-Gibson, Inc. warrants that this product, when applied in accordance with our written directions in applications recommended by us as suitable for the product, is free of defects in material and workmanship for a period of 12 months from the date of purchase. If you notify us of such a defect and provide adequate proof of purchase during this warranty period, we will replace the defective product at no cost to you. This limited warranty is the sole and exclusive remedy for any such defective product. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESSED OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/ OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE, AND GARDNER-GIBSON, INC. WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449  
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com