



Section 1 - Product and Company Identification

Material Name	- Ready Road Repair® Pothole Patch
Chemical Category	- Mixture
Product Code(s)	- 6430-9-50
Product Description	- Permanent, all-weather pothole patch for asphalt, concrete, brick, and wood.
Product Use	- Blend of stones and asphalt designed to fill larger holes (4" or more) and depressions to make a permanent repair.
Synonyms	- Pothole Patch
Manufacturer	- Gardner-Gibson 4161 E. 7th Avenue Tampa, FL 33605 United States
Telephone	
Technical	- 813-248-2101 - Customer Service: 8 AM - 5 PM M-F Eastern Standard Time
<u>Emergency</u>	- 800-424-9300 - CHEMTREC
<u>Emergency</u>	- 703-527-3887 - CHEMTREC (Outside US)
Preparation Date	- 05/18/2015

Section 2 - Hazards Identification

Signal Word: WARNING

Hazards and Precautions

Contains Petroleum Based Products. Keep away from heat, sparks, and open flame. The solvent portion of this product is classified as Combustible Liquid per GHS. May be harmful if swallowed. May cause respiratory irritation. Causes eye irritation. Causes mild skin irritation. Vapors may cause headache, nausea, and respiratory tract irritation. Use only with adequate ventilation. Avoid prolonged breathing of vapor or spray mist. Keep product closed and properly stored when not in use. Avoid contact with skin. Use protective gloves, safety glasses, and protective clothing when using this product. Do not use in drinking water or food systems. Do not reuse empty container. Make sure container is sealed and secured in an upright position during transportation. Do not eat or drink while using this product and wash hand thoroughly after use.

Prevention Avoid prolonged breathing of any dust, fume, gas, mist, and vapors during product application. Do not handle until all safety precautions have been read and understood. Always work in area with adequate ventilation.

Response IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.



Physical Form	- Granular solid
Color	- Black
Odor	- N/A
Flash Point	- >140°F (Based on Fuel Oil ingredient)
HCS2012	- Combustible Liquid – Category 4. Specific Target Organ Toxicity Repeated Exposure - Category 2, Skin Corrosion/Irritation - Category 2, Serious Eye Damage, Eye Irritation - Category 2, Carcinogenicity - Category 1A (Asphalt fumes – High Temperatures / Quartz – dust)

WHMIS

- Class D - Poisonous and Infectious Materials - Division 2 - Subdivision A

**GHS**

- Combustible Liquid – Category 4. Specific Target Organ Toxicity Repeated Exposure - Category 2, Skin Corrosion/Irritation - Category 2, Serious Eye Damage, Eye Irritation - Category 2, Carcinogenicity - Category 1A (Asphalt fumes – High Temperatures / Quartz – dust)

Route Of Entry

- Inhalation, Skin, Eye

Potential Health Effects**Inhalation****Acute (Immediate)**

- May cause irritation.

Chronic (Delayed)

- No data available

Skin**Acute (Immediate)**

- May cause irritation.

Chronic (Delayed)

- Repeated and prolonged exposure may cause dermatitis.

Eye**Acute (Immediate)**

- May cause burning and redness or swelling of the eyes. May cause irritation.

Chronic (Delayed)

- Repeated and prolonged exposure may cause irritation.

Ingestion**Acute (Immediate)**

- May be harmful or fatal if swallowed.

Chronic (Delayed)

- No data available

Carcinogenic Effects

- See Section 11 - Toxicological Information.

Carcinogenic Effects			
	CAS	IARC	NTP
Asphalt	8052-42-4	Group 2B-Possible Carcinogen	Under Consideration
Quartz	14808-60-7	Group 1-Carcinogenic	Known Human Carcinogen

	CAS	IARC	NTP
Asphalt	8052-42-4	Group 2B-Possible Carcinogen	Under Consideration
Quartz	14808-60-7	Group 1-Carcinogenic	Known Human Carcinogen

See Section 12 for Ecological Information.

Section 3 - Composition/Information on Ingredients

Hazardous Components						
Chemical Name	CAS	%(wt)	UN;EINECS	LD50/LC50	Classifications According to Regulation/Directive	
Aggregate	Various	90% TO 95%				
Asphalt Cement (as fumes)	8052-42-4	1-5%	NA1999, 232-490-9	Ingestion/Oral-Rat LD50 · >5000 mg/kg Inhalation-Rat LC50 · >94.4 mg/m ³	WHMIS: Other Toxic Effects - D2A UN GHS: Carc. 2; Eye Irrit. 2A; Skin Irrit. 2	
Fuels, Diesel No. 2	68476-34-6	1-5%			NDA	
Quartz	14808-60-7	Varies	238-878-4		UN GHS: Carc. 1A; STOT RE 1	

Hazardous Components						
Chemical Name	CAS	%(wt)	UN;EINECS	LD50/LC50	Classifications According to Regulation/Directive	
Aggregate	Various	90% TO 95%				
Asphalt Cement (as fumes)	8052-42-4	1-5%	NA1999, 232-490-9	Ingestion/Oral-Rat LD50 · >5000 mg/kg Inhalation-Rat LC50 · >94.4 mg/m ³	WHMIS: Other Toxic Effects - D2A UN GHS: Carc. 2; Eye Irrit. 2A; Skin Irrit. 2	
Fuels, Diesel No. 2	68476-34-6	1-5%			NDA	
Quartz	14808-60-7	Varies	238-878-4		UN GHS: Carc. 1A; STOT RE 1	

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

See Section 11 for Toxicological Information.

Section 4 - First Aid Measures

- | | |
|-------------------|---|
| Inhalation | - Remove to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Seek medical attention. |
| Skin | - Wash the contaminated area of body with soap and fresh water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. |
| Eye | - Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing eye. If eye irritation persists: Get medical advice/attention. |
| Ingestion | - Call a physician or poison control center immediately. Do not give anything by mouth to an unconscious person. Do NOT induce vomiting. |

See Section 2 for Potential Health Effects.

Section 5 - Fire Fighting Measures

- | | |
|---|---|
| Extinguishing Media | - SMALL FIRES: Dry chemical, carbon dioxide, foam and water fog. Water may cause frothing. |
| Firefighting Procedures | - Keep unauthorized personnel away. Stay upwind. |
| Unusual Fire and Explosion Hazards | - Some of these materials may burn, but none ignite readily. May release irritating or toxic gases, fumes, or vapors. |
| Hazardous Combustion Products | - Oxides of carbon, hydrogen sulfide and sulfur oxides. |
| Protection of Firefighters | - Wear positive pressure self-contained breathing apparatus (SCBA). |
| Flash Point | - >140°F |

Section 6 - Accidental Release Measures

- | | |
|--------------------------------------|--|
| Personal Precautions | - Do not handle damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate enclosed areas. |
| Emergency Procedures | - Stop leak if you can do it without risk. Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up. |
| Environmental Precautions | - Do NOT wash away into sewer |
| Containment/Clean-up Measures | - Contain spilled material and do not allow to flow into public sewers or water systems. Shut off all ignition sources. |
| Special Procedures | - Unused material can be recycled. Dispose of in accordance with Federal, State, and Local regulations. |

Section 7 - Handling and Storage

- | | |
|---|--|
| Handling | - Keep containers tightly closed when not in use. Use only with adequate ventilation. |
| Storage | - Keep only in the original container/package in a cool well-ventilated place. Keep away from fire. Keep container closed when not in use. |
| Special Packaging Materials | - No data available |
| Incompatible Materials or Ignition Sources | - Avoid contact with strong oxidizing agents and acids |

Section 8 - Exposure Controls/Personal Protection

Personal Protective Equipment Pictograms



- | | |
|--------------------|---|
| Respiratory | - When used with adequate ventilation, a respirator is not normally required. If required, use a NIOSH-approved air purifying respirator with organic vapor |
|--------------------|---|

cartridge or supplied air respirator. This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

Eye/Face

Hands

Skin/Body

General Industrial Hygiene

Considerations

Engineering

Measures/Controls

- Wear ANSI approved safety glasses with side shields or safety goggles.
- Use impervious gloves.
- Wear clothing that covers the skin to prevent skin exposure.
- Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke during work. Wash hands before eating.
- Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values.

Exposure Limits/Guidelines					
	Result	ACGIH	NIOSH	OSHA	United States - California
Fuels, Diesel No. 2 (68476-34-6)	TWAs	<100 mg/m3			
Quartz (14808-60-7)	TWAs	0.025 mg/m3 TWA (respirable fraction)	0.05 mg/m3 TWA (respirable dust)	Not established	0.3 mg/m3 PEL (total dust); 0.1 mg/m3 PEL (respirable dust)
Asphalt (8052-42-4)	TWAs	0.5 mg/m3 TWA (as benzene soluble aerosol, fume, inhalable fraction)	5 mg/m3 Ceiling (15 min, fumes)	Not established	5 mg/m3 PEL (fume)

Exposure Control Notations

ACGIH

- Asphalt (8052-42-4):Carcinogens:A4 - Not Classifiable as a Human Carcinogen (fume, coal tar-free)
- Quartz (14808-60-7):Carcinogens:A2 - Suspected Human Carcinogen

Key to abbreviations

- PEL = Permissible Exposure Level determined by the Occupational Safety and Health Administration (OSHA)
- TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

Physical Form

- Granular solid

Appearance/Description

- Black

Color: Black		Odor: Slight Petroleum	
Taste: NDA		Odor Threshold: N/A	
Specific Gravity:	N/A	Evaporation Rate:	N/A
Vapor Density:	N/A	VOC (Wt.):	NDA
Bulk Density:	NDA	VOC (Vol.):	<150 g/l
Solubility in Water:	Insoluble	Flash Point:	>140°F

Section 10 - Stability and Reactivity

Stability

- Stable under normal temperatures and pressures.

Hazardous Polymerization

- Hazardous polymerization not indicated.

Conditions to Avoid

- Avoid contact with strong oxidizing agents and acids.

Incompatible Materials

- Strong oxidizers and acids.

Hazardous Decomposition Products

- Carbon monoxide, carbon dioxide and hydrocarbons.

Section 11 - Toxicological Information

Component Name	Concentration	CAS	Data
Asphalt (as fumes)	<5%	8052-42-4	Acute Toxicity: ; orl-rat LD50:>5000 mg/kg; ihl-rat LC50:>94.4 mg/m3; ihl-hmn TDLo:10 mg/m3/5.5Y-I Tumorigen/Carcinogen: ; skn-mus TDLo:905 gm/kg/2Y-I

Other Component Information

- IARC has concluded that the following chemicals in this product are carcinogenic to humans (Group 1): silica, quartz. ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz. NTP has listed the following chemicals in this product as known human carcinogens: silica, quartz. Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist. Airborne exposure is not expected with this product. The materials are encapsulated and would only be release if the dry material was sanded. Exposure could increase if the product is sprayed.

Other Information

- This product contains petroleum asphalt. Petroleum asphalt is not listed as a carcinogen by OSHA or NTP. The National Institute of Occupational Safety and Health (NIOSH), has concluded that at higher temperatures roofing asphalt fumes are a potential occupational carcinogen. If this product is heated or comes in contact with heated material, avoid breathing fumes. This product may contain small amounts of polycyclic aromatic hydrocarbons (PAH's) which are recognized carcinogens in humans and experimental animals. Mouse skin painting studies of roofing asphalt vapor concentrate have shown evidence of tumor formation associated with localized skin irritation in recent studies. Inhalation studies of high airborne concentrations of asphalt/bitumen fumes in rats and mice produced bronchitis, pneumonitis, and lung changes such as fibrosis and cell damage.

Section 12 - Ecological Information

Ecological Fate

- No data available.

Persistence/Degradability

- No data available.

Bioaccumulation Potential

- No data available.

Mobility in Soil

- No data available.

Section 13 - Disposal Considerations

Product

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transportation Information

DOT - United States - Department of Transportation

Shipping Name: Not Restricted

TDG - Canada - Transport of Dangerous Goods

Shipping Name: Not Restricted

IMO/IMDG –International Maritime Transport

Shipping Name: Not Restricted

Section 15 - Regulatory Information

SARA Hazard Classifications

- Acute, Chronic, Fire

Risk & Safety Phrases

- California PROP 65: Asphalt and Asphalt Fumes may contain detectable

amounts of chemicals known to the State of California to cause cancer or reproductive harm. .

State Right To Know				
Component	CAS	MA	MN	NJ
Asphalt	8052-42-4	Yes	Yes	Yes
Quartz	14808-60-7	Yes	Yes	Yes
Fuels, Diesel No.2	68476-34-6	No	No	Yes

Inventory			
Component	CAS	EU EINECS	TSCA
Asphalt	8052-42-4	Yes	Yes
Quartz	14808-60-7	Yes	Yes
Fuels, Diesel No.2	68476-34-6	Yes	Yes

Canada

Labor

Canada - WHMIS - Classifications of Substances

▪ Asphalt	8052-42-4	<5%	Not listed.
▪ Quartz	14808-60-7	Varies	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS website.)

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

▪ Asphalt	8052-42-4	<5%	Asphalt and Asphalt fumes may contain detectable amounts of chemicals known to the state of California to cause cancer or reproductive harm.
▪ Quartz	14808-60-7	Varies	carcinogen, initial date 10/1/88 (airborne particles of respirable size)

Section 16 - Other Information

Last Revision Date	- 5/18/2015
Prepared By	- Gardner-Gibson
Disclaimer/Statement of Liability	- This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to verify the suitability and completeness of such information for particular use. Gardner-Gibson does not accept liability for any loss or damage that may occur from the use of this information.