



# 6460

## DRIVE-PATCH BLACKTOP CRACK & HOLE REPAIR Data Sheet

- Heavy Duty Sand/Asphalt Mix
- Smooth Finish
- Ideal for Larger Cracks or Small Holes

**DESCRIPTION:** Drive-Patch Blacktop Crack & Hole Repair is a ready to use cement textured patching compound. It is a latex fortified and provides a long lasting durable patch that resists gas, oil and chemical deterioration. Use Drive-Patch Blacktop Crack & Hole Repair to repair small holes and cracks (up to 3" deep) or to smooth out surfaces that are damaged by gasoline and oil spillage. Dries black.

**PREPARATION:** Use Driveway Kleen™ prior to applying driveway patches and coating to surface to remove dirt, and light oil stains. This degreaser will allow for much improved adhesion of driveway sealers. On heavier oil stains, apply liberally and scrub area for best results. Rinses thoroughly with water leaving no puddles. Remove any loose and flaking material from area prior to application.

**APPLICATION:** Apply product on a clear, warm, sunny day when surface temperature is at least 65°F and rising. Mix contents to a uniform consistency and apply to dampened surface. Do not apply to cracks or holes which have water puddles. Use trowel or putty knife to apply Drive-Patch to problem areas, ending with a smooth surface finish. For repairs or depths greater than 1", it is recommended that the compound be applied in layers. This will assure proper drying and strength. Area is ready to be sealcoated in approximately 24 hours.

DO NOT APPLY AT TEMPERATURES BELOW 50°F  
DO NOT ALLOW STORED PRODUCT TO FREEZE.

**COVERAGE RATE:** Approximately 10 lbs. will patch an area 10 sq. ft. x 1/8 inch deep.

**CLEAN-UP:** Clean tools with soap and water when wet, or an orange citrus cleaner when cured.

**PRECAUTIONS:** When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills.

### TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon, lbs.	15.5 lbs.
Residue by Evaporation, %	90 min.
Combustible Solvents	None
Consistency	Trowel
Cure Time (at recommended coverage)	24 hours
Application Temperatures	65°F and rising
Flammability (Flash point, °F solvent)	N/A
Clean-up Tools	Soap and water when wet Orange citrus cleaner when cured

**Approx. Shipping Weights:** (Note: All approx. weights include container.)  
1 gal. pail 10 lbs. (4.5 kg)

### CAUTION! HARMFUL OR FATAL IF SWALLOWED

For exterior use only. Contains petroleum based products. Keep away from heat, sparks and open flame. Use only with adequate ventilation. Eye and skin irritant. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid contact with skin and breathing vapor. If swallowed, do not induce vomiting. Call physician immediately. Seal container when not in use. Do not use in drinking water or food systems.

### CAUTION! EYE, SKIN AND RESPIRATORY IRRITANT - DO NOT INGEST KEEP OUT OF REACH OF CHILDREN.

**CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ).** WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

**VOC/VOS = 10g/l**

CLAY C.A.S.#1332-58-7  
SAND C.A.S.#14808-60-7  
ASPHALT C.A.S.#8052-42-4

Product is asbestos free

PATENT PENDING

© 2006 Gardner Asphalt

Manufactured by Gardner Asphalt, P.O. Box 5449, Tampa, FL 33675

### WARRANTY AND DISCLAIMER:

Gardner Asphalt Co., warrants this product to give satisfactory results when our directions are followed in its use and application, for a period of 12 months from the date of purchase. In no event however shall the manufacturer be liable for an amount in excess of the purchase price of the product used. If not completely satisfied, return to place of purchase for a refund.

See MSDS for more info



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449  
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardnerasphalt.com