

## DYNAMITE 780

- Strippable
- Good tack and slip
- Ideal for paste machines
- Recommended for light to heavy weight wallcoverings

Dynamite® 780 Strippable Heavy Duty Clear Wallcovering Adhesive is a general purpose product recommended for hanging light to heavy weight wallcoverings.

- Strippable on primed or unprimed drywall with all strippable, fabric-backed vinyls, after proper curing
- Flowable, pourable viscosity for easy use with paste machines
- Dries clear and cleans up with water when wet

### DIRECTIONS

Material Preparation. Use as supplied. Do not dilute.

Surface preparation. Make sure wall surface is sound, clean and dry. For best results, wash wall surface with a diluted household bleach solution; rinse and let dry thoroughly. Wear protective glasses and rubber gloves to avoid eye and skin irritation. Repair or fill cracks in wall with spackling paste. Prime difficult surface (oil-based or alkyd paints/primers, glossy paints, vinyl, mylar, etc.) with a Dynamite Wallcovering Primer.

### APPLICATION

Hang wallcovering according to manufacturer's instructions. Apply adhesive evenly, making sure sufficient adhesive is on edges and corners. As each wallcovering strip is positioned on wall, smooth firmly and evenly. Immediately remove adhesive from face of washable wallcoverings and adjacent surfaces with a clean, wet sponge. Dry with a clean, lint-free towel to check for paste residue. Important Note: When hanging porous or delicate wallcoverings (such as silks, grasscloths and papers), apply adhesive directly to wall. Hang one test strip and check for possible bleed-through or staining before continuing. Some wallcoverings can be stained by water alone.

Do not hang over oil/alkyd paint or paint primer unless it is first primed with a Dynamite wallcovering primer.

### COVERAGE

Five gallons of adhesive will hang up to 40 single rolls. (1,200 sq. ft./5 gal.).

### CLEAN-UP

Immediately remove adhesive from face of washable wallcoverings and adjacent surfaces with a clean, wet sponge. Dry with a clean, lint-free towel to check for paste residue. Clean equipment with water.

### STORAGE

Strippable Heavy Duty Clear Adhesive should be stored at temperatures between 40°F and 100°F. Protect from freezing.

### DISPOSAL

Contains no hazardous ingredients. Remove any residual product from the container, allow product to air-dry, and then dispose of in conjunction with non-hazardous refuse. Consult your sanitation department for more information regarding disposal of empty containers. Contact your state-designated environmental agency for additional information concerning the possible re-use or recycling of unused water-based products.

### TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon	9.8 lbs.
Solids by Weight	32.0%
Viscosity (ASTM D-2697)	30,000-33,000 cps
pH	6.2-7.0
Flammability	Non-flammable
Clean-up Tools	Water
Resistance to Mold/Mildew	Excellent
Color	Light cream
Freeze/Thaw Stability	Yes

### Approx. Shipping Weights: (Note: All approx. weights include container.)

1 gallon (3.8L)	9.5 lbs.
5 gallons (18.9L)	48.0 lbs.

**CAUTION! MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. KEEP OUT OF THE REACH OF CHILDREN.**

For emergency information call (800) 424-9300. For additional safety and chronic hazard information, refer to the Material Safety Data Sheet for this product. Close container after each use. If sanding is done, wear a dust mask to avoid breathing of sanding dust. FIRST AID: In case of skin contact, wash off quickly with plenty of water, then soap and water; remove contaminated clothing. For eye contact flush immediately with large amounts of water, especially under lids, for at least 15 minutes. Obtain emergency medical treatment. If swallowed, obtain medical treatment immediately. If inhalation causes physical discomfort remove to fresh air. Restore and support continued breathing. Have trained person give oxygen, if necessary. If discomfort persists or any breathing difficulty occurs, get medical help. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Do not use in drinking water or food systems. KEEP FROM FREEZING.

**CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ).** WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

**VOC:** <1.1g/L of material

### INGREDIENTS:

STARCH (9005-25-8), WATER (7732-18-5), DEHYDRATED CORN SYRUP (68131-37-3), HYDROLYZED STARCH (8029-43-4)

### LIMITED WARRANTY

The Gardner-Gibson Company warrants that this product, when applied in accordance with our written directions in applications recommended by us as suitable for this product, is free of defects in material and workmanship for a period of 12 months from the date of purchase. If you notify us of such a defect and provide adequate proof of purchase during this warranty period, we will replace the defective product to you at no cost to you. This limited warranty is the sole and exclusive remedy for any such product.

THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE AND THE GARDNER-GIBSON COMPANY WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

© 2007 Gardner-Gibson, Inc.  
Manufactured by:  
Gardner-Gibson, Inc., Tampa,  
FL 33675

See SDS for more info

Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449  
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com