



6025 Foundation & Roof Coating

Non-Fibered Coating For Damproofing Exterior Masonry Surfaces

- Weatherproofs - provides a barrier against moisture
- Easy to apply
- Thin bodied to penetrate and protect masonry surfaces
- Ideal for foundations

Black Jack® Foundation & Roof Coating Black Jack Foundation & Roof Coating is a liquid applied, thin “paint like”, asphalt based coating designed to penetrate and seal foundation block walls below grade and masonry roof surfaces. Prevents moisture from penetrating walls. Can also be used to seal and protect underground wood footings and metal surfaces.

PREP THE AREA: Remove all dust, dirt, and debris. Patch all cracks or seams with Black Jack 6230 All-Weather Roof Cement. Remove all rust or loose paint from metal surfaces. Do not apply over damp or wet surfaces. On foundations apply only over cured concrete and masonry. Not for use on sloped roofs, as product will run and drip.

HOW TO APPLY: Use brush or roller to spread across surface of foundation or roof.

COVERAGE RATE: This 5-gallon pail covers 350 - 500 sq. ft., per coat, over masonry and roof surfaces, depending on texture and porosity of surface. Two coats are recommended.

CLEAN UP: Tools should be cleaned with paint thinner or mineral spirits.

PRECAUTIONS: Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100 °F. This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Do not reuse empty containers. Do not use in drinking water or food systems.

Limited Warranty: Gardner-Gibson warrants product to be free of material defects for a period of 12 months, the “Warranty Period”, from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper prep and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser’s timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
6025-9-34	1 gal.	6.75" x 6.75" x 7.75"	3.6 qt. / 3.4 L	8 lbs.	6/case	027134602511
6025-9-30	5 gal.	12" x 12" x 14.75"	4.75 qt. / 18 L	40 lbs.	1 ea.	027134602559

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101