



6125 Roof & Foundation Coating Fibered Liquid Asphalt Coating

- Helps protect roof and masonry surfaces
- Renews worn roof surfaces
- Reinforced with fibers
- Good for protecting foundations

Black Jack® Roof & Foundation Coating is a fibered liquid applied, brushable, asphalt based coating designed to renew worn roof surfaces.

PREP THE AREA: Surfaces must be clean, free of surface rust and loose material.

HOW TO APPLY: Use brush or roller to spread across surface of roof.

HOW MUCH DO I NEED? Covers approximately 50 sq. ft. per gallon. 250 sq. ft. per 5 gallon pail.

DO's and DON'Ts: Do apply in exterior applications only. Do wear protective clothing. Don't apply to wet surfaces. Do not use on EPDM, Hypalon or PVC surfaces. Do not use on single ply or synthetic roofs. If there is any question regarding compatibility, test a small section first.

FOR BEST RESULTS: Apply on a clear warm day with no rain expected for 24 hours. In colder weather (50°F and below), product should be stored in heated room (70° to 80°F.) at least 24 hours prior to application to promote ease of application. MIXING MAY BE REQUIRED TO ENSURE PRODUCT UNIFORMITY. DO NOT APPLY DIRECT HEAT/FLAMES OR THIN. Apply when surface temperatures are between 50° and 120°F. Product formulated to be used year round. Allow product to cure a minimum of 30 - 60 days prior to application of reflective coating.

PRECAUTIONS: Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100°F. This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Do not reuse empty containers. Do not use in drinking water or food systems.

HOW TO CLEAN-UP: Clean tools or spills with paint thinner or mineral spirits.

WARRANTY AND DISCLAIMER: Gardner-Gibson warrants product to be free of material defects for a period of 12 months, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper prep and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
6125-9-34	1 gal.	6.75" x 6.75" x 7.75"	3.6 qt. / 3.4 L	9 lbs.	6/case	027134612510
6125-9-30	5 gal.	12" x 12" x 14.75"	4.75 qt. / 18 L	44 lbs.	1 ea.	027134612558

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101