



# 6148 Rubr-Seal Rubberized Roof & Flashing Cement

## RUBR-SEAL

- Stops leaks fast
- Best for extreme weather conditions
- Longest lasting rubberized seal
- Ideal on flat or vertical surfaces
- Best stick in wet or dry conditions



**Black Jack® Rubr-Seal Rubberized Roof & Flashing Cement** is our best quality roof cement, designed for year round use in any weather conditions to stop and seal leaks. This high performance product provides an exceptionally long lasting seal, formulated to repair cracks, seams and holes in roofing materials. Black Jack Rubr-Seal is also designed for use in new construction and setting flashings, drip edges and other roofing edges. It seals and provides a rubberized layer of waterproofing protection. Use on roofs around skylights, vents, exhaust pipes, chimneys, valleys, and in the construction or repair of flashings, roll roofing and shingles. Great for repairs and installation of mod-bit membranes, and on laminate Shingles. Also excellent for use as a heavy duty below grade and underground waterproofer, and damproofer.

**PREPARATION:** Trowel, reinforcing fabric and gloves, are recommended for application. Apply generously with a trowel or putty knife. Surfaces must be clean and free of surface rust and loose material. Apply in exterior applications only. Wear protective clothing.

**PREPARATION:** Trowel, reinforcing fabric and gloves, are recommended for application. Apply generously with a trowel or putty knife. Surfaces must be clean and free of surface rust and loose material. Apply in exterior applications only. Wear protective clothing.

**APPLICATION:** It is highly recommended to reinforce the repair with a strip of Universal Patching Fabric. Work material to an even consistency over and into the area to be repaired approximately 1/8" to 1/2" thick, two or three inches beyond the problem area. Embed fabric into the cement and cover with a second layer of cement. Form a feathered edge with cement where chimney's, vent pipes, and other projections meet the roof line. **DO NOT APPLY DIRECT HEAT/FLAMES OR THIN.** Apply when surface temperatures are between 50 °F and 120 °F. In colder weather (50 °F and below), product should be stored in heated room (70 °F to 80 °F) at least 24 hours prior to application to promote ease of application. Product formulated to be used year round. Allow product to cure a minimum of 30 - 60 days prior to application of reflective coating.

**COVERAGE RATE:** One gallon covers approximately 12 sq. ft. when applied 1/8" thick.

**PRECAUTIONS:** Protective clothing, gloves, and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100 °F. This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Do not use on EPDM, TPO, PVC or other rubber/synthetic surfaces. Do not use on single ply or synthetic roofs. If there is a question regarding compatibility, test a small section first. Products should be applied in accord with NRCA guidelines. Do not reuse empty containers. Do not use in drinking or food water systems. Do not heat or thin. Seal container when not in use and store in a well ventilated area. Protect from freezing. Protect building inlets from product fumes during application.

**CLEAN-UP:** Clean tools or spills with mineral spirits.

**WARRANTY AND DISCLAIMER:** Gardner-Gibson warrants product to be free of material defects for a period of 15 years, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper preparation and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product to repair the affected area or prorate a portion of the purchase price of the defective product based on the claim period. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. **THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.**

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
6148-9-62	10 fl.oz.	2" x 2" x 11.5"	10 fl.oz. / 296 mL	1 lbs.	12/crtn	027134614866
6148-9-34	1 gal.	7.75" x 7.75" x 7.75"	3.6 qt. / 3.4 L	9 lbs.	6/case	027134614811
6148-9-27	2.75 gal.	13.3" x 13.3" x 12"	3.3 gal. / 12.52 L	28 lbs.	36/crtn	027134614835

**www.gardner-gibson.com**  
**Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449**  
**Phone: (813) 248-2101**