



6150

Roll Roofing Adhesive

Bonding Adhesive For New Construction Or Repairs

- Use with roll roofing
- Great adhesive & bonding strength
- Restores worn roof surfaces
- Fiber reinforced
- Brush grade

Black Jack® Roll Roofing Adhesive is a liquid applied, brushable, asphalt based adhesive, designed to bond sheets roll roofing and also adds additional waterproofing protection to the roof surface. No Heating Needed.

TOOLS/SUPPLIES: Roof brush, gloves and roll roofing material.

PREPARATION: Surfaces must be clean, free of surface rust and loose material. Apply in exterior applications only. Wear protective clothing. Don't apply to wet or damp surfaces. Don't apply to plastic, EPDM, Hypalon or similar type of synthetic rubber roof system. If there is a question on compatibility, test a small section first before application to entire surface area.

APPLICATION: Use brush to spread across surface of roof and roll the rolls of roofing material into wet adhesive. Apply on a clear warm day with no rain forecasted for 24 - 36 hours. MIXING MAY BE REQUIRED TO ENSURE PRODUCT UNIFORMITY. DO NOT APPLY DIRECT HEAT/FLAMES OR THIN. Apply when surface temperatures are between 50 °F and 120 °F. In colder weather (50 °F and below), product should be stored in heated room (70 °F to 80 °F.) at least 24 hours prior to application to promote ease of application. Product formulated to be used year round.

COVERAGE RATE: Covers approx. 40 - 45 sq. ft. per gallon.

PRECAUTIONS: Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100 °F. Do not reuse empty containers. Do not use in drinking water or food systems.

CLEAN-UP: Clean tools or spills with mineral spirits or paint thinner.

LIMITED WARRANTY: Limited Warranty: Gardner-Gibson warrants product to be free of material defects for a period of 12 months, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper prep and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

| AVAILABLE SIZES | | | | | | |
|-----------------|-----------|-----------------------|-------------------|-------------|--------|--------------|
| PRODUCT CODE | UNIT SIZE | UNIT DIMENSIONS | FILL LEVEL | UNIT WEIGHT | PACK | UPC |
| 6150-9-34 | 1 gal. | 6.75" x 6.75" x 7.75" | 3.6 qt. / 3.4 L | 10 lbs. | 6/case | 027134615016 |
| 6150-9-30 | 5 gal. | 12" x 12" x 14.75" | 4.7 gal. / 17.8 L | 48 lbs. | 1 ea. | 027134615054 |

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101