



6453 Drive-Maxx™ 700 Filler and Sealer

DRIVE-MAXX™ 700

- Restores blacktop surfaces
- Heavy-duty sand mix, added traction
- Advanced gel, faster & E-Z to apply
- Latex enhanced, durable rubberized finish

Black Jack® Drive-Maxx™ 700 is a better quality rubberized blacktop filler and sealer designed for asphalt pavements. This product renews the look of old worn driveways, and contains sand particles to fill in small cracks. **Drive-Maxx™ 700** is enhanced with latex to improve performance and durability. Gel Technology enables faster and easier installation.

SURFACE PREPARATION: Newly paved asphalt surfaces must be allowed to cure for a minimum of six months or a full summer's season prior to application of any sealer. Driveways should be pressure washed before sealcoating. For oil stains, apply a degreaser (or dish soap) and scrub into surface to penetrate oil spots. This will promote proper bonding and will help prevent adhesion failures. Repair cracks and holes with **Black Jack® Speed-Fill Elastic Crack Filler** for longest lasting results. For cracks and holes larger than 1" use **Black Jack® Speed-Patch**. For larger potholes use **Ready Road Repair Permanent Pot Hole Patch** (allow 6 weeks to cure). All repaired areas must be allowed to cure, see product instructions for curing times.

APPLICATION: Turn all pails upside down the night before, or at least prior to sealcoating. Temperatures must be 60°F and rising, but below 90°F during application. Clean driveway thoroughly and rinse. Remove puddles and then apply sealer to a slightly damp surface (not wet). A small amount of water separation in the pail is normal, and should be easily mixed in. Pour out 1/3 of the container and spread product across the blacktop surface with a squeegee. Squeegee must be used to spread product and for proper application rates. After application with squeegee, a follow up with a brush may be used if a textured surface is desired. Complete the entire driveway in one continuous application to prevent "color shading". If multiple pails are used, it is best to match batch codes and blend the end of one pail into the beginning of the other to maintain consistent coloring and texture. Do not over apply as this may lead to tracking. Do not apply if rain or cold temperatures are expected within 36 hours. This sealer is not recommended or warranted for use on surfaces containing slopes of greater than 20°.

COVERAGE RATE: Approximate coverage rate for this pail: 350 sq/ft on smooth driveways, 300 sq/ft. on rough/worn driveways. Rough driveways have a higher surface area so more product is needed. Coverage rates vary depending upon the condition of the existing surface. A brush and/or squeegee works best, allowing the sealer to penetrate the driveway surface. Working in a small area at a time apply thin coat, brushing away any excess as you seal. Use a cross pattern of application to insure all voids are filled and sealed. Driveway must cure approx. 2 - 4 hours for foot traffic and 24 - 48 hours for vehicle traffic. Humid or cloudy conditions may prolong curing time. Two thin coats are strongly recommended. Thick coats will result in uneven coverage, tracking and drying problems. Apply second coat perpendicular to the first, after the first coat has cured (approx. 3 - 6 hours). When possible, match batch codes on lids when using multiple containers.

CLEAN-UP: While wet, clean tools with warm water and soap. If dry, scrub with citrus based cleaner.

PRECAUTIONS: Do not mix or blend this product with any other driveway products. Protective clothing and eyewear should be used during application of these products, as product may cause skin irritation. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. **CLOSE CONTAINER WHEN NOT IN USE.** Do not reuse empty containers. Dispose of in an environmentally acceptable manner, if not for yours, than for your children's sake. This container is recyclable if cleaned immediately. Do not pour excess product in drains or watercourses. **KEEP FROM FREEZING.** Do not use in drinking water or food systems.

WARRANTY AND DISCLAIMER: Gardner-Gibson warrants product to be free of material defects for a period of 7 years, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper preparation and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product to repair the affected area or prorate a portion of the purchase price of the defective product based on the claim period. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Warranty not applicable for areas that have ponding water, poor drainage or snow removal damage. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. **THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.**

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
6453-9-30	5 gal.	12" x 12" x 14.75"	4.75 gal. / 18 L	49 lbs.	1 ea.	027134645358

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101