



6460 Speed-Patch™ Blacktop Crack & Hole Repair

SPEED-PATCH™

- Heavy Duty Sand/Asphalt Mix
- Smooth Finish
- Ideal for Larger Cracks or Small Holes

DESCRIPTION: Speed-Patch™ Blacktop Crack & Hole Repair is a ready to use sand and asphalt patching compound that spreads to a smooth finish. It is latex fortified which provides a long lasting durable repair for small holes and cracks (up to 3" wide and 3" deep). The product dries black to match existing asphalt pavements.

PREPARATION: Use a cleaner/degreaser prior to applying driveway patches and coating to surfaces. All dirt, and light oil stains must be removed for proper adhesion of driveway repair products and sealers. Rinse areas thoroughly with water leaving no puddles. Remove any loose and flaking material from area prior to application.

APPLICATION: Apply product on a clear, warm, sunny day when surface temperature is at least 65 °F and rising. Do not apply if rain or cooler temperatures are expected within 24 hours. Mix contents to a uniform consistency and apply to slightly dampened surface. Do not apply to cracks or holes which have water puddles. Use trowel or putty knife to apply Speed-Patch to fill problem areas, ending with a smooth surface finish. For repairs or depths greater than 1", it is recommended that the compound be applied in layers. This will assure proper drying and strength. In warm drying conditions, product can be coated in 1 hour for sealcoating. Allow 24 hours before full cure.

If weather conditions are cool and or damp, drying time will be extended. Allow 24 - 48 hours before vehicle traffic.

COVERAGE RATE: Approximately 10 lbs. will patch an area 10 sq. ft. x 1/8 inch deep.

CLEAN-UP: Clean tools with soap and water when wet, or an orange citrus cleaner when cured.

PRECAUTIONS: When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not apply at temperatures below 50 °F. Do not allow stored product to freeze. Seal container when not in use. Do not use in drinking water or food systems.

WARRANTY AND DISCLAIMER: Gardner-Gibson warrants product to be free of material defects for a period of 12 months, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper prep and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
6460-9-20	10 gal.	8.5"w x 7"h	10 lbs / 4.5 kg	10 lbs.	4/case	027134646010

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101