

Dynamite[®]
DEFENDER[™] **234mx**

- DynaGuard Defense Matrix[™] gives a mildew resistant* coating

- Strippable for easy maintenance and flexibility
- Longest open time for superb wet tack and slip
- Optimized for pasting machines



Dynamite[®] **DEFENDER**[™] **234mx** is a revolutionary, mildew-resistant* heavy duty clear adhesive that takes the worry out of hanging wallcovering. Ideal for hanging all wallcovering types – from lightweight foil to heavyweight commercial vinyl. It is highly suited for hanging delicate and difficult wallcoverings such as silk, suede, velour, linen, burlap, grasscloth and stringcloth. This remarkable adhesive offers the easiest application when pasting cuts and gives excellent slip for repositioning. **Dynamite Defender 234mx** will provide worry-free strippability when the time comes for future redecorating projects. For complete mold and mildew protection, this formula is Pure Pasteurized[™] then enhanced with the **Dynamite**[®] **Defense Matrix**[™]. Used with **Dynamite**[®] **DEFENDER**[™] **235 Mildew-Resistant* Primer**, this product creates the safest, most powerful protection, eliminating mold concerns behind the paper.

*This adhesive contains a preservative which inhibits the growth of mildew on the surface of the adhesive film.

SURFACE PREPARATION: Make sure wall surface is sound, clean and dry. For best results, use a diluted household bleach solution to prepare and clean walls. Repair or fill cracks in wall with spackling prior to priming.

Plaster – New plaster must age at least 30 days before hanging wallcovering. Prime with **Dynamite**[®] **DEFENDER**[™] **235**.

Drywall – New drywall must be wiped down with a damp cloth to remove dirt, dust, grease, wax and peeling paint. Prime with **Dynamite**[®] **DEFENDER**[™] **235**.

Other Porous Surfaces – Walls must be clean, dry, smooth and structurally sound. Prime with **Dynamite**[®] **DEFENDER**[™] **235**.

Glossy Surfaces – Ceramic tile, glossy paint, existing vinyl wallcoverings, Formica[®], glass or plastic should be primed with **Dynamite**[®] **DEFENDER**[™] **235**.

Commercial Grade II & III – Prime with **Dynamite**[®] **DEFENDER**[™] **235** when hanging heavyweight commercial grade papers.

Strippability – No primer is needed when hanging strippable, fabric-backed vinyl wallcoverings. Adhesive and primer (if used) must be completely cured prior to stripping.

DO NOT USE OVER OIL/ALKYD PAINT/PRIMER OR VARNISH UNLESS PRIMED WITH DYNAMITE[®] **DEFENDER**[™] **235**.

APPLICATION: *Hang wallcovering according to manufacturer's instructions.* Stir to thin paste to desired consistency. **Do not dilute.** Apply evenly, making sure sufficient adhesive is on edges and corners. Apply to wallcovering with a roller, stiff brush or pasting machine. Allow proper booking time according to manufacturer's instructions. **Immediately** remove adhesive from face of washable wallcoverings and adjacent surfaces with a clean, wet sponge. (*FABRICS, FOILS, STRINGS, GRASSCLOTH AND SILK – When hanging delicate wallcoverings, special care must be taken in keeping the adhesive off the face of the wallcovering as it may cause permanent discoloration. It is recommended that a sample of the selected wallcovering be tested for degree of stain resistance prior to the installation. Some wallcovering can be stained by water alone.*)

COVERAGE: 280 to 330 sq. ft. per gallon - depending on the weight (Type I, II, or III) of the wallcovering and the condition of the wall. Fully primed surfaces will allow the maximum coverage rate when hanging lightweight (Type I) wallcovering.

CLEAN-UP: **Immediately** remove adhesive from face of washable wallcoverings and adjacent surfaces with a clean, wet sponge. Dry with a clean, lint-free towel to check for paste residue. Clean equipment with water.

PRECAUTIONS: Do not store at temperatures above 100 °F or below 40 °F. **KEEP FROM FREEZING.** This product is not intended for long term storage once pail is opened and a portion of its contents used. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not reuse empty containers. Do not use in drinking water or food systems.

QUALITY PROMISE: Gardner-Gibson warrants product to be free of material defects for a period of 12 months, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper prep and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. **THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.**

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
7236-3-30	5 gal.	12" x 12" x 14.75"	4.75 gal. / 18 L	50 lbs.	1 ea.	027134723650