



# 6435

## POURABLE DRIVEWAY CRACK SEALER Data Sheet

- Protects driveway by preventing moisture penetration
- Fills cracks up to 1/2" wide
- Easy-to-use pour spout

**DESCRIPTION:** Black Jack® Pourable Driveway Crack Sealer is ideal for filling cracks 1/2 inch wide or smaller in any blacktop or concrete surface. It dries to a black, hard rubber seal, providing a crack-free surface prior to the application of Black Jack Driveway Sealers on blacktop surfaces.

**SURFACE PREPARATION:** Surface must be clean and free of loose material, dirt and dust. Cracks and joints may be hosed clean, but remove standing water before applying crack filler. Cracks over 1/2" deep should be partially filled with sand or other suitable material.

**APPLICATION: DO NOT DILUTE.** Shake this gallon container thoroughly to mix contents before and during use. Pour into crack which is preferably damp (not wet), filling to slightly above surface. For best results do not apply when temperature is below 50° F. Do not use in cracks more than 1/2" in width. Deep cracks may require filling partially with sand or other material. Allow to harden before permitting traffic. Allow 24 hours cure time prior to application of driveway sealer.

**COVERAGE RATE:** One gallon fills 200-225 linear feet of 1/4" x 1/4" cracks.

**CLEAN UP:** Wash fresh product from tools with soap and water. Use citrus-based cleaner if material has dried.

**PRECAUTIONS:**

Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and bottle is secure and upright. Do not allow bottle to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100°F. Do not reuse empty containers. Do not use in drinking water or food systems. **DO NOT ALLOW PRODUCT TO FREEZE.**

**DESCRIPCION:** Black Jack® Sellador de Grieta de Camino de entrada de Pourable es ideal para llenar las grietas 1/2 pulgada ancha o más pequeña en cualquier asfalto o superficie concreta. Seca a un sello negro y duro del caucho, proporcionando una superficie de grieta-liberta antes de la aplicación de Selladores Negros de Camino de entrada de Jack en superficies de asfalto.

**PREPARACION DE SUPERFICIE:** La superficie debe ser limpia y libre de flojo material, la tierra y el polvo. Las grietas y las coyunturas pueden ser regadas con una manga limpio, pero quitan parándose agua. Las grietas más de 1/2" profundo debe ser llenado de parcialmente la arena u otra materia conveniente.

**APLICACION:** No DILUYA. Sacuda este contenedor de galón para mezclar completamente el contenido antes de y durante el uso. Vierta en la grieta que está preferiblemente húmeda (no mojó), llenando a ligeramente encima de superficie. Para mejores resultados no aplica cuando temperatura es abajo 50° F. No utilice en grietas más de 1/2" en la anchura. Las grietas profundas pueden requerir relleno parcialmente con arena u otra materia. Permita endurecer antes de permitir el tráfico. Permita 24 tiempo del curación de horas antes de la aplicación de sellador de camino de entrada.

**TASA del ALCANCE:** Un galón llena 200-225 pies lineales de 1/4" X 1/4" grietas.

**LIMPIE:** Lave el producto fresco de instrumentos con el jabón y el agua. Utilice disolvente si material ha secado.

**PRECAUCIONES:** La ropa y las gafas protectoras deben ser utilizadas durante la aplicación de estos productos. No permita que el balde caiga ya que eso puede causar que la tapa se suelte lo cual puede resultar en fugas. No debe transportarlo sobre asientos de pasajeros ni a dentro del compartimiento de pasajeros de ningún vehículo. Almacene el producto en el área de cargo del vehículo, y sujételo por encima de paños protectores para evitar que ocurran daños debidos a derrames accidentales. No almacene a temperaturas superiores a 100°F (37,8°C). No debe usarse en sistemas alimenticios o de agua potable. No utilice en sistemas potables de agua ni alimento.

**TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS**

Flash Point N/A	Waterbased
Weight Per Gallon, lbs.	8.7 lbs.
Viscosity	Pourable
Residue by Evaporation, %	55% Min.
Cure Time	24 Hours

**Approx. Shipping Weights:** (Note: All approx. weights include container.)

1 gallon (3.8L) Plastic Jug	8.7 lbs.
-----------------------------	----------

**VOC=30 g/l (0.4 lb./ gal) Maximum**

Asphalt/El Asfalto	CAS# 8052-42-4
Clay/La Arcilla	CAS# 1332-58-7
Water	CAS# 7732-18-5
Polymer	Proprietary / Mixture

**DANGER!: HARMFUL OR FATAL IF SWALLOWED.  
CAUTION!: KEEP OUT OF REACH OF CHILDREN  
CAUTION!: COMBUSTIBLE**

For exterior use only. Contains petroleum based products. Keep away from heat, sparks, and open flame. Eye, skin and respiratory irritant. In case of contact with eyes, flush with plenty of warm water. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid prolonged breathing of vapor or spray mist. (NIOSH/MSHA TC 23C or equivalent). Use only with adequate ventilation. In case of irregular or stopped breathing, administer oxygen and/or give artificial respiration. Get medical attention immediately. Contact with skin should be followed by washing with soap and water. If swallowed, do not induce vomiting. Call physician immediately. Do not use in drinking water systems. Seal container when not in use. When transporting product, be sure lid is tight and product is kept upright and secure.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ) Detectable amounts of some chemicals known to the State of California to cause cancer, birth defects or other reproductive harm may be found in various Gardner-Gibson, Inc. petroleum based products and their vapors. Read and follow label directions and information given on Material Safety Data Sheets and use care when handling or using all petroleum products.

**EL CUIDADO!  
PERJUDICIAL O FATAL SI TRAGADO.  
MANTENGA FUERA DEL ALCANCE DE NIÑOS.**

Para el uso exterior sólo. Contiene petróleo los productos basados. Aleje del calor, las chispas, y abra la llama. El ojo, la piel y sustancia irritante respiratoria. En caso de contacto con los ojos, enjuague inmediatamente con abundante agua limpia y a temperatura ambiente. Las personas con piel o sensibilidad respiratoria no deben utilizar el producto sin la protección suficiente. Evite respirar prolongado de la niebla de vapor o rocío. Utilice sólo con ventilación adecuada. En caso de respirar irregular o parado, administre oxígeno y/o da la respiración artificial. Consiga la atención médica inmediatamente. El contacto con piel debe ser seguido lavando con el jabón y el agua. Si tragado, no induce vomitar. Llame a médico inmediatamente. CALIF. PROP .65. ADVERTENCIA QUIMICA (CODIGO DE SALUD Y SEGURIDAD DE CALIFORNIA #25249.5 ET SEQ) ADVERTENCIA: Este producto contiene sustancias químicas conocidas por el Estado de California que pueden causar cancer, defectos de nacimiento o daños reproductores. Utilice la protección apropiada y la ventilación adecuada, cuando se usa producto.

**LIMITED WARRANTY: Gardner-Gibson, Inc.** warrants that this product, when applied in accordance with our written directions in applications recommended by us as suitable for the product, is free of defects in material and workmanship for a period of 12 months from the date of purchase. If you notify us of such a defect and provide adequate proof of purchase during this warranty period, we will replace the defective product at no cost to you. This limited warranty is the sole and exclusive remedy for any such defective product.

THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESSED OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/ OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE, AND GARDNER-GIBSON, INC. WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

See SDS for more info



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449  
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com