



# 6456

## BLACK MAXX 600 Data Sheet

### BLACK MAXX 600 - 6 Year Warranty Dura-Gel Blacktop Resurfacer



- Durable 6-year protection
- Gel formula for less work
- Renews blacktop surfaces
- Traction Gard™ skid resistors

**Black Jack® Black Maxx 600** is a premium quality rubberized blacktop resurfacer designed for asphalt pavements. This product is designed to renew the look of older worn driveways. This heavy duty blend of asphalt, sand and latex is ideal to fill in cracks and smooth out imperfections. Gel Technology enables easier and faster installation.

**SURFACE PREPARATION:** Newly paved asphalt surfaces must be allowed to cure for a minimum of six months or a full summer's season prior to application of any sealer. Driveways must be cleaned with Driveway Kleen™, spray on cleaner & degreaser before sealcoating. For oil stains, apply Driveway Kleen™ liberally and scrub into surface to penetrate oil spots. This step promotes proper bonding and will help prevent adhesion failures. Repair cracks and holes with Black Jack® Speed-Fill Elastic Crack Filler for longest lasting results. For cracks and holes larger than 1" use Black Jack® Speed-Patch. For larger potholes use Ready Road Repair Permanent Pot Hole Patch (allow 6 weeks to cure). All repaired areas must be allowed to cure, see product instructions for curing times.

**APPLICATION:** Turn all pails upside down the night before, or at least prior to sealcoating. Temperatures must be 65°F and rising, but below 90°F during application. Clean driveway with Drive Kleen and thoroughly rinse. Remove puddles and then apply sealer to a slightly damp surface (not wet). A small amount of water separation in the pail is normal, and should be easily mixed in. Pour out 1/3 of the container and spread product across the blacktop surface with a squeegee. Squeegee must be used to spread product and for proper application rates. After application with squeegee, a follow up with a brush may be used if a textured surface is desired. Complete the entire driveway in one continuous application to prevent "color shading". If multiple pails are used, it is best to match batch codes and blend the end of one pail into the beginning of the other to maintain consistent coloring and texture. Do not over apply as this may lead to tracking. Do not apply if rain or cold temperatures are expected within 36 hours. This sealer is not recommended or warranted for use on surfaces containing slopes of greater than 20°.

**COVERAGE RATE:** Coverage rates vary depending upon the condition of the existing surface. A brush and/or squeegee works best, allowing the sealer to penetrate the driveway surface. Working in a small area at a time apply thin coat, brushing away any excess as you seal. Use a cross pattern of application to insure all voids are filled and sealed. Driveway must cure approx. 2-4 hours for foot traffic and 24-48 hours for vehicle traffic. Humid or cloudy conditions may prolong curing time. Two thin coats are strongly recommended. Thick coats will result in uneven coverage, tracking and drying problems. Apply second coat perpendicular to the first, after the first coat has cured (approx. 3-6 hours). When possible, match batch codes on lids when using multiple containers. Approximate Coverage Rate for 5 gallon pail: 350 sq/ft on smooth driveways, 300 sq/ft. on rough/worn driveways.

**CLEAN-UP:** While wet, clean tools with warm water and soap. If dry, scrub with citrus based cleaner.

**PRECAUTIONS:** Do not mix or blend this product with any other driveway products. Protective clothing and eyewear should be used during application of these products, as product may cause skin irritation. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. **CLOSE CONTAINER WHEN NOT IN USE.** Do not reuse empty containers. Dispose of in an environmentally acceptable manner, if not for yours, than for your children's sake. This container is recyclable if cleaned immediately. Do not pour excess product in drains or watercourses. Caution should be taken on linoleum floors, which may experience slight discoloration from household traffic stains, including asphalt driveway sealers. Consult your linoleum manufacturer for suggestions. **KEEP FROM FREEZING.** Do not use in drinking water or food systems.

### TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon, lbs.	10.8 - 11.0 lbs.
Residue by Evaporation, %	50% ± 1%
Combustible Solvents	None
Consistency	Brush, Roller or Squeegee
Cure Time (50% Relative Humidity, 70°F)	2 hours
Full Cure (50% Relative Humidity, 70°F)	24-48 hours
Application Temperatures	65°-90°F
Flammability	N/A waterbased
Clean-up Tools	Soap & water when wet Mineral spirits when dry

**Approx. Shipping Weights:** (Note: All approx. weights include container.)

4.75 gallons (18L)	58 lbs.
55 gallons (208.2L)	630 lbs.

### CAUTION!: HARMFUL OR FATAL IF SWALLOWED.

#### FOR EXTERIOR USE ONLY. KEEP OUT OF REACH OF CHILDREN.

Contains petroleum based products. Keep away from heat, sparks and open flame. Use only with adequate ventilation. Eye and skin irritant. In case of contact with eyes, flush with plenty of clean, room temperature water. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid contact with skin and breathing vapor. If swallowed, do not induce vomiting. Call physician immediately. In case of contact with skin, wash thoroughly with soap and water.

**CALIF. PROP. 65 • CHEMICAL WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Use proper protection and adequate ventilation, when using product.

**VOC:** less than 6.0 g/L

Asphalt C.A.S.# 8052-42-4  
Clay C.A.S.# 1332-58-7  
Fillers C.A.S.# 14808-60-7  
Latex C.A.S.# 9003-55-8

Product is asbestos free

PATENT PENDING

© 2012 Gardner-Gibson, Inc.

Manufactured by Gardner-Gibson, Inc.,  
P.O. Box 5449, Tampa, FL 33675 USA

**WARRANTY AND DISCLAIMER:** Black Maxx 600 is guaranteed to maintain a protective film on your driveway surface for a period of six (6) years from date-of-purchase when applied according to our directions. If the product proves to be defective within 6 years of date of purchase, with your original retail receipt, it shall be replaced or refunded on a prorated basis. Gardner-Gibson, Inc. will not be liable for areas that have ponding water, poor drainage problems, or snow removal damage. Failures due to acts of God, fire, structural defects or causes beyond our control are excluded from this guarantee and we are not responsible for labor or other costs incurred in the original or any replacement application. Except as stated above, we make no warranties or guarantees, expressed implied, and none should be inferred. For this guarantee to be valid, products produced by Gardner-Gibson, Inc. must be used for repair. This warranty is only for residential (single family) homes. Two coats must be applied. Not applicable on commercial parking lots. If product wears away before the warranty period, a refund will be made based on the prorated cost vs. the life of the product.

See SDS for more info

Hecho en E.U.A.



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449  
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com