



5002 Elasto Prime™

Primer/Sealer for use before elastomeric coatings

ELASTO PRIME™

- Seals worn surfaces
- Improves coverage of roof coatings
- Applies quickly and easily
- Fast drying

Black Jack® Elasto Prime™ is designed to seal surfaces and act as a primer for worn or older surfaces. This product creates a strong bond between old and new coatings. **Elasto Prime™** is specially formulated to improve the adhesion of white elastomeric roof coatings and enables them to last longer.

PREPARATION: All surfaces must be dry and free of dust, dirt, oil, loose granules, gravel or peeling paint and all other foreign matter. Roofs must have proper ventilation. Rusty metal must be cleaned with a wire brush and primed with rust preventative primer. Pressure washing entire surface is recommended for best results. Repair all leaks and cracks with **Black Jack® Roof Patch** and **Universal Patching Fabric™** in accordance with patching instructions. For best results, use **Elasto Prime™** before applying roof coatings. Surfaces previously coated with aluminum, asphalt or tar coatings, should be allowed to cure for a minimum of one summer season prior to coating with this product. Surfaces with mildew growth or stains must be cleaned with a bleach solution (2 parts water to one part bleach). Be certain all surfaces are thoroughly rinsed and dry prior to applying coating. For longest life, store unused product in a controlled environment, 55 °F-80 °F. Do not store in direct sunlight.

APPLICATION: Surface and air temperatures must be a minimum of 55 °F and rising. DO NOT apply if heavy dew or rain is expected within 24-48 hours. Apply on clear, sunny day in morning hours with a 3/4" nap exterior paint roller. Mix well before using. Do not thin or dilute. Surface must be clean; free of sand, dust, mold, dirt, and loose particles. Using a roller or sprayer, apply a uniform coat of **Elasto Prime™** to the existing surface. Apply additional **Elasto Prime™** on severely worn areas. Allow to cure for 1-2 hours depending on drying conditions. NOT FOR USE ON EPDM OR SOME SINGLE PLY MEMBRANES. ROOFS MUST HAVE PROPER VENTILATION.

COVERAGE RATE: Approximately 50-75 sq. ft. per gal. per coat. Total Coverage for two (2) coat application is 25-35 sq. ft. per gallon.

CLEAN-UP: Clean tools with soap and water.

PRECAUTIONS: For exterior use only. Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. DO NOT allow pail to tumble as this will cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. DO NOT store at temperatures above 100°F. This container is recyclable if cleaned immediately. DO NOT reuse empty containers. Close container when not in use. Do not use on EPDM, Hypalon or PVC surfaces. Do not use on single ply or synthetic roofs. If there is any question regarding compatibility, test a small section first. Do not use in drinking water or food systems. Protect from freezing. For the longest life, store in controlled environment, 35 °F-80 °F. Do not store in direct sunlight.

WARRANTY AND DISCLAIMER: For limited warranty and disclaimer information, contact the Gardner-Gibson, Inc. corporate office at 1-800-237-1155.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
5002-0-30	5 gal.	12" x 12" x 14.75"	5 gal. / 18.9 L	45 lbs.	1 ea.	027134000256

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101