



5175 Silver-Seal 300 Fibered Aluminum Coating

SILVER-SEAL 300

- Protects and preserves roof surfaces
- Reflective silver finish
- Helps reduce roof temps
- Lasts 2-3 times longer than standard black coatings

WHAT IT IS? Black Jack® Silver Seal 300 is a liquid applied, coating that forms a reflective and protective finish to roofs. This blend of asphalt and aluminum forms a bright silver finish that reflects heat and UV rays.

WHAT IT DOES: Provides a protective layer of protection to your roof so it lasts longer.

PREPARATION: All surfaces should be dry, clean, smooth, and in good repair. Surface temperatures should be a minimum of 65°F and rising, not to exceed 110°F. Repair all leaks and problem areas with Roof Patch and Glass Fabric. (See back labels of reinforcement fabrics for specific repair instructions). Properly repair rust areas and prime, before applying this coating. Specific instructions should be followed according to manufacturers recommendations. When applying this product to a newly coated asphalt surface, it is suggested that the surface weather a minimum of one full summer to prevent bleed-through and alligating, unless you are coating over an asphalt emulsion, only a 1 week wait.

FOR BEST RESULTS: DO NOT THIN. MIX CONTENTS WITH A DRILL AND MIXING PADDLE, BEFORE AND DURING APPLICATION FOR PROPER RESULTS. Aluminum pigment and fibers settle out, and complete mixing is necessary to redisperse the pigment to provide a uniform looking finish. A power drill mixer is the best and easiest way to mix this product. In cold weather, store product in heated room (65°F to 80°F) at least 24 hours prior to coating.

NOTE: This product is not recommended for use on wood, asphalt shingles or roofs with slopes less than 1% (or 1/8" per ft.). Standing water dulls aluminum, and may cause adhesion failure between the coating and substrate. In warmer weather, application to steep slopes may result in some running of the coating until fully dry. Avoid foot traffic for longest life. When buying multiple containers, it is recommended to match the batch codes on the lids to avoid shade variances.

APPLICATION: Mix coating and apply evenly by brush or roller to the roof. Spread in both horizontal and vertical directions, overlapping ends of strokes. Avoid excessive build-up or puddling. When brushing, avoid scraping into existing roof surface. All finish strokes should be made in the same direction. **DO NOT APPLY IF RAIN IS EXPECTED WITHIN 24-36 HOURS.** Do not use on EPDM, TPO, PVC or other rubber/synthetic surfaces. Do not use on single ply or synthetic roofs. If there is any question regarding compatibility, test a small section.

COVERAGE RATES: All rates are approximate. Built-up (roll roofing) 1 gal. per 50 sq. ft.; Smooth surface and Metal Roofing - 1 gal. per 75 sq. ft. Avoid foot traffic once applied.

CLEAN-UP: Clean tools with mineral spirits.

PRECAUTIONS: Contains petroleum based products. Keep away from heat, sparks and open flame. For exterior use only. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid prolonged breathing of vapor or spray mist. Do not use in drinking water or food systems. Seal container when not in use. Protective clothing, gloves and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail is upright and secured from tumbling. Do not transport inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and protect for accidental spillage. Protect building ventilation inlet from product fumes. Protect from freezing.

WARRANTY AND DISCLAIMER: This product is believed to be of good quality and to be in accordance with the specifications set forth herein. If the product proves to be defective, it shall be replaced at the cost of the company. Such replacement is and shall be the only liability of the company. The Company is not liable for product failure where poor drainage and ponding water exist. The company shall not be responsible to the consumer or any person for labor costs of any kind or any other costs or damages associated with the product or its installation, application or reapplication or any damages resulting therefrom. This warranty is exclusive and there are no other warranties either expressed or implied, including warranties of fitness or merchantability. No other written or oral representation by any person, entity, dealer, installer or representative of Gardner shall have any force or effect. For additional warranty and disclaimer information, contact the Gardner corporate office at 1-800-237-1155.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
5175-A-34	1 gal.	6.75" x 6.75" x 7.75"	3.6 qt. / 3.4 L	10 lbs.	6/case	027134517518
5175-A-30	5 gal.	12" x 12" x 14.75"	4.75 gal. / 18 L	50 lbs.	1 ea.	027134517556

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101