



5586-1-61 Silicone Silicone Roof Sealant

SILICONE

- Seals and stops leaks
- Permanent seal
- Excellent adhesion
- Heavy duty repair

Black Jack® Silicone Roof Sealant is a white rubber sealant that provides the ultimate waterproofing protection from the elements. This product has exceptional adhesion and flexibility and is compatible with most building materials. Ideal for roof repairs, or on new installations of skylights, windows, doors or vents. In hot or cold climates, this waterproof seal will permanently stretch to prevent cracking and peeling. Cured sealant is mold and mildew resistant.

PREPARATION: Surfaces must be clean and dry.

APPLICATION: Surface and air temperatures must be between 40 °F and 100 °F. Make sure any dew or moist areas have completely dried before applying. Apply sealant to fully cover cracks and damaged areas. For cracks over 1/2" embed a layer of Universal Repair Fabric into the repair areas. Allow to cure 1-2 hours before top coating. DO NOT apply if heavy dew or rain is expected within 2 hours.

COVERAGE: 55 linear feet of 3/16" bead.

CLEAN-UP: Clean tools with mineral spirits.

PRECAUTIONS: For exterior use only. Protect building inlets from product vapors or fumes. DO NOT allow product to freeze. Protective clothing, gloves and eyewear should be used during application of these products. When transporting this product, ensure that plug is tight and tube secure and upright. Do not allow to tumble as this may cause a spill. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure with protective cloths to prevent damage due to accidental spills. For longest life, store in controlled environment, 45 °F to 80 °F. DO NOT store in direct sunlight. DO NOT store at temperatures above 99 °F. Close container after use. DO NOT reuse empty containers. Do not thin.

WARRANTY AND DISCLAIMER: When used in the **Black Jack®** system, it is guaranteed to form a protective coating to your roof for a period of 50 years from the date of purchase. This limited warranty is only applicable when this product is applied to a sound roof according to our directions. If the coating does not perform as stated during the guarantee period, we will provide, with sales receipt, the original purchaser with replacement coating to repair the affected part of the roof. Failures due to acts of God, fire, structural defects or causes beyond our control are excluded from this guarantee. Gardner-Gibson, Inc is not responsible for any labor, property or other consequential damages or costs incurred in the original or any replacement application. Except as stated above, we make no warranties or guarantees, expressed or implied, and none should be inferred.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
5586-1-61	10 fl.oz.	2" x 2" x 11.5"	10 fl.oz. /296 mL	0.8 lbs	12/case	027134558665

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101