



6449 Speed-Coat Advanced Acrylic Blacktop Coating

SPEED-COAT

- Greater Coverage Rate
- Walk on, in 1 hour
- Deep, Rich Black Finish
- Reduces Apply Time
- Low Odor
- Water Clean-up

Black Jack® Speed-Coat Advanced Acrylic Blacktop Coating is an easy applying sealer designed to beautify blacktop and asphalt pavements. It is formulated with 100% acrylic resin, which provides a rich deep black finish. Speed-Coat is designed to improve the look of driveways in good condition. (Not intended for worn driveways with cracks.) Under normal drying conditions, (temperatures above 75°F, clear sunny skies, and humidity below 35%) this driveway sealer can be open to foot traffic in just 1 hour after application. (For vehicle traffic, you must allow 4-6 hours for product to completely cure.)

SURFACE PREPARATION: Newly paved asphalt surfaces must be allowed to cure for a minimum of six months or a full summer's season prior to application of any sealer. Driveways must be cleaned with **Driveway Kleen™**, spray on cleaner & degreaser before sealcoating. For oil stains, apply **Driveway Kleen™** liberally and scrub into surface to penetrate oil spots. This step promotes proper bonding and will help prevent adhesion failures. Repair cracks and holes with **Black Jack® Speed-Fill Elastic Crack Filler** for longest lasting results. For cracks and holes larger than 1" use **Black Jack® Speed-Patch**. For larger potholes use Ready Road Repair Permanent Pot Hole Patch (allow 6 weeks to cure). All repaired areas must be allowed to cure, see product instructions for curing times.

APPLICATION: Temperatures must be at least 65°F and rising, but below 90°F for application. Rinse and clean driveway with driveway cleaner. Properly treat oil spots with cleaners, or coating will not adhere and flake off. After driveway is rinsed thoroughly, allow surface to dry completely before applying this coating to the pavement. Mix thoroughly. A small amount of water separation in the pail is normal. Pour out 1/2 the container and work product across blacktop with roller, brush or squeegee. Allow the coating to penetrate the driveway surface. Working in a small area at a time apply thin coat, brushing away any excess as you seal. Complete the entire driveway in one continuous application to prevent "color shading". Do not over apply, which will result in tracking. Do not apply if rain or cold temperatures are expected within 36 hours. This sealer is not recommended or warranted for use on surfaces which contain a slope greater than 20 degrees. Match batch codes, if possible. Humid or cloudy conditions will prolong curing time. Air temperature of 70-90°F and relative humidity 50% or less must be maintained during and after application to attain 1 hour drying time. Check surface before resuming vehicle traffic.

COVERAGE RATE: Coverage rates vary depending upon the condition of the existing surface. Approximate coverage for driveways in average condition: 125 sq. ft. per gallon (3.07 m² per liter).

CLEAN-UP: While wet, clean tools with warm water and soap. If dry, scrub with citrus based cleaner.

PRECAUTIONS: Do not mix or blend this product with any other driveway products. Protective clothing and eyewear should be used during application of these products, as product may cause skin irritation. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not reuse empty containers. Dispose of in an environmentally acceptable manner. This container is recyclable if cleaned immediately. Do not pour excess product in drains or watercourses. KEEP FROM FREEZING. Do not use in drinking water or food systems. Seal container when not in use.

WARRANTY AND DISCLAIMER: Gardner-Gibson, Inc., warrants this product to give satisfactory results when our directions are followed in its use and application, for a period of 12 months from the date of purchase. In no event however shall the manufacturer be liable for an amount in excess of the purchase price of the product used. If not completely satisfied, return to place of purchase for a refund.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
6449-9-22	2 gal.	9.5" x 9.5" x 9.5"	2 gal. / 7.5 L	19.5 lbs.	36/crtn	027134644924

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101