



Installation Guide: Marble

Elon® **ALWAYS** recommends that all installations be done in accordance with local building codes and adhere to Tile Council of North America specifications.

Preparation

Prior to installation of Natural Marble:

- Open and inspect all marble cartons.
- All cartons should be opened, and material should be separated to allow the installer to layout all pieces and blend them together to give the final installation a uniform color blend, known as "Dry Laid."
- On large jobs, blend material from multiple pallets during Dry Laying.
- When laying out the installation, DO NOT set marble with a "Butt Joint"; Tile Council of North America suggests a minimum 1/16" grout joint.
 - For grout joints 1/16" - 1/8" width, use Unsanded Grout.
 - For grout joints 1/8" - 5/8" width, use Sanded Grout.

Installation

When installing Natural Marble:

- Use a white thinset when installing any light-colored natural stone.
 - Using grey thinset could show trowel ridges or shading through the marble, affecting the finished installation color of natural stones.
- On natural marble with fiberglass backs, always use a quality Latex Modified Thinset to ensure proper adhesion to the fiber back.
- Many manufacturers recommend using latex modified thinset for marble rather than mastics, which may stain and discolor many natural stones.
 - Always follow manufacturers' Limitations and Instructions.
- When used in showers or tubs, Marble should never be set with the bottom course extending into the shower base or tight to tub lip. Always leave a minimum gap of 1/4" above and perpendicular to the floor or lip of the tub or shower base and use a waterproof flexible sealant where they meet per TCNA specification B412-23.
 - This prevents water from wicking up the body of the marble, preventing discoloration.
- For marble shower floors, recommend installations that incorporate a Complete Water Management System (e.g., Bonded Waterproof Tiled Shower Assemblies - Schluter) vs. Traditional shower installations (Mud job).

Grouting

Grouting Natural Marble:

- The use of sanded grouts may cause scratching of polished or high honed marble.
 - When using sanded grout, always conduct a test sample first.
- Pre-Sealing marble prior to grouting helps prevent pigments in grout colors from staining natural stone.
- Pre-sealing makes for easier installation cleanup of grout residue.

Sealing

Sealing Natural Marble and Grout Joints after installation regardless of the finish:

- Always use a high-quality penetrating sealer like *Aqua Mix® Sealers Choice® Gold* to maintain the stone's natural color or a high-quality color-enhancing penetrating sealer like *Aqua Mix® Enrich 'N' Seal™* to enhance the natural color of the stone.
- When sealing natural marble, apply each coat in a different direction (e.g., first coat Left to Right, Second coat Front to Back).
- Multi-sided or 6-sided sealing of material 48 hours before installation will help minimize darkening of Marble on shower floors caused by water absorption and reduce the formation of effervescence and rust.
 - Use on material in areas with excessive moisture exposure: shower floors, marble walls along the base of the shower or tub flange, soap niches.
 - As per National Tile Contractors Association Reference Manual, Custom, or Mapei technical articles.

Common Problems

Common problems in Natural Marble:

- Stain Removal:
 - Sealing marble will help reduce staining.
 - Always clean up spills promptly.
 - Minor stains occurring in natural marble after installation can be removed using a Product like *Aqua Mix® Poultice Stain Remover* per the manufacturer's directions.
- Etching in natural stone:
 - Sealing marble after installation will help minimize etching.
 - Enhancing Sealers may help hide the dullness of some etched stones, but professional repolishing may be required to eliminate it.
- Lippage or uneven surface height issues are often a result of improper installation.
 - Always inspect material for uniform thickness before installation.

Installation is Acceptance

This Tile Installation Guide provided by Elon® Tile & Stone is intended solely for educational purposes. Users must understand that the information herein is not a substitute for professional advice. Elon® Tile & Stone does not assume any responsibility for the accuracy, completeness, or outcomes resulting from the application of the provided guidelines. Users utilize this guide at their own risk. It is imperative to consult with qualified professionals and adhere to specific product guidelines for optimal results. Elon® Tile & Stone, its employees, and affiliates expressly disclaim any liability for direct, indirect, or consequential damages arising from the use of this guide.