

ELON TILE & STONE



TORO SHIELD™

Overview: Toro Shield™ is a safe clear water based acrylic finish designed to be a protective barrier over Toro Saltillo Sealer™. It is easy to apply and safe to strip when needed.

Preperation: All surfaces must be free of efflorescence, grout residue, dirt, oil, wax, grease, moisture, or any existing sealant other than Toro Saltillo Sealer™.

Application: Apply 2 even coats of Toro Shield™ with a sponge mop making sure no puddles are left. Allow each coat to dry to the touch before applying additional coats. Apply in dry weather conditions between 55 & 90 degrees Farenheit.

Coverage: 900 Square Feet Per Gallon per Coat.

Maintenance: Sweep and damp mop floor with Turo Clean™ as needed. Re-apply Toro Shield™ at least once a year. When necessary strip with Toro Clean™ and apply two additional coats of Toro Shield™.

1 QUART



QMX120

1 GALLON



QMX120

5 GALLONS



QMX120

Warning: Avoid contact with skin, eyes, and mucous membranes. May cause burns to skin and eyes. Do not inhale. Do not ingest. Harmful or fatal if swallowed. KEEP OUT OF REACH OF CHILDREN.

First Aid: External - Flush with clear water for at least 15 minutes, if irritation persists, call a physician. Internal - Drink large amounts of water and call a Physician. Eyes - Flush with clear water for at least 15 minutes. Call a physician.

Special Caution: Finished surface will be slippery when wet.

